

## Cable marker - WML HF 5(25X10)R - 0830814

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Cable marker, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: adhesive, cable diameter: ≤ 5 mm, lettering field size: 25 x 10 mm, Number of individual labels: 3000

### Your advantages

- The cable marker labels consist of a self-adhesive marking field and a transparent protective foil
- The cable marker labels do not increase the cross section of the cable, allowing the cable to be subsequently drawn through cable ducts, for example
- The protective foil is wound over the labeling and provides permanent protection against dirt and abrasion
- Resistant to solvents
- Halogen-free

### Key Commercial Data

|              |   |
|--------------|---|
| Packing unit | 1 pc  |
| GTIN         | <br>4 046356 800600 |
| GTIN         | 4046356800600   |

### Technical data

#### Dimensions

|            |         |
|------------|---------|
| Length (b) | 25.4 mm |
| Width (a)  | 2.4 mm  |

#### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -40 °C ... 100 °C   |
| Recommended storage conditions  | 21°C/50% relative humidity. Storage in the original packaging is recommended prior to processing. |

#### General

|                       |            |
|-----------------------|------------|
| Color                 | white      |
| Base element material | Vinyl film |
| Type                  | Label      |

## Cable marker - WML HF 5(25X10)R - 0830814

### Technical data

#### General

|   |   |
|---|---|
| Components  | free from silicone and halogen                        |
| Material  | Polyethylene  |
| RoHS compliant  | Yes   |
| Wipe resistance   | DIN EN 61010-1 (VDE 0411-1)                           |
| Number of individual labels   | 3000  |
| Number of individual labels per row                                 | 3   |
| Adhesive  | Acrylic   |
| Printability  | Thermal transfer                                      |
| Device  | 5146477 THERMOMARK ROLL<br>5146723 THERMOMARK ROLL X1 |
| Ink ribbon  | 5145384 THERMOMARK-RIBBON 110                         |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02                                  |
| Result  | Test passed   |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03                          |
| Test duration   | 96 h  |
| Result of weather resistance test                                   | Test passed   |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02                             |
| Test duration   | 96 h  |
| Salt spray testing result   | Test passed   |
| Alternating condensation climate with SO2 test specification        | DIN 50018:2013-05                                     |
| Climate level   | AHT 1.0 S   |
| Cycles  | 2   |
| Condensation test result  | Test passed   |
| Wipe resistance of test specification inscriptions                  | DIN EN 61010-1 (VDE 0411-1):2011-07                   |
| Result of wipe resistance test                                      | Test passed   |
| Marking mounting type   | adhesive  |

#### Standards and Regulations

|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>