



DB25F AND XLRM WIRING CHART

XLR (CHANNEL)	XLR (DESC.)	PIN 2	PIN 3	PIN 1
1	XLRM	24	12	25
2	XLRM	10	23	11
3	XLRM	21	9	22
4	XLRM	7	20	8
5	XLRM	18	6	19
6	XLRM	4	17	5
7	XLRM	15	3	16
8	XLRM	1	14	2

WIRING REPEATED FOR CHANNELS "9-16" & "17-36"

NOTES:

- MATERIALS:
FRONT PANEL - ALUMINUM ALLOY, BLUE ANODIZED
REAR COVER - ALUMINUM ALLOY, UNPLATED
XLR CONNECTORS:
HOUSING - ZINC DYCAST
CONTACTS - COPPER ALLOY, SILVER PLATED

DB25 CONNECTORS:
BODY - STEEL, NICKEL PLATED
CONTACTS - COPPER ALLOY, SILVER PLATED
CONNECTOR INSULATOR - BLACK THERMOPLASTIC
PCB - FR4
- THIS PRODUCT IS RoHS COMPLIANT

CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
1. ALL DIMENSIONS IN INCHES [mm]					SIZE	WIDTH	MULT	LBS/M	TEMPER
- TWO PLACE DECIMALS ±0.02 [0.5]					FINISH				MATERIAL
- THREE PLACE DECIMALS ±0.005 [0.13]					SPEC No.				SPEC No.
					FIRST USED ON				SCALE
					DATE DRAWN				3:5
					6/21/16	AB	6/21/16	10-3-16	
					NAME IO PANEL, ALL FRONT, 24 MALE QG TO 3 DB25, RoHS				PART No.
									AP24MX3DB25F
									REV
									A