

Passive module - VIP-2/PT/FLK50/MODI-TSX/Q - 2904285

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



VARIOFACE interface module, with Push-in connection for MODICON® TSX Quantum, with MODICON®-specific labeling, for I/O of 32 channels



Key commercial data

| | |
|--------------------------------------|---------------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 223.1 GRM |
| Custom tariff number | 85369010 |
| Country of origin | United States |

Technical data

Dimensions

| | |
|--------|----------|
| Width | 107.9 mm |
| Height | 72.1 mm |
| Depth | 56 mm |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

General

| | |
|---|-----------------------|
| Nominal voltage U_N | 60 V AC/DC |
| Max. current carrying capacity per branch | 1 A |
| Number of positions | 50 |
| Status display | No |
| Test voltage | 500 V (50 Hz, 1 min.) |
| Mounting position | any |
| Standards/regulations | IEC 60664 |

Passive module - VIP-2/PT/FLK50/MODI-TSX/Q - 2904285

Technical data

General

| | |
|------------------------|--------------|
| | DIN EN 50178 |
| | IEC 62103 |
| Pollution degree | 2 |
| Surge voltage category | II |
| Rated surge voltage | 0.6 kV |

Connection data for connection 1

| | |
|--|----------------------|
| Connection name | Field level |
| Connection method | Push-in connection |
| Conductor cross section solid min. | 0.14 mm ² |
| Conductor cross section solid max. | 2.5 mm ² |
| Conductor cross section stranded min. | 0.14 mm ² |
| Conductor cross section stranded max. | 2.5 mm ² |
| Conductor cross section AWG/kcmil min. | 26 |
| Conductor cross section AWG/kcmil max | 14 |
| Stripping length | 8 mm |

Connection data for connection 2

| | |
|-----------------------|-----------------------------|
| Connection name | Control system level |
| Number of connections | 1 |
| Connection method | IDC/FLK pin strip (2.54 mm) |
| Number of positions | 50 |

Supported controller

| | |
|---------------------|--|
| Controller | Schneider Electric MODICON TSX QUANTUM |
| - suitable I/O card | DDI 353 |
| | DDI 841 |
| | DDI 853 |
| | DAI 340 |
| | DAI 353 |
| | DAI 440 |
| | DAI 453 |
| | DDO 353 |
| | DDM 390 |
| | ACI 030 |
| | ACI 040 |
| | ATI 030 |
| | ARI 030 |
| | AVI 030 |

Passive module - VIP-2/PT/FLK50/MODI-TSX/Q - 2904285

Technical data

Supported controller

| | |
|--|---------|
| | ACO 020 |
| | ACO 130 |
| | AVO 020 |
| | EHC 105 |
| | EHC 202 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250313 |
| eCl@ss 4.1 | 27250313 |
| eCl@ss 5.0 | 27250313 |
| eCl@ss 5.1 | 27250313 |
| eCl@ss 6.0 | 27242608 |
| eCl@ss 7.0 | 27141152 |
| eCl@ss 8.0 | 27141152 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001604 |
| ETIM 4.0 | EC001423 |
| ETIM 5.0 | EC002780 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211824 |
| UNSPSC 7.0901 | 39121421 |
| UNSPSC 11 | 39121421 |
| UNSPSC 12.01 | 39121421 |
| UNSPSC 13.2 | 39121421 |

Approvals

Approvals

Approvals

CSA / UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Passive module - VIP-2/PT/FLK50/MODI-TSX/Q - 2904285

Approvals

Approvals submitted

Approval details

| | |
|--------------------------------|-------|
| CSA | |
| mm ² /AWG/kcmil | 26-14 |
| Nominal current I _N | 1 A |
| Nominal voltage U _N | 125 V |

| | |
|--------------------------------|-------|
| UL Recognized | |
| mm ² /AWG/kcmil | 26-14 |
| Nominal current I _N | 1 A |
| Nominal voltage U _N | 125 V |

| | |
|--------------------------------|-------|
| cUL Recognized | |
| mm ² /AWG/kcmil | 26-14 |
| Nominal current I _N | 1 A |
| Nominal voltage U _N | 125 V |

| | |
|------------------|--|
| cULus Recognized | |
|------------------|--|

Drawings

Passive module - VIP-2/PT/FLK50/MODI-TSX/Q - 2904285

Circuit diagram

