

## EnviroSense2 (E2) Environmental Sensor Module with Temperature and Digital Inputs

MODEL NUMBER: E2MTDI



Monitors ambient temperature conditions, as well as contact closures from alarm, security and telecom products.

### Description

The E2MTDI E2 Environmental Sensor Module works with Tripp Lite LX Platform devices, including WEBCARDLX, WEBCARDLXS, PDU3XE-Series PDUs and PDU3E-Series PDUs. By connecting the included USB cable to an LX Platform device, the E2MTDI allows you to remotely monitor ambient temperature conditions in network environments. It also monitors, via dry contact interface, contact closure status of two compatible products, such as smoke detectors, fire alarms and security systems.

If temperature values exceed a certain limit or monitored contacts change state, it is recorded in the event log of the LX Platform device's PowerAlert® Device Manager interface. The E2MTDI mounts magnetically to most racks and cabinets. Up to three E2 modules can be daisy-chained together. A built-in retention harness secures cable connections to reduce clutter.

### Features

#### Compatible with Tripp Lite LX Platform Devices

- Compatible devices include WEBCARDLX, WEBCARDLXS, PDU3XE-Series PDUs and PDU3E-Series PDUs
- Measures and monitors ambient temperature
- Monitors contact closure status of alarm, security and telecom products
- Only dry contact open/closed connection allowed

#### Easy to Install and Operate

- Attaches magnetically to most racks and cabinets
- Up to 3 E2 modules can be daisy-chained together

### Highlights

- Compatible with Tripp Lite LX Platform devices
- Easy magnetic mounting to most racks and cabinets
- Up to 3 E2 modules can be daisy-chained together
- Built-in cable harness reduces clutter
- USB cable included

### Package Includes

- E2MTDI EnviroSense2 Environmental Sensor Module
- USB cable (A/Micro-B), 3 ft.
- Owner's manual



- Built-in cable harness reduces clutter
- USB cable included
- Compatible with Tripp Lite's free downloadable PowerAlert software

## Specifications

OVERVIEW	
UPC Code	037332196255
Power Management Type	Sensors
INPUT	
Cable Length (ft.)	3
PHYSICAL	
Shipping Dimensions (hwd / cm)	2.79 x 10.92 x 15.24
Shipping Dimensions (hwd / in.)	1.10 x 4.30 x 6.00
Shipping Weight (kg)	0.13
Shipping Weight (lbs.)	0.29
CONNECTIONS	
Side A - Connector 1	USB A (FEMALE)
Side B - Connector 1	MICRO-USB B (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>