

Specification Sheet

Part Number: T120I0HSH4



Heavy Duty Cable Tie, 11.8" Long, UL Rated, 120lb Tensile Strength, PA66HS, Black, 500/pkg

| | |
|---------------------|---|
| Article Number | 111-12216 |
| Type | T120I |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">• Heat stabilized heavy-duty cable ties provide excellent resistance to high heat exposures.• Head design provides high tensile strength with very low insertion force.• Bent tail ensures a quick and simple installation. |
| Quantity Per | bag |

Product Description

Heavy-Duty T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

| | |
|--|--|
| Short Description | Heavy Duty Cable Tie, 11.8" Long, UL Rated, 120lb Tensile Strength, PA66HS, Black, 500/pkg |
| Global Part Name | T120I-PA66HS-BK |
| Minimum Tensile Strength (Imperial) | 120.0 |
| Minimum Tensile Strength (Metric) | 535.0 |
| Length L (Imperial) | 11.8 |
| Length L (Metric) | 300.0 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.30 |
| Width W (Metric) | 7.6 |
| Bundle Diameter Min (Imperial) | 0.20 |
| Bundle Diameter Min (Metric) | 5.0 |
| Bundle Diameter Max (Imperial) | 3.2 |
| Bundle Diameter Max (Metric) | 81.3 |

| | |
|--|--|
| Thickness T (Metric) | 1.6 |
| Cable Tie Width Max (Imperial) | 0.3 |
| Cable Tie Width Max (Metric) | 7.61 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS |
| Flammability | UL 94 V2 |
| Halogen free | Yes |
| Operating Temperature (Metric) | -40°F to +257°F (-40°C to +125°C) |
| ROHS Complaint | Yes |
| Certification/Specification WEB | UL-ZODZ2.E64139 |
| UL Recognized (US) | Yes |
| UL Listed (US and Canada) | Yes |
| UL Recognized (US and Canada) | Yes |
| UL Listed (US) | Yes |
| Package Quantity(Imperial) | 500 |

Package Quantity (Metric)

500

Customs Number

3926909988