



Labeling plate for potentiometer, black label, white font, with inscription: 0...10, Outer diameter 40 mm

| | |
|---|--------------------------------------|
| product brand name | SIRIUS ACT |
| product designation | Labeling plate |
| design of the product | for potentiometers |
| product type designation | 3SU1 |
| General technical data | |
| protection class IP | IP66, IP67, IP69(IP69K) |
| shock resistance for railway applications according to EN 61373 | Category 1, Class B |
| vibration resistance for railway applications according to EN 61373 | Category 1, Class B |
| Substance Prohibittance (Date) | 10/01/2014 |
| Ambient conditions | |
| ambient temperature | |
| • during operation | 70 ... -25 °C |
| • during storage and transport | 80 ... -40 °C |
| Accessories | |
| material of accessory | Plastic |
| fastening method of label | without |
| marking of the name plate for command devices | SYMBOL: 0 ... 10 (for potentiometer) |
| shape of the name plate for command devices | round |
| color of the label | black (plate); white (text) |
| printed ISO symbols | SYMBOL: 0 ... 10 (for potentiometer) |
| Certificates/ approvals | |
| General Product Approval | Declaration of Conformity |



[Confirmation](#)



EG-Konf.

Test Certificates **Marine / Shipping**

[Type Test Certificates/Test Report](#)



ABS



LRS



PRS



RINA



RMRS

other

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1900-0BG16-0SA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1900-0BG16-0SA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1900-0BG16-0SA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1900-0BG16-0SA0&lang=en

last modified:

3/29/2022 