

### **TOM-2.5GMR-SR1-C**

Infinera® TOM-2.5GMR-SR1 Compatible TAA Compliant 2.5GBase-LX SFP Transceiver (SMF, 1310nm, 10km, LC, DOM)

#### **Features:**

- INF-8074 and SFF-8472 Compliance
- Duplex LC Connector
- Single-mode Fiber
- Commercial Temperature 0 to 70 Celsius
- Hot Pluggable
- Metal with Lower EMI
- Excellent ESD Protection
- RoHS Compliant and Lead Free



#### **Applications:**

- OC-48 Transmission
- Access and Enterprise

#### **Product Description**

This Tellabs® TOM-2.5GMR-SR1 compatible SFP transceiver provides OC-48 (2488mbps) transmission rates for up to 15km over single-mode fiber (SMF) using a wavelength of 1310nm via an LC connector. It is guaranteed to be 100% compatible with the equivalent Tellabs® transceiver. This easy to install, hot swappable transceiver has been programmed, uniquely serialized and data-traffic and application tested to ensure that it will initialize and perform identically. Digital optical monitoring (DOM) support is also present to allow access to real-time operating parameters. This transceiver is Trade Agreements Act (TAA) compliant. We stand behind the quality of our products and proudly offer a limited lifetime warranty.

ProLabs's transceivers are RoHS compliant and lead-free.

TAA refers to the Trade Agreements Act (19 U.S.C. & 2501-2581), which is intended to foster fair and open international trade. TAA requires that the U.S. Government may acquire only "U.S. – made or designated country end products."



## Regulatory Compliance

- ESD to the Electrical PINs: compatible with MIL-STD-883E Method 3015.4
- ESD to the LC Receptacle: compatible with IEC 61000-4-3
- EMI/EMC compatible with FCC Part 15 Subpart B Rules, EN55022:2010
- Laser Eye Safety compatible with FDA 21CFR, EN60950-1& EN (IEC) 60825-1,2
- RoHS compliant with EU RoHS 2.0 directive 2015/863/EU

## Absolute Maximum Ratings

| Parameter                  | Symbol           | Min. | Max. | Unit |
|----------------------------|------------------|------|------|------|
| Maximum Supply Voltage     | Vcc              | -0.5 | 3.6  | V    |
| Storage Temperature        | TS               | -40  | +85  | °C   |
| Operating Case Temperature | Tc               | 0    | +70  | °C   |
| Operating Humidity         | RH               | 0    | 95   | %    |
| Receiver Power             | R <sub>MAX</sub> |      | -3   | dBm  |
| Data Rate                  |                  |      | 2.5  | Gbps |

## Electrical Characteristics (TOP=25°C, Vcc=3.3Volts)

| Parameter                      | Symbol | Min. | Typ. | Max. | Unit | Notes |
|--------------------------------|--------|------|------|------|------|-------|
| Power Supply Voltage           | Vcc    | 3.15 | 3.30 | 3.45 | V    |       |
| Power Supply Current           | Icc    |      |      | 300  | mA   |       |
| <b>Transmitter</b>             |        |      |      |      |      |       |
| Single ended data input swing  | Vin    | 400  |      | 1600 | mVpp | 1     |
| Input differential impedance   | Zin    | 85   | 100  | 115  | Ω    | 2     |
| <b>Receiver</b>                |        |      |      |      |      |       |
| Single ended data output swing | Vout   | 400  | 800  | 1200 | mVpp | 1     |
| Output differential impedance  | Zin    | 85   | 100  | 115  | Ω    |       |

### Notes:

1. AC coupled.
2. Rin > 100 kohms @ DC

## Optical Characteristics

| Parameter                             | Symbol                | Min.  | Typ. | Max. | Unit | Notes |
|---------------------------------------|-----------------------|-------|------|------|------|-------|
| 9µm Core Diameter SMF                 | L                     |       | 10   |      | km   |       |
| Data Rate                             |                       |       |      | 2.5  | Gbps |       |
| <b>Transmitter</b>                    |                       |       |      |      |      |       |
| Average Output Power                  | P <sub>out</sub>      | -11.7 |      | -3   | dBm  | 1     |
| Optical Extinction Ratio              | ER                    | 8.2   |      |      | dB   | 2     |
| Optical Wavelength                    | Tλ                    | 1260  | 1310 | 1360 | nm   |       |
| Spectral Width (RMS)                  | Δλ                    |       |      | 3    | nm   |       |
| P <sub>out</sub> @TX Disable Asserted | P <sub>out</sub>      |       |      | -45  | dBm  |       |
| Rise/Fall Time (20%~80%)              | tr/tf                 |       |      | 150  | ns   |       |
| Total Jitter                          | TJ                    |       |      | 0.07 | UI   | 2     |
| Output Optical Eye                    | ITU-T G.957 Compliant |       |      |      |      |       |
| <b>Receiver</b>                       |                       |       |      |      |      |       |
| Receiver Sensitivity                  | P <sub>min</sub>      |       |      | -18  | dBm  | 3     |
| Receiver Overload                     | P <sub>max</sub>      | -3    |      |      | dBm  |       |
| Optical Center Wavelength             | λ <sub>C</sub>        | 1260  |      | 1600 | nm   |       |
| LOS De-Assert                         | LOSD                  |       |      | -19  | dBm  |       |
| LOS Assert                            | LOSA                  | -30   |      |      | dBm  |       |
| LOS Hysteresis                        |                       | 0.5   |      |      | dB   |       |

### Notes:

1. Output power is measured by coupling into a 9/125 single-mode fiber.
2. Filtered, measured with a PRBS 2<sup>23</sup>-1 test pattern @2500Mbps.
3. Minimum average optical power is measured at BER less than 1E-12, with 2<sup>23</sup>-1 PRBS and ER=9 dB

## Pin Descriptions

| Pin | Symbol     | Name/Descriptions  | Ref. |
|-----|------------|--|------|
| 1   | VeeT       | Transmitter Ground (Common with Receiver Ground).                              | 1    |
| 2   | TX Fault   | Transmitter Fault. LVTTTL-O  | 2    |
| 3   | TX Disable | Transmitter Disable. Laser output disabled on high or open. LVTT-I.            | 3    |
| 4   | SDA        | 2-Wire Serial Interface Data Line (Same as MOD-DEF2 in INF-8074i). LVTTTL-I/O. |      |
| 5   | SCL        | 2-Wire Serial Interface Data Line (Same as MOD-DEF2 in INF-8074i). LVTTTL-I.   |      |
| 6   | MOD_ABS    | Module Absent, Connect to VeeT or VeeR in Module.                              | 4    |
| 7   | RS0        | Rate Select 0. Not used  | 5    |
| 8   | LOS        | Loss of Signal indication. Logic 0 indicates normal operation. LVTTTL-O.       | 2    |
| 9   | RS1        | Rate Select 1. Not used  | 5    |
| 10  | VeeR       | Receiver Ground (Common with Transmitter Ground).                              | 1    |
| 11  | VeeR       | Receiver Ground (Common with Transmitter Ground).                              | 1    |
| 12  | RD-        | Receiver Inverted DATA out. AC Coupled. CML-O.                                 |      |
| 13  | RD+        | Receiver Non-inverted DATA out. AC Coupled. CML-O.                             |      |
| 14  | VeeR       | Receiver Ground (Common with Transmitter Ground).                              | 1    |
| 15  | VccR       | Receiver Power Supply.   |      |
| 16  | VccT       | Transmitter Power Supply.  |      |
| 17  | VeeT       | Transmitter Ground (Common with Receiver Ground).                              | 1    |
| 18  | TD+        | Transmitter Non-Inverted DATA in. AC Coupled. CML-I.                           |      |
| 19  | TD-        | Transmitter Inverted DATA in. AC Coupled. CML-O.                               |      |
| 20  | VeeT       | Transmitter Ground (Common with Receiver Ground).                              | 1    |

### Notes:

1. The module signal ground contacts, VeeR and VeeT, should be isolated from the module case.
2. This contact is an open collector/drain output and should be pulled up to the Vcc\_Host with resistor in the range 4.7K $\Omega$  to 10K $\Omega$ . Pull ups can be connected to one or several power supplies, however the host board design shall ensure that no module contract has voltage exceeding module VccT/R +0.5.V.
3. Tx\_Disable is an input contact with a 4.7K $\Omega$  to 10K $\Omega$  pull-up resistor to VccT inside module.
4. Mod\_ABS is connected to VeeT or VeeR in the SFP+ module. The host may pull the contract up to Vcc\_Host with a resistor in the range from 4.7K $\Omega$  to 10K $\Omega$ . Mod\_ABS is asserted "High" when the SFP+ module is physically absent from a host slot.
5. Internally pulled down per SFF-8431



Pin-out of connector Block on Host board

### Recommended Circuit Schematic



### Mechanical Specifications

Small Form Factor Pluggable (SFP) transceivers are compatible with the dimensions defined by the SFP Multi-Sourcing Agreement (MSA).



### EEPROM Information

EEPROM memory map specific data field description is as below:



## **About ProLabs**

Our experience comes as standard; for over 15 years ProLabs has delivered optical connectivity solutions that give our customers freedom and choice through our ability to provide seamless interoperability. At the heart of our company is the ability to provide state-of-the-art optical transport and connectivity solutions that are compatible with over 90 optical switching and transport platforms.

## **Complete Portfolio of Network Solutions**

ProLabs is focused on innovations in optical transport and connectivity. The combination of our knowledge of optics and networking equipment enables ProLabs to be your single source for optical transport and connectivity solutions from 100Mb to 400G while providing innovative solutions that increase network efficiency. We provide the optical connectivity expertise that is compatible with and enhances your switching and transport equipment.

## **Trusted Partner**

Customer service is our number one value. ProLabs has invested in people, labs and manufacturing capacity to ensure that you get immediate answers to your questions and compatible product when needed. With Engineering and Manufacturing offices in the U.K. and U.S. augmented by field offices throughout the U.S., U.K. and Asia, ProLabs is able to be our customers best advocate 24 hours a day.

## **Contact Information**

ProLabs US

Email: [sales@prolabs.com](mailto:sales@prolabs.com)

Telephone: 952-852-0252

ProLabs UK

Email: [salessupport@prolabs.com](mailto:salessupport@prolabs.com)

Telephone: +44 1285 719 600