

## Specification Sheet

Part Number: 156-01657

Patented retention design on clip features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement. Controlled flex and angled entry promote easy installation.

Independent rotation allows for adjustable routing orientation.

Cable tie accommodates wide range of secondary bundle sizes.



MOC Clip, 8 mm, Assembled to T50SMVC Swivel Tie, PA66HIRHSUV, Black, 1000/ctn

Article Number 156-01657

Type T50SMVCMOC8M

Color Black (BK)

Quantity Per carton

**Product Description** The MOC to Swivel Tie is a rotatable routing clip coupled to a cable tie that keeps two routings secured and separated. Tie provides additional security against axial slip by clamping around solid tube, pipe or harness. The swivel coupler allows the two routings to rotate independently of each other.

**Short Description** MOC Clip, 8 mm, Assembled to T50SMVC Swivel Tie, PA66HIRHSUV, Black, 1000/ctn

Global Part Name T50SMVCMOC8M-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 0.60

Length L (Metric) 15.2

Fixation Method Omega Clips

Identification Plate Position none

Bundle Diameter Min (Imperial) 0.28

Bundle Diameter Min (Metric) 7.0

Bundle Diameter Max (Imperial) 0.35

Bundle Diameter Max (Metric) 9.0

Height H (Imperial) 1.03

Height H (Metric) 26.1

Depth D (Imperial) 0.39

Depth D (Metric) 10.0

|                             |                                                                          |
|-----------------------------|--------------------------------------------------------------------------|
| Material                    | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut           | PA66HIRHSUV                                                              |
| Flammability                | UL 94 HB                                                                 |
| Halogen Free                | Yes                                                                      |
| UV Resistant (Yes/No)       | Yes                                                                      |
| Operating Temperature       | -40°F to +230°F (-40°C to +110°C)                                        |
| ROHS Compliant              | Yes                                                                      |
| Package Quantity (Imperial) | 1000                                                                     |
| Package Quantity (Metric)   | 1000                                                                     |
| Customs Number              | 3926909988                                                               |