



ITEM	DIM	ALTERNATE
W	24.00 <sup>+0.30</sup> <sub>-0.30</sub>	
E	1.75 <sup>+0.10</sup> <sub>-0.10</sub>	
F	11.50 <sup>+0.10</sup> <sub>-0.10</sub>	
P	12.00 <sup>+0.10</sup> <sub>-0.10</sub>	
P0	4.00 <sup>+0.10</sup> <sub>-0.10</sub>	
P2	2.00 <sup>+0.10</sup> <sub>-0.10</sub>	
<del>D0</del>	<del>∅1.50<sup>+0.10</sup><sub>-0.00</sub></del>	
T	0.5 <sup>+0.05</sup> <sub>-0.05</sub>	
A0	6.50 <sup>+0.10</sup> <sub>-0.10</sub>	
B0	7.40 <sup>+0.10</sup> <sub>-0.10</sub>	
K0	8.50 <sup>+0.10</sup> <sub>-0.10</sub>	

- (1) 任意10个扣链齿轮孔的累计误差不得超过±0.20mm;  
 10 sprocket hole pitch cumulative tolerance ±0.20 .  
 (2) 材料厚度以载带边缘测量为准;  
 Material thickness measure based on Carrier edge.  
 (3) 载带长度方向250mm距离的非平行度不得超过1mm;  
 Carrier camber is within 1 mm in 250mm.  
 (4) 未注公差为:±0.1mm.  
 Unmark tolerance:±0.1mm.  
 (5) 未注脱模斜度为:5° .  
 Unmark pattern draft :5° .  
 (6) 所有尺寸符合EIA-481-D版本。  
 All dimensions meet EIA-481-D requirements.  
 (7) 材料: 透明PS  
 Material: **Transparent PS**  
 (8) 卷轮: 13"\*4", 卷轮料号: 9640124, 载带长度: 8.532 M/卷, 载带料号: 9641083.  
 Reel: 13"\*4", Reel P/N: 9640124, Carrier Length: 8.532 M/R, Carrier P/N: 9641083.  
 (9) 包装颗数: 650 PCS/卷 (不包括前空 14 PCS后空 47 PCS)  
 Package quantity:650PCS/R, (Don't include 14pcs in the core and 47pcs in the end.)  
 (10) 最外圈需要保护带。  
 Need protective belt in the last circle.  
 (11) 产品料号: 67SLG060080070P100  
 PRODUCT PN: 67SLG060080070P100

ZONE	REV.	DESCRIPTION	DATE	APPD.
3				
2				
1				

STANDARD TOLARENCE EXCEPT NOTED		APPD:	PAGE:		PART NO:	PART NAME:
0.5-0.5:±0.05	0.5-1.5:±0.1	CHG:	1/1		67-SLG-060-080-070-P100	Soft SMD Grounding Contacts
0.5-0.5:±0.05	1.5-2.80	SCALE:	ND SCALE	REV:		DWG NO:
0.9-2.80:±0.3	280-1000	UNIT:	mm	0		SCALE:
2.0-25	±0.5	ANG	90°	DESIGN:	Peter Huang	DATE: