


REVISIONS

REV	ECR	DESCRIPTION	DRAWN	DATE
1		ENGINEERING RELEASE	P. BURDGE	09/10/2020

-XX IN THE ENDING OF THE CABLE PART NUMBER IS CALLING OUT THE LENGTH OF THE ASSEMBLY FROM CENTER TO CENTER OF CONNECTORS. EXAMPLES SHOWN BELOW:

LTI P/N: CB1.17LL-2IPX4L-3IN-6O (3 INCHES)
 CB1.17LL-2IPX4L-6.5IN-6O (6.5 INCHES)




Inches	Millimeters
0 - 2IN +/- 0.040	0 - 51 +/- 1
2IN - 6IN +/- 0.080	51 - 153 +/- 2
6IN - 12IN +/- 0.140	153 - 305 +/- 3.5
12IN - 48IN +/- 0.250	305 - 1219 +/- 6.4
48IN - 144IN (12FT) +/- 0.500	1219 - 3658 +/- 13
144IN (12FT) - ABOVE +/- 1.0	3658 - ABOVE +/- 25

UNLESS OTHERWISE SPECIFIED ON DRAWING

ITEM	PART NUMBER	DESCRIPTION	QTY
1	1.17LL MICRO COAX	CABLE, 1.17LL (LOW LOSS) MICRO COAX, BLACK	AR
2	IPX4LLF11GPB-113	IPX4L (MHF4L), RHT ANGLE, JACK, CABLE CRIMP	2

MHF IS A REGISTERED TRADEMARK OF I-PEX CO., LTD. CORPORATION

DO NOT SCALE DRAWING		 Lighthouse Technologies San Diego, CA WWW.RFCONNECTOR.COM	
TOLERANCES UNLESS OTHERWISE SPECIFIED			
DIMENSIONS ARE IN MILLIMETERS X = ±0.5 X.X = ±0.25 X.XX = ±0.13 ANGLE = ±30'		TITLE: CABLE ASSY, IPX4L (MHF4L), R/A JACK, TO IPX4L (MHF4L), R/A JACK, 1.17LL (LOW LOSS) MICRO COAX, GRAY, OPPOSITE ORIENTATION	
THIRD ANGLE PROJECTION		CUSTOMER APPROVAL	
SIGN / DATE:		SIZE	PART/DWG. NO:
ENG APPR.		B	CB1.17LL-2IPX4L-XXIN-6O
CHECKED		SCALE: 4:1	FILE NAME
DRAWN	P. BURDGE	09/10/2020	REV
	NAME	DATE	1
		SHEET 1 OF 1	

PROPRIETARY AND CONFIDENTIAL

UNLESS OTHERWISE SPECIFIED: THIS DOCUMENT CONTAINS LIGHTHORSE TECHNOLOGIES INFORMATION. REPRODUCTION, USE, DISCLOSURE OR TRANSMITTAL OF ALL OR ANY PART OF THIS DOCUMENT IS PROHIBITED EXCEPT TO THE EXTENT APPROVED IN WRITING BY AN AUTHORIZED REPRESENTATIVE OF LIGHTHORSE TECHNOLOGIES. LIGHTHORSE TECHNOLOGIES RESERVES ALL RIGHTS UNDER PATENTS, TRADEMARKS, COPY RIGHTS AND TRADE SECRETS. COPY RIGHTS OF LIGHTHORSE TECHNOLOGIES 2011, ALL RIGHTS RESERVED.

