



NOTE
FACE VIEW
ON CONNECTOR

SPECIFICATION
 MATERIALS:
 HOUSING: PBT
 INSERT: PBT
 COUPLING: BRASS-NICKEL PLATED
 O-RING: VITON
 ELECTRICAL:
 VOLTAGE: 10-30VDC
 CURRENT RATING: 4A PER PORT, 12 AMPS MAX.
 PROTECTION CLASS: IP67
 OPERATING TEMPERATURE: -25°C to +90°C

NOTES:
FIXING HOLES TO SUIT M4 SCREWS

MATERIAL NUMBER	OLD PART NUMBER
1201140085	BTX803PC

DESCRIPTION EC NO: WEU2010-0450 DRWN: REISSNER 2010/03/22 CHKD: FP APPR: NSTAUDIG 2010/03/23	QUALITY SYMBOLS ▽ = 0 ∇ = 0	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ±--- ±--- 3 PLACES ±--- ±--- 2 PLACES ±--- ±--- 1 PLACE ±0.3 ±--- ANGULAR ± --- °	DIMENSION STYLE MM ONLY	SCALE 1:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
	DRAWN BY REISSNER	DATE 2010/03/22	MICRO-CHANGE MPIS 8 PORT TOP MOUNT 19POLE M23 MALE CONNECT.			
	CHECKED BY NS	DATE 2010/03/22				
	APPROVED BY NSTAUDIG	DATE 2010/03/23	MOLEX INCORPORATED			
MATERIAL NO.	DOCUMENT NO. SD-120114-087	SHEET NO. 1 OF 1	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			