
## **HellermannTyton**

## **Specification Sheet**

Part Number: 184-22028



Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High-Density Slotted-Wall Wiring Duct, 2" x 5", Non-Adhesive, PVC, Intrinsic Blue, 120 ft/ctn

Article Number	184-22028

Type SLHD2X5

Color Intrinsic Blue (IBU)

Quantity Per carton

**Product Description** 

Manufactured from the same PVC material as standard Pro-Duct colors, HellermannTyton also offers an intrinsic blue color option. The intrinsic blue color indicates that the wiring contained in the duct runs to intrinsically safe components in the control panel. HellermannTyton Pro-Duct High-Density, Slotted-Wall Wiring Duct features narrow fingers equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description	High-Density Slotted-Wall Wiring Duct, 2" x 5", Non-Adhesive, PVC, Intrinsic Blue, 120 ft/ctn
Global Part Name	SLHD2X5-PVC-BU
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	2.0
Width W (Metric)	50.8
Height H (Imperial)	5.07
Height H (Metric)	128.8
Mounting Hole Centers (Imperial)	2.0
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC

Flammability Self-extinguishing

**Halogen Free** No

Operating Temperature +122°F (+50°C)

Reach Compliant (Article 33)

No

ROHS Compliant

Yes

**Certification/Specification**UL EN 50085-1:2005 + A1:2013 EN 50085-2-3\_1A CSA

UL Recognized (US) Yes

Package Quantity (Imperial) 120

Package Quantity (Metric) 36.58

Customs Number 3925900000

© 2021 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions