


TOLERANCE UNLESS OTHERWISE SPECIFIED					
.X	±0.25				
.XX	±0.13				
.XXX	±0.05				

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL



NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, NICKEL PLATED

CONTACT: COPPER ALLOY, 30µ" GOLD PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C

40A (CURRENT) POWER/CO-AX CONTACT RATING:

(IF PRESENT)


SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT

SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: 5000MΩ min.

DIELECTRIC

WITHSTANDING VOLTAGE: 1000V AC rms



— 11.9 4						
3.20				1114		0

COMBINATION D-SUB



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

	SW REFERENCE NO.: 629 C	OMBO ASSEMBLY				
	DRAWN: C.B	DATE: JAN. 01/2019				
	CHECKED:	DATE:				
	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 2				
ĺ	DRAWING NUMBER: 620 43W2640 4N5					

DRAWING NUMBER: 629-43W2640-4N5 ISSUE PART NUMBER: 629-43W2640-4N5



TOLERANCE UNLESS OTHERWISE SPECIFIED

.X ±0.25 .XX ±0.13 .XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER (1) ORIGINAL

00 2W2

2WK2

ಂ೧್≎

5W1

00000 3W3

000 3WK3

0...0 7W2

...o...

11W1

00000 5W5

00000000 8W8

9W4

0000

13W3

0:::::::0

..... 21W1

17W2

000000:::

13W6

(00:::::000 lo 17W5

000:::::0

O :::::::::::: 27W2

25W3

0000000

21W4

00000000 24W7

36W4

......

47W1

COMBINATION D-SUB

YOUR CONNECTION TO QUALITY & SERVICE

EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

629 COMBO ASSEMBLY SW REFERENCE NO.: DRAWN: DATE: JAN. 01/2019 CHECKED: DATE: SHEET 2 OF 2 SCALE: N.T.S ISSUE

629-43W2640-4N5 DRAWING NUMBER: PART NUMBER: 629-43W2640-4N5