NSYTBP775

PC box IP66 IK08 RAL7035 Int.H65W65D45 Ext.H74W74D56 opaque PC cover H10





Main Range

| Range | Thalassa | |
|-------------------------|---|--|
| Product name | Thalassa TBP | |
| Device Application | Multi-purpose | |
| Category | Industrial box | |
| Height | 2.91 in (74 mm) | |
| Width | 2.91 in (74 mm) | |
| Depth | 2.13 in (54 mm) | |
| Internal height | 2.56 in (65 mm) | |
| Internal width | 2.56 in (65 mm) | |
| Internal depth | 1.85 in (47 mm) | |
| Enclosure mounting | Wall mounted | |
| Device composition | 1 body 1 cover 4 cover screw | |
| Quantity per Set | Set of 5 | |
| Body type | One piece moulded | |
| Type of front cover | Low plain cover | |
| | • | |
| Cover fixing | Metal screws | |
| Cover fixing Lock type | Metal screws Captive screw flat outside sealed area | |
| | | |

Complementary

| Material | polycarbonate | |
|-----------------------------|------------------------|--|
| Color | Gray RAL 7035) | |
| Standards | IEC 62208 UL 508 A | |
| Product Certifications | TÜV UL | |
| Electrical Insulation Class | Class II | |
| Mounting location | Outdoor | |
| Net Weight | 0.17 lb(US) (0.076 kg) | |

Environment

| IP degree of protection | IP66 conforming to NEMA 4.4X |
|-------------------------------------|------------------------------|
| IK degree of protection | IK08 IEC 62262 |
| Fire resistance | 1760 °F (960 °C) |
| Ambient Air Temperature for Storage | 5140 °F (-1560 °C) |
| Operating temperature | -13176 °F (-2580 °C) |

Ordering and shipping details

| Category | 80033-ENCLOSURE SYSTEMS POLYESTER | |
|-----------------------|-----------------------------------|--|
| Discount Schedule | ES1 | |
| GTIN | 3606480165580 | |
| Nbr. of units in pkg. | 1 | |
| Package weight(Lbs) | 2.68 oz (76.0 g) | |
| Returnability | No | |
| Country of origin | HU | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|--------------------------|
| Package 1 Height | 2.20 in (5.6 cm) |
| Package 1 width | 2.91 in (7.4 cm) |
| Package 1 Length | 2.91 in (7.4 cm) |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 185 |
| Package 2 Weight | 37.57 lb(US) (17.04 kg) |
| Package 2 Height | 15.75 in (40.0 cm) |
| Package 2 width | 16.14 in (41.0 cm) |
| Package 2 Length | 23.62 in (60.0 cm) |
| Unit Type of Package 3 | PAM |
| Number of Units in Package 3 | 4625 |
| Package 3 Weight | 972.24 lb(US) (441.0 kg) |
| Package 3 Height | 85.83 in (218.0 cm) |
| Package 3 width | 39.37 in (100.0 cm) |
| Package 3 Length | 47.24 in (120.0 cm) |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|--|
| REACh Regulation | ☑ REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | ₫Yes |
| China RoHS Regulation | ☐ China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | ☑ End Of Life Information |
| | |

Contractual warranty

| Warranty | 18 months |
|----------|-----------|
|----------|-----------|