

Specification Sheet

Part Number: 596-00851

| PHOTOVOLTAIC SYSTEM DC DISCONNECT | |
|--------------------------------------|----------------------|
| OPERATING CURRENT: | <input type="text"/> |
| OPERATING VOLTAGE: | <input type="text"/> |
| MAXIMUM SYSTEM VOLTAGE: | <input type="text"/> |
| SHORT CIRCUIT CURRENT: | <input type="text"/> |

Solar Label, Printable, DC Rating, 3.75" x 2.0", PET, Red, 10/pkg

| | |
|--------------------------------|---|
| Article Number | 596-00851 |
| Type | DCRATING10 |
| Color | Red (RD) |
| Features & Benefits | <ul style="list-style-type: none">•Made with UV-stable inks and materials for durability and weather resistance.•Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.•High abrasion and scuff resistance for high-performance labeling.•Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections. |
| Quantity Per | pack |

Product Description

HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC 2014, 2017 and 2020 code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC 2014, 2017 and 2020 code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack.

Short Description

Solar Label, Printable, DC Rating, 3.75" x 2.0", PET, Red, 10/pkg

Global Part Name

DCRATING10-840/281-RD

Technical Description

Printable Solar Label, DC RATING LABEL, 3.75" X 2.0", Red

Local Order Number 2

Cross Reference = 50 per roll: 596-00241; Printable Metal Solar Placard 5 pack: 596-00864; Engravable Metal Solar Placard 5 pack: 596-00865

Width W (Imperial)

3.75

Width W (Metric)

92.25

Thickness T (Imperial)

0.0025

Thickness T (Metric)

64.0

Height H (Imperial)

2.0

Height H (Metric)

50.80

Material

Type 840/281, Polyester (PET), UV Stable, Clear Polyester Laminate

Material Shortcut 840/281

Adhesive Acrylic

Halogen free Yes

Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)

Operating Temperature (Metric) -40°F to +302°F (-40°C to +150°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB CSA 66956 NEC2014 NEC2011

Warranty (US) Yes

UL Recognized (US) Yes

Package Quantity(Imperial) 10

Package Quantity (Metric) 10

Customs Number 3919905060

Labels per Column 1

Labels per Row 1

Weight (Metric) 0.521

Weight (Imperial) 1.14

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)