

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0640011900](#)
Status: **Active**
Overview: [Application Tooling](#)
Description: Hand Crimp Tool

Documents:

[RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family	Application Tooling
Series	207129
Comments	Type RHT, Type RHT
Function	Crimp
Geographic Area	Global
Level of Automation	Manual
More Detailed Tech Information	applicationtooling@molex.com
Overview	Application Tooling
Product Name	Avikrimp, InsulKrimp
Tool Type	Hand Crimp Tool
UPC	822348373314
Warranty Disclaimer	CAUTION: Molex tooling crimp specifications are valid only when used with Molex terminals and tooling manufactured by Molex and sold by Molex or authorized distributors ("Molex Tooling"). When using tooling other than Molex Tooling with Molex specific connector systems listed in our ATS documents, the Molex tooling qualification does not apply and the responsibility for full qualification of the connector system is that of the customer. Molex accepts no liability for connector performance or tooling support where tooling other than Molex Tooling is used or where Molex Tooling is modified.

Material Info

Engineering Number RHT-5766

Reference - Drawing Numbers

Application Tooling Documents
640011900-001, TM-640160065, TM-640160065CN, TM-640160065DE, TM-640160065FR, TM-640160065IT, TM-640160065JP, TM-640160065KR, TM-640160065MY, TM-640160065PL, TM-640160065RU, TM-640160065SK, TM-640160065SP, TM-640160065TH, TM-640160065TW, TM-640160065VN



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Not Reviewed

REACH SVHC

Not Contained Per - ED/30/2017 (7 July 2017)

Halogen-Free

Status

Not Relevant

For more information, please visit [Contact US](#)

China ROHS

Not Relevant

ELV

Not Relevant

RoHS Phthalates

Not Contained

Search Parts in this Series

[207129 Series](#)

Use With

Loose Piece Terminals

Application Tooling

Description

FAQ

Product #

1.57mm Diameter, Standard .062" Pin and Socket Crimp Terminal, Female, with Tin (Sn) Plated Brass Contact, 18-24 AWG, Reel	2061101
1.57mm Diameter, Standard .062" Pin and Socket Crimp Terminal, Female, with Tin (Sn) Plated Brass Contact, 18-24 AWG, Bag	2061103
1.57mm Diameter, Standard .062" Pin and Socket Crimp	2061104

Terminal, Series
4529, Female, with
Tin (Sn) Plated
Phosphor Bronze
Contact, 18-24 AWG,
Reel
1.57mm Diameter, 2061118
Standard .062" Pin
and Socket Crimp
Terminal, Series
1561, Female, with
Tin (Sn) Plated Brass
Contact, Without
Locking Tabs,
18-24 AWG, Reel
Packaged
1.57mm Diameter, 2061131
Standard .062" Pin
and Socket Crimp
Terminal, Series
1855, Female, with
Tin (Sn) Plated Brass
Contact, 24-30 AWG,
Reel
1.57mm Diameter, 2061132
Standard .062" Pin
and Socket Crimp
Terminal, Series
1855, Female, with
Tin (Sn) Plated Brass
Contact, 24-30 AWG,
Bag
1.57mm Diameter, 2061141
Standard .062" Pin
and Socket Crimp
Terminal, Series
1855, Female, with
Tin (Sn) Plated
Brass Contact,
24-30 AWG, Without
Locking Tabs, Reel
Packaged
1.57mm Diameter, 2061143
Standard .062" Pin
and Socket Crimp
Terminal, Series
1855, Female, with
Tin (Sn) Plated Brass
Contact, 24-30 AWG,
Reel Packaged with
Interleaf Paper
1.57mm Diameter, 2062101
Standard .062" Pin
and Socket Crimp
Terminal, Series
1560, Male, with Tin
(Sn) Plated Brass
Contact, 18-24 AWG,
Reel
1.57mm Diameter, 2062103
Standard .062" Pin
and Socket Crimp
Terminal, Series
1560, Male, with Tin
(Sn) Plated Brass

Contact, 18-24 AWG,
Bag
1.57mm Diameter, 2062131
Standard .062" Pin
and Socket Crimp
Terminal, Series
1854, Male, with Tin
(Sn) Plated Brass
Contact, 24-30 AWG,
Reel
1.57mm Diameter, 2062132
Standard .062" Pin
and Socket Crimp
Terminal, Series
1854, Male, with Tin
(Sn) Plated Brass
Contact, 24-30 AWG,
Bag
1.57mm Diameter, 2065100
Standard .062" Pin
and Socket Crimp
Terminal, Female,
with 0.38 μ m Gold
(Au) Plated Brass
Contact, 18-24 AWG,
Reel
1.57mm Diameter, 2065101
Standard .062" Pin
and Socket Crimp
Terminal, Female,
with 0.76 μ m Gold
(Au) Plated Brass
Contact, 18-24 AWG,
Reel
1.57mm Diameter, 2065102
Standard .062" Pin
and Socket Crimp
Terminal, Female,
with 0.76 μ m Gold
(Au) Plated Brass
Contact, 18-24 AWG,
Bag
1.57mm Diameter, 2065103
Standard .062" Pin
and Socket Crimp
Terminal, Female,
with 0.38 μ m Gold
(Au) Plated Brass
Contact, 18-24 AWG,
Bag
1.57mm Diameter, 2065104
Standard .062" Pin
and Socket Crimp
Terminal, Series
1561, Female,
with 1.27 μ m Gold
Max. Insulation
Diameter, Loose in
Bag Packaged
1.57mm Diameter, 2065105
Standard .062" Pin
and Socket Crimp
Terminal, Series
1561, Female, with
1.27 μ m Gold Max.

Insulation Diameter,
Reel

1.57mm Diameter, 2065108
Standard .062" Pin
and Socket Crimp
Terminal, Female,
with Selective Gold
(Au) Plated Brass
Contact, 18-24 AWG,
Reel

1.57mm Diameter, 2065109
Standard .062" Pin
and Socket Crimp
Terminal, Female,
with Selective Gold
(Au) Plated Brass
Contact, 18-24 AWG,
Bag

1.57mm Diameter, 2065130
Standard .062" Pin
and Socket Crimp
Terminal, Series
1855, Female,
with 0.38 μ m Gold
(Au) Plated Brass
Contact, 24-30 AWG,
Reel

1.57mm Diameter, 2065135
Standard .062" Pin
and Socket Crimp
Terminal, Series
1855, Female,
with 0.38 μ m Gold
(Au) Plated Brass
Contact, 24-30 AWG,
Bag

1.57mm Diameter, 2065138
Standard .062" Pin
and Socket Crimp
Terminal, Series
1855, Female,
with 0.76 μ m Gold
(Au) Plated Brass
Contact, 24-30 AWG,
Reel

1.57mm Diameter, 2065139
Standard .062" Pin
and Socket Crimp
Terminal, Series
1855, Female,
with 0.76 μ m Gold
(Au) Plated Brass
Contact, 24-30 AWG,
Bag

1.57mm Diameter, 2065147
Standard .062" Pin
and Socket Crimp
Terminal, Series
1855, Female, with
Selective Gold
(Au) Plated Brass
Contact, 24-30 AWG,
Reel

1.57mm Diameter, 2065148
Standard .062" Pin

and Socket Crimp
Terminal, Series
1855, Female, with
Selective Gold
(Au) Plated Brass
Contact, 24-30 AWG,
Bag

1.57mm Diameter, 2066100

Standard .062" Pin
and Socket Crimp
Terminal, Series
1560, Male, with
Gold (Au) Plated
Brass Contact, 18-24
AWG, Reel

1.57mm Diameter, 2066101
Standard .062"

Pin and Socket
Crimp Terminal,
Series 1560, Male,
with .76 μ m Selective
Gold (Au) Plated
Brass Contact,
18-24 AWG, Reel
Packaged

1.57mm Diameter, 2066102
Standard .062"

Pin and Socket
Crimp Terminal,
Series 1560, Male,
with .76 μ m Selective
Gold (Au) Plated
Brass Contact, 18-24
AWG, Bag Packaged

1.57mm Diameter, 2066103
Standard .062" Pin

and Socket Crimp
Terminal, Series
1560, Male, with
Gold (Au) Plated
Brass Contact, 18-24
AWG, Bag

1.57mm Diameter, 2066104
Standard .062"

Pin and Socket
Crimp Terminal,
Series 1560, Male,
with Selective
1.27 μ m Select Gold
(Au) Plated Brass
Contact, 18-24 AWG,
Bag Packaged

1.57mm Diameter, 2066118
Standard .062" Pin

and Socket Crimp
Terminal, Series
1560, Male, with
Selective Gold
(Au) Plated Brass
Contact, Tin/Lead
Plated Crimp Area,
18-24 AWG, Reel

1.57mm Diameter, 2066119
Standard .062" Pin

and Socket Crimp

Terminal, Series
1560, Male, with
Selective Gold
(Au) Plated Brass
Contact, Tin/Lead
Plated Crimp Area,
18-24 AWG, Bag
1.57mm Diameter, 2066122
Standard .062"
Pin and Socket
PC Tail Terminal,
Series 1778, Male,
with Selective Gold
(Au) Plated Brass
Contact, Bag
1.57mm Diameter, 2066130
Standard .062" Pin
and Socket Crimp
Terminal, Series
1854, Male, with
Gold (Au) Plated
Brass Contact, 24-30
AWG, Reel
1.57mm Diameter, 2066135
Standard .062" Pin
and Socket Crimp
Terminal, Series
1854, Male, with
Gold (Au) Plated
Brass Contact, 24-30
AWG, Bag
1.57mm Diameter, 2066138
Standard .062" Pin
and Socket Crimp
Terminal, Series
1854, Male, with
Selective Gold
(Au) Plated Brass
Contact, 24-30 AWG,
Reel
1.57mm Diameter, 2066139
Standard .062" Pin
and Socket Crimp
Terminal, Series
1854, Male, with
Selective Gold
(Au) Plated Brass
Contact, 24-30 AWG,
Bag
1.57mm Diameter, 2066143
Standard .062" Pin
and Socket Crimp
Terminal, Series
1854, Male, with
Selective Gold
(Au) Plated Brass
Contact, Tin (Sn)
Plated Crimp Area,
24-30 AWG, Reel
1.57mm Diameter, 2066144
Standard .062" Pin
and Socket Crimp
Terminal, Series
1854, Male, with
Selective Gold

(Au) Plated Brass
Contact, Tin (Sn)
Plated Crimp Area,
24-30 AWG, Bag
1.57mm Diameter, 2067103
Standard .062" Pin
and Socket PC Tail
Terminal, Series
1779, Female,
with 2.54µm Tin
(Sn) Plated Brass
Contact, Bag
Packaged
1.57mm Diameter, 2067104
Standard .062" Pin
and Socket PC Tail
Terminal, Series
1779, Female,
with .76µm Selective
Gold (Au) Plated
Brass Contact, Bag
Packaged
1.57mm Diameter, 2068103
Standard .062" Pin
and Socket PC Tail
Terminal, Series
1778, Male, with Tin
(Sn) Plated Brass
Contact, Bag
Disk Drive Power 2081201
Connection System,
Female Crimp
Terminal, Reel,
Phosphor Bronze,
AWG 14-20
.084" UNPLATED 2081211
TERMINAL 8980V01
.084" PC TAIL TERM2081212
- 999 8980R11
.084" PC TAIL TERM2081214
- 999 8980R13
2.096MM DIA 2081266
TERMINAL
2.096MM DIA 2081268
TERMINAL
2.13mm DIA PC 2081309
TAIL TERM PhBr
2.54SnLF
2.096MM DIA 2081363
TERMINAL PhBr
2.54SnLF
2.096MM DIA 2081365
TERMINAL PhBr
2.54SnLF
MLX Crimp Terminal 2082008
42023, 14-20 AWG,
Bag Selective Gold
(Au)
2.36mm Diameter, 2091102
Standard .093" Pin
and Socket Crimp
Terminal, Series
1189, Female, with
Tin (Sn) Plated Brass

Contact, 14-20 AWG,
Reel
2.36mm Diameter, [2091104](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1189, Female, with
Tin (Sn) Plated Brass
Contact, 14-20 AWG,
Bag
2.36mm Diameter, [2091117](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1381, Female, with
Tin (Sn) Plated Brass
Contact, 18-22 AWG,
Reel
2.36mm Diameter, [2091119](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1381, Female, with
Tin (Sn) Plated Brass
Contact, 18-22 AWG,
Bag
2.36mm Diameter, [2091122](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
2273, Female, with
Tin (Sn) Plated
Contact, Low
Engagement Force,
18-22 AWG, Reel
2.36mm Diameter, [2091123](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
2273, Female, with
Tin (Sn) Plated
Contact, Low
Engagement Force,
18-22 AWG, Bag
2.36mm Diameter, [2091134](#)
Standard .093" Pin
and Socket PC Tail
Terminal, Series
1377, Female, with
Tin (Sn) Plated
Contact, Bag
2.36mm Diameter, [2091155](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
41483, Female, with
Tin (Sn) Plated Brass
Contact, 14-18 AWG
with Large Insulation
Diameter, Chain
2.36mm Diameter, [2091205](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
4550, Female, with

Tin (Sn) Plated
Phosphor Bronze
Contact, 14-20 AWG,
Reel
2.36mm Diameter, 2091206
Standard .093" Pin
and Socket Crimp
Terminal, Series
4550, Female, with
Tin (Sn) Plated
Phosphor Bronze
Contact, 14-20 AWG,
Bag
2.36mm Diameter, 2091615
Standard .093"
Pin and Socket
Crimp Terminal,
Series 42477,
Female, with Tin
(Sn) Plated Contact,
High Current/Low
Engagement Force,
14-18 AWG, Reel
2.36mm Diameter, 2092101
Standard .093" Pin
and Socket Crimp
Terminal, Series
1190, Male, with Tin
(Sn) Plated Brass
Contact, 14-20 AWG,
Reel
2.36mm Diameter, 2092103
Standard .093" Pin
and Socket Crimp
Terminal, Series
1190, Male, with Tin
(Sn) Plated Brass
Contact, 14-20 AWG,
Bag
2.36mm Diameter, 2092116
Standard .093" Pin
and Socket Crimp
Terminal, Series
1380, Male, with Tin
(Sn) Plated Brass
Contact, 18-22 AWG,
Reel
2.36mm Diameter, 2092117
Standard .093" Pin
and Socket Crimp
Terminal, Series
1380, Male, with Tin
(Sn) Plated Brass
Contact, without
Dents, 18-22 AWG,
Reel
2.36mm Diameter, 2092118
Standard .093" Pin
and Socket Crimp
Terminal, Series
1380, Male, with Tin
(Sn) Plated Brass
Contact, 18-22 AWG,
Bag

2.36mm Diameter, [2092133](#)
Standard .093" Pin
and Socket PC Tail
Terminal, Series
1376, Male, with Tin/
Lead (Sn/Pb) Plated
Contact, With Detent,
Bag Packaged

2.36mm Diameter, [2092134](#)
Standard .093" Pin
and Socket PC Tail
Terminal, Series
1376, Male, with Tin
(Sn) Plated Contact,
Without Detent, Bag
Packaged

2.36mm Diameter, [2092166](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
4549, Male, with
Tin (Sn) Plated
Phosphor Bronze
Contact, 14-20 AWG,
Reel Packaged

2.36mm Diameter, [2092167](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
4549, Male, with
Tin (Sn) Plated
Phosphor Bronze
Contact, 14-20 AWG,
Bag Packaged

2.36mm Diameter, [2092170](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1190, Male, with Tin
(Sn) Plated Brass
Contact, 14-18 AWG,
Large Insulation
Crimp, Reel

2.36mm Diameter, [2092171](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1190, Male, with Tin
(Sn) Plated Brass
Contact, 14-18 AWG,
Large Insulation
Crimp, Bag

2.36mm Diameter, [2092611](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
42478, Male, with Tin
(Sn) Plated Contact,
High Current/Low
Engagement Force,
14-18 AWG, Reel

2.36mm Diameter, [2095100](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series

1189, Female, with
Gold (Au) Plated
Brass Contact, 14-20
AWG, Reel
2.36mm Diameter, [2095101](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1190, Male, with Tin
(Sn) Plated Brass
Contact, 14-20 AWG,
Chain
2.36mm Diameter, [2095102](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1189, Female, with
Selective Gold
(Au) Plated Brass
Contact, 14-20 AWG,
Reel
2.36mm Diameter, [2095106](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1189, Female, with
Gold (Au) Plated
Brass Contact, 14-20
AWG, Bag
2.36mm Diameter, [2095111](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1189, Female, with
Selective Gold
(Au) Plated Brass
Contact, 14-20 AWG,
Bag
2.36mm Diameter, [2095130](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1381, Female, with
Selective Gold
(Au) Plated Brass
Contact, 18-22 AWG,
Reel
2.36mm Diameter, [2095132](#)
Standard .093" Pin
and Socket PC Tail
Terminal, Series
1377, Female, with
Gold (Au) Plated
Contact, Bag
2.36mm Diameter, [2095133](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1381, Female, with
Selective Gold
(Au) Plated Brass
Contact, 18-22 AWG,
Bag
2.36mm Diameter, [2095142](#)
Standard .093" Pin

and Socket Crimp
Terminal, Series
1381, Female, with
Gold (Au) Plated
Brass Contact, 18-22
AWG, Bag
2.36mm Diameter, [2095143](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1381, Female, with
Gold (Au) Plated
Brass Contact, 18-22
AWG, Reel
2.36mm Diameter, [2095169](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
4550, Female, with
Gold (Au) Plated
Phosphor Bronze
Contact, 14-20 AWG,
Reel
2.36mm Diameter, [2095170](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
4550, Female, with
Gold (Au) Plated
Phosphor Bronze
Contact, 14-20 AWG,
Bag
2.36mm Diameter, [2096100](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1190, Male, with
Gold (Au) Plated
Brass Contact, 14-20
AWG, Reel
2.36mm Diameter, [2096101](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1190, Male, with
Selective Gold
(Au) Plated Brass
Contact, 14-20 AWG,
Reel
2.36mm Diameter, [2096102](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1189, Female, with
Tin (Sn) Plated Brass
Contact, 14-20 AWG,
Reel
2.36mm Diameter, [2096106](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1190, Male, with
Gold (Au) Plated
Brass Contact, 14-20
AWG, Bag

2.36mm Diameter, [2096110](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1190, Male, with
Selective Gold
(Au) Plated Brass
Contact, 14-20 AWG,
Bag

2.36mm Diameter, [2096122](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1380, Male, with
Gold (Au) Plated
Brass Contact, 18-22
AWG, Reel

2.36mm Diameter, [2096123](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1380, Male, with
Gold (Au) Plated
Brass Contact, 18-22
AWG, Bag

2.36mm Diameter, [2096125](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1380, Male, with
Selective Gold
(Au) Plated Brass
Contact, 18-22 AWG,
Reel

2.36mm Diameter, [2096126](#)
Standard .093" Pin
and Socket Crimp
Terminal, Series
1380, Male, with
Selective Gold
(Au) Plated Brass
Contact, 18-22 AWG,
Bag

2.36mm Diameter, [2096132](#)
Standard .093"
Pin and Socket
PC Tail Terminal,
Series 1376, Male,
with Gold (Au)
Plated Contact,
Without Detent, Bag
Packaged

2.36mm Diameter, [2098103](#)
Standard .093" Pin
and Socket Crimp
Grounding Terminal,
Series 1973, Male,
with Tin (Sn) Plated
Brass Contact, 18-22
AWG, Reel

2.36mm Diameter, [2098104](#)
Standard .093" Pin
and Socket Crimp
Grounding Terminal,
Series 1973, Male,

with Tin (Sn) Plated
Brass Contact, 18-22
AWG, Bag
2.36mm Diameter, 2098108
Standard .093" Pin
and Socket Crimp
Grounding Terminal,
Series 1973, Male,
with Tin (Sn) Plated
Brass Contact, 14-18
AWG, Reel
2.36mm Diameter, 2098109
Standard .093" Pin
and Socket Crimp
Grounding Terminal,
Series 1973, Male,
with Tin (Sn) Plated
Brass Contact, 14-18
AWG, Bag
1.57mm Diameter 3061011
Standard .062"
Pin and Socket
Receptacle Housing,
1 Circuits, Natural
1.57mm Diameter 3061022
Standard .062"
Pin and Socket
Receptacle Housing,
2 Circuits, with Pre-
bent Mounting Ears,
Natural
1.57mm Diameter 3061023
Standard .062"
Pin and Socket
Receptacle Housing,
2 Circuits, without
Mounting Ears,
Natural
1.57mm Diameter 3061031
Standard .062"
Pin and Socket
Receptacle Housing,
3 Circuits, with
Standard Mounting
Ears
1.57mm Diameter 3061032
Standard .062"
Pin and Socket
Receptacle Housing,
3 Circuits, without
Mounting Ears,
Natural
1.57mm Diameter 3061038
Standard .062"
Pin and Socket
Receptacle Housing,
3 Circuits, with Pre-
bent Mounting Ears,
Natural
1.57mm Diameter 3061041
Standard .062"
Pin and Socket
Receptacle Housing,
4 Circuits, with

Standard Mounting
Ears

1.57mm Diameter 3061042

Standard .062"
Pin and Socket
Receptacle Housing,
4 Circuits, without
Mounting Ears,
Natural

1.57mm Diameter 3061044

Standard .062"
Pin and Socket
Receptacle Housing,
Dual Row, without
Mounting Ears, PA
Polyamide Nylon 6/6,
UL 94V-2, 4 Circuits,
Natural

1.57mm Diameter 3061062

Standard .062"
Pin and Socket
Receptacle Housing,
6 Circuits, without
Mounting Ears,
Natural

1.57mm Diameter 3061092

Standard .062"
Pin and Socket
Receptacle Housing,
9 Circuits, without
Mounting Ears,
Natural

1.57mm Diameter 3061121

Standard .062"
Pin and Socket
Receptacle Housing,
12 Circuits, with
Standard Mounting
Ears, Natural

1.57mm Diameter 3061122

Standard .062"
Pin and Socket
Receptacle Housing,
12 Circuits, without
Mounting Ears,
Natural

1.57mm Diameter 3062011

Standard .062" Pin
and Socket Plug
Housing, 1 Circuits,
Natural

1.57mm Diameter 3062023

Standard .062" Pin
and Socket Plug
Housing, 2 Circuits,
without Mounting
Ears, Natural

1.57mm Diameter 3062024

Standard .062"
Pin and Socket
Plug Housing, 2
Circuits, with Pre-
bent Mounting Ears,
Natural

1.57mm Diameter Standard .062" Pin and Socket Plug Housing, 3 Circuits, with Standard Mounting Ears, Natural	<u>3062031</u>
1.57mm Diameter Standard .062" Pin and Socket Plug Housing, 3 Circuits, without Mounting Ears, Natural	<u>3062032</u>
1.57mm Diameter Standard .062" Pin and Socket Plug Housing, 3 Circuits, with Pre- bent Mounting Ears, Natural	<u>3062033</u>
1.57mm Diameter Standard .062" Pin and Socket Plug Housing, 4 Circuits, with Standard Mounting Ears	<u>3062041</u>
1.57mm Diameter Standard .062" Pin and Socket Plug Housing, 4 Circuits, without Mounting Ears, Natural	<u>3062042</u>
1.57mm Diameter Standard .062" Pin and Socket Plug Housing, Dual Row, without Mounting Ears, PA Polyamide Nylon 6/6, UL 94V-2, 4 Circuits, Natural	<u>3062044</u>
1.57mm Diameter Standard .062" Pin and Socket Plug Housing, 6 Circuits, without Mounting Ears, Natural	<u>3062061</u>
1.57mm Diameter Standard .062" Pin and Socket Plug Housing, 9 Circuits, without Mounting Ears, Natural	<u>3062092</u>
1.57mm Diameter Standard .062" Pin and Socket Plug Housing, 12 Circuits, with Pre- bent Mounting Ears, Natural	<u>3062121</u>
1.57mm Diameter Standard .062" Pin and Socket Plug Housing, 12 Circuits, without Mounting Ears, Natural	<u>3062122</u>

1.57mm Diameter 3066023
Standard .062"
Pin and Socket
Receptacle Housing,
2 Circuits, without
Mounting Ears, Black

1.57mm Diameter 3066062
Standard .062"
Pin and Socket
Receptacle Housing,
6 Circuits, without
Mounting Ears, Black

1.57mm Diameter 3067023
Standard .062" Pin
and Socket Plug
Housing, Black, 2
Circuits, without
Mounting Ears, Black

1.57mm Diameter 3067044
Standard .062" Pin
and Socket Plug
Housing, Dual Row,
without Mounting
Ears, PA Polyamide
Nylon 6/6, UL 94V-2,
4 Circuits, Black

1.57mm Diameter 3067061
Standard .062" Pin
and Socket Plug
Housing, 6 Circuits,
without Mounting
Ears, Black

2.36mm Diameter 3091011
Standard .093"
Pin and Socket
Receptacle Housing,
1 Circuit, Friction
Lock, Natural

2.36mm Diameter 3091022
Standard .093"
Pin and Socket
Receptacle Housing,
2 Circuits, without
Mounting Ears, with
Ramps, Natural

2.36mm Diameter 3091027
Standard .093"
Pin and Socket
Receptacle Housing,
2 Circuits, with Pre-
bent Mounting Ears,
with Ramps, Natural

2.36mm Diameter 3091031
Standard .093"
Pin and Socket
Receptacle Housing,
3 Circuits, Single
Row, Natural

2.36mm Diameter 3091032
Standard .093"
Pin and Socket
Receptacle Housing,
3 Circuits, Single
Row, Natural

2.36mm Diameter 3091033
Standard .093"
Pin and Socket
Receptacle Housing,
3 Circuits, Single
Row, Free-Hanging,
without Passive Lock
Ramps, Natural

2.36mm Diameter 3091041
Standard .093"
Pin and Socket
Receptacle Housing,
4 Circuits, Single
Row, Natural

2.36mm Diameter 3091042
Standard .093"
Pin and Socket
Receptacle Housing,
4 Circuits, Single
Row, Natural

2.36mm Diameter 3091049
Standard .093"
Pin and Socket
Receptacle Housing,
4 Circuits, Dual Row,
without Mounting
Ears, Natural

2.36mm Diameter 3091061
Standard .093"
Pin and Socket
Receptacle Housing,
6 Circuits, Dual Row,
Natural

2.36mm Diameter 3091062
Standard .093"
Pin and Socket
Receptacle Housing,
6 Circuits, Dual Row,
Natural

2.36mm Diameter 3091063
Standard .093"
Pin and Socket
Receptacle Housing,
6 Circuits, Dual Row,
without Panel Mount
Ears, without Friction
Lock Ramp

2.36mm Diameter 3091064
Standard .093"
Pin and Socket
Receptacle Housing,
6 Circuits, Dual Row,
Natural

2.36mm Diameter 3091081
Standard .093"
Pin and Socket
Receptacle Housing,
3 Circuits, Single
Row, Natural

2.36mm Diameter 3091091
Standard .093"
Pin and Socket
Receptacle
Housings, 9 Circuits,
3 Rows, Natural

2.36mm Diameter 3091092
Standard .093"
Pin and Socket
Receptacle
Housings, 9 Circuits,
3 Rows, with Panel
Mount Ears, without
Passive Lock Ramp

2.36mm Diameter 3091093
Standard .093"
Pin and Socket
Receptacle
Housings, 9 Circuits,
3 Rows, without
Panel Mount Ears,
without Passive Lock
Ramp

2.36mm Diameter 3091094
Standard .093"
Pin and Socket
Receptacle
Housings, 9 Circuits,
3 Rows, Natural

2.36mm Diameter 3091121
Standard .093"
Pin and Socket
Receptacle Housing,
12 Circuits, 3 Rows,
Panel Mountable,
without Passive
Locking Ramps

2.36mm Diameter 3091125
Standard .093"
Pin and Socket
Receptacle Housing,
12 Circuits, 3 Rows,
Natural

2.36mm Diameter 3091126
Standard .093"
Pin and Socket
Receptacle Housing,
12 Circuits, 3 Rows,
Natural

2.36mm Diameter 3091151
Standard .093"
Pin and Socket
Receptacle Housing,
15 Circuits, 3 Rows,
with Pre-Bent
Mounting Ears,
without Lock Ramps

2.36mm Diameter 3091152
Standard .093"
Pin and Socket
Receptacle Housing,
15 Circuits, 3 Rows,
without Mounting
Ears, without Lock
Ramps

2.36mm Diameter 3091153
Standard .093"
Pin and Socket
Receptacle Housing,
15 Circuits, 3 Rows,
with Pre-bent

Mounting Ears, with Lock Ramps 2.36mm Diameter Standard .093" Pin and Socket Receptacle Housing, 15 Circuits, 3 Rows, without Mounting Ears, with Lock Ramps	<u>3091157</u>
2.36mm Diameter Standard .093" Pin and Socket Receptacle Housing without Mounting Ears, Positive Lock, 2 Circuits	<u>3091161</u>
2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 1 Circuit, Friction Lock, Natural	<u>3092011</u>
2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 2 Circuits, with Standard Mounting Ears, Natural	<u>3092021</u>
2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 2 Circuits, without Mounting Ears, Natural	<u>3092022</u>
2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 3 Circuits, Single Row, Natural	<u>3092031</u>
2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 3 Circuits, Single Row, Natural	<u>3092032</u>
2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 4 Circuits, Single Row	<u>3092041</u>
2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 4 Circuits, Single Row	<u>3092042</u>
2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 4 Circuits, Dual Row, without Mounting Ears, Natural	<u>3092049</u>
2.36mm Diameter Standard .093" Pin and Socket Plug	<u>3092061</u>

Housing, 6 Circuits, Dual Row 2.36mm Diameter Standard .093" Pin and Socket Plug	<u>3092062</u>
Housing, 6 Circuits, Dual Row 2.36mm Diameter Standard .093" Pin and Socket Plug	<u>3092092</u>
Housings, 9 Circuits, 3 Rows 2.36mm Diameter Standard .093" Pin and Socket Plug	<u>3092121</u>
Housing, 12 Circuits, 3 Rows 2.36mm Diameter Standard .093" Pin and Socket Plug	<u>3092122</u>
Housing, 12 Circuits, 3 Rows 2.36mm Diameter Standard .093" Pin and Socket Plug	<u>3092151</u>
Housing, 15 Circuits, 3 Rows, without Mounting Ears, with Pull Tabs, without Lock Windows	<u>3092159</u>
2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 15 Circuits, 3 Rows, with Pre- Bent Mounting Ears, without Pull Tabs, with Lock Windows	<u>3092161</u>
2.36mm Diameter Standard .093" Pin and Socket Plug Housing without Mounting Ears, Positive Lock, 2 Circuits	<u>3096021</u>
2.36mm Diameter Standard .093" Pin and Socket Receptacle Housing, 2 Circuits, with Pre- bent Mounting Ears, with Ramps, Black	<u>3097022</u>
2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 2 Circuits, without Mounting Ears, Black	<u>3097024</u>
2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 2 Circuits, without Mounting Ears, Red	

2.36mm Diameter 3097032
Standard .093" Pin
and Socket Plug
Housing, 3 Circuits,
Single Row, Black

3.18mm Diameter, 3121022
HCS125, Pin and
Socket Receptacle
Housing, 2 Circuits,
Single Row, with and
without Panel Mount
Ears

3.18mm Diameter, 3121026
HCS125, Pin and
Socket Receptacle
Housing, Single
Row, 2 Circuits,
Natural (Translucent)

3.18mm Diameter, 3121036
HCS125, Pin and
Socket Receptacle
Housing, Single
Row, without Panel
Mount Ears, 3
Circuits, Natural,
Nylon 94V-2

3.18mm Diameter, 3121046
HCS125, Pin and
Socket Receptacle
Housing, Single
Row, 4 Circuits,
Natural (Translucent)

3.18mm Diameter, 3122022
HCS125, Pin
and Socket Plug
Housing, 2 Circuits,
Single Row, with and
without Panel Mount
Ears

3.18mm Diameter, 3122025
HCS125, Pin
and Socket Plug
Housing, Single
Row, with Panel
Mount Ears, 2
Circuits, Natural
(Translucent)

3.18mm Diameter, 3122026
HCS125, Pin
and Socket Plug
Housing, Single
Row, without Panel
Mount Ears, 2
Circuits, Natural
(Translucent)

3.18mm Diameter, 3122035
HCS125, Pin
and Socket Plug
Housing, Single
Row, with Panel
Mount Ears, 3
Circuits, Natural,
Nylon 94V-2

3.18mm Diameter, 3122036
HCS125, Pin

and Socket Plug
Housing, Single
Row, without Panel
Mount Ears, 3
Circuits, Natural,
Nylon 94V-2
3.18mm Diameter, 3122045
HCS125, Pin
and Socket Plug
Housing, Single
Row, with Panel
Mount Ears, 4
Circuits, Natural
(Translucent)
3.18mm Diameter, 3122046
HCS125, Pin
and Socket Plug
Housing, Single
Row, without Panel
Mount Ears, 4
Circuits, Natural
(Translucent)
3.96 and 5.08mm 8700012
Pitch KK Cat Ear
Crimp Terminal,
Female, 18-24 AWG,
Reel
SPOX Crimp 8701030
Terminal, 18-24
AWG, Brass, Bag
SPOX Crimp 8701031
Terminal, 18-24
AWG, Brass, Reel
3.96mm Pitch SPOX 9501023
Crimp Housing,
Female, with Friction
Ramp and Void, 2
Circuits, Natural
3.96mm Pitch SPOX 9501033
Crimp Housing,
Female, with Friction
Ramp and Void, 3
Circuits, Natural
3.96mm Pitch SPOX 9501043
Crimp Housing,
Female, with Friction
Ramp and Void, 4
Circuits, Natural
3.96mm Pitch SPOX 9501053
Crimp Housing,
Female, with Friction
Ramp and Void, 5
Circuits, Natural
3.96mm Pitch SPOX 9501063
Crimp Housing,
Female, with Friction
Ramp and Void, 6
Circuits, Natural
3.96mm Pitch SPOX 9501073
Crimp Housing,
Female, with Friction
Ramp and Void, 7
Circuits, Natural
3.96mm Pitch SPOX 9501083
Crimp Housing,

Female, with Friction
Ramp and Void, 8
Circuits, Natural
3.96mm Pitch SPOX [9501093](#)
Crimp Housing,
Female, with Friction
Ramp and Void, 9
Circuits, Natural
3.96mm Pitch SPOX [9501103](#)
Crimp Housing,
Female, with Friction
Ramp and Void, 10
Circuits, Natural
3.96mm Pitch SPOX [9501113](#)
Crimp Housing,
Female, with Friction
Ramp and Void, 11
Circuits, Natural
SPOX and KK [9652028](#)
396 Wire-to-Board
Header, Vertical,
with Friction Lock, 2
Circuits
SPOX and KK [9652029](#)
396 Wire-to-Board
Header, Vertical, with
Friction Lock, with
Void, 2 Circuits
SPOX and KK [9652038](#)
396 Wire-to-Board
Header, Vertical,
with Friction Lock, 3
Circuits
SPOX and KK [9652039](#)
396 Wire-to-Board
Header, Vertical, with
Friction Lock, with
Void, 3 Circuits
SPOX and KK [9652048](#)
396 Wire-to-Board
Header, Vertical,
with Friction Lock, 4
Circuits
SPOX and KK [9652049](#)
396 Wire-to-Board
Header, Vertical, with
Friction Lock, with
Void, 4 Circuits
SPOX and KK [9652058](#)
396 Wire-to-Board
Header, Vertical,
with Friction Lock, 5
Circuits
SPOX and KK [9652068](#)
396 Wire-to-Board
Header, Vertical,
with Friction Lock, 6
Circuits
SPOX and KK [9652069](#)
396 Wire-to-Board
Header, Vertical, with
Friction Lock, with
Void, 6 Circuits
SPOX and KK [9652078](#)
396 Wire-to-Board

Header, Vertical, with Friction Lock, 7 Circuits SPOX and KK 396 Wire-to-Board	<u>9652079</u>
Header, Vertical, with Friction Lock, with Void, 7 Circuits SPOX and KK 396 Wire-to-Board	<u>9652088</u>
Header, Vertical, with Friction Lock, 8 Circuits SPOX and KK 396 Wire-to-Board	<u>9652089</u>
Header, Vertical, with Friction Lock, with Void, 8 Circuits 2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 3 Circuits, 2 Male Terminals	<u>10181031</u>
2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 3 Circuits, 3 Male Terminals	<u>10181032</u>
2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 3 Circuits, 1 Female Terminal, 2 Male Terminals	<u>10181033</u>
2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 3 Circuits, 1 Female Terminal, 2 Male Terminals	<u>10181034</u>
2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 3 Circuits, 2 Male Terminals, 1 Female Terminal	<u>10181035</u>
2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 3 Circuits, 1 Female Terminal, 1 Male Terminal	<u>10181036</u>
2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 3 Circuits, 2 Female Terminals, 1 Male Terminal	<u>10181037</u>
2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 3 Circuits, 3 Female Terminals	<u>10181038</u>
2.36mm Diameter Standard .093" Pin	<u>10181040</u>

and Socket Header,
Shrouded, 4 Circuits,
1 Female Terminal, 1
Male Terminal
2.36mm Diameter 10181041
Standard .093" Pin
and Socket Header,
Shrouded, 4 Circuits,
4 Male Terminals
2.36mm Diameter 10181042
Standard .093" Pin
and Socket Header,
Shrouded, 4 Circuits,
4 Female Terminals
2.36mm Diameter 10181043
Standard .093" Pin
and Socket Header,
Shrouded, 4 Circuits,
1 Female Terminal, 3
Male Terminals
2.36mm Diameter 10181044
Standard .093" Pin
and Socket Header,
Shrouded, 4 Circuits,
3 Female Terminals,
1 Male Terminals
2.36mm Diameter 10181045
Standard .093" Pin
and Socket Header,
Shrouded, 4 Circuits,
2 Male Terminals, 2
Female Terminals
2.36mm Diameter 10181046
Standard .093" Pin
and Socket Header,
Shrouded, 4 Circuits,
3 Male Terminals, 1
Female Terminal
2.36mm Diameter 10181047
Standard .093" Pin
and Socket Header,
Shrouded, 4 Circuits,
1 Female Terminal, 3
Male Terminals
2.36mm Diameter 10181048
Standard .093" Pin
and Socket Header,
Shrouded, 4 Circuits,
1 Female Terminal,
2 Male Terminals, 1
Female Terminal, 1
Male Terminal
2.36mm Diameter 10181049
Standard .093" Pin
and Socket Header,
Shrouded, 4 Circuits,
2 Female Terminals,
1 Male Terminal, 1
Female Terminal,
1 Male Terminal, 1
Female Terminal
2.36mm Diameter 10181050
Standard .093" Pin
and Socket Header,
Shrouded, 4 Circuits,

2 Female Terminals,
2 Male Terminals
2.36mm Diameter 10181090
Standard .093" Pin
and Socket Header,
Shrouded, 9 Circuits,
9 Male Terminals
2.36mm Diameter 10181091
Standard .093" Pin
and Socket Header,
3 Rows, Shrouded,
Unfilled Polyester,
UL 94V-0, 9 Circuits,
9 Female Terminals
2.36mm Diameter 10181120
Standard .093"
Pin and Socket
Header, Shrouded,
12 Circuits, 12 Male
Terminals
2.36mm Diameter 10181122
Standard .093"
Pin and Socket
Header, 3 Rows,
Shrouded, Unfilled
Polyester, UL 94V-0,
12 Circuits, 12
Female Terminals
2.36mm Diameter 10181150
Standard .093"
Pin and Socket
Header, Shrouded,
15 Circuits, 15 Male
Terminals
5.08mm Pitch SPOX 10221022
Crimp Housing,
Female, with Friction
Ramp and Void, 2
Circuits
5.00mm Pitch SPOX 10633024
Crimp Housing,
Female, with Friction
Ramp and Void, 2
Circuits, Natural
5.00mm Pitch SPOX 10633034
Crimp Housing,
Female, with Friction
Ramp and Void, 3
Circuits, Natural
5.00mm Pitch SPOX 10633044
Crimp Housing,
Female, with Friction
Ramp and Void, 4
Circuits, Natural
5.00mm Pitch SPOX 10633054
Crimp Housing,
Female, with Friction
Ramp and Void, 5
Circuits, Natural
5.00mm Pitch SPOX 10633064
Crimp Housing,
Female, with Friction
Ramp and Void, 6
Circuits, Natural

zQSFP+ Cage, 1- by-1 with Spring Fingers, Closed Top and 1 Rear Pin	<u>1000141242</u>
zQSFP+ Cage, 1- by-1 with Spring Fingers, with SAN Heatsink and 1 Rear Pin	<u>1000141344</u>
zQSFP+ Cage, 1- by-1 with Spring Fingers, with NET Heatsink and 1 Rear Pin	<u>1000141345</u>
zQSFP+ Cage, 1- by-1 and Spring Fingers, and SAN Heatsink, Single Lightpipes with 1 Rear Pin	<u>1000141541</u>
zQSFP+ Cage, 1- by-1 and Spring Fingers, and NET Heatsink, Single Lightpipes with 1 Rear Pin	<u>1000141542</u>
zQSFP+ Cage, 1- by-1 and Spring Fingers, and NET Heatsink, Double Lightpipes with 1 Rear Pin	<u>1000141545</u>
zQSFP+ Cage, 1- by-1 and Spring Fingers, and SAN Heatsink, Quad Lightpipes with 1 Rear Pin	<u>1000141547</u>
zQSFP+ Cage, 1- by-1 and Spring Fingers, and NET Heatsink, Quad Lightpipes with 1 Rear Pin	<u>1000141548</u>
zQSFP+ Cage, 1- by-4 with Spring Fingers, with PCI Heatsink, and 1 Rear Pin	<u>1000171343</u>
zQSFP+ Cage, 1- by-4 with Spring Fingers, with SAN Heatsink and 1 Rear Pin	<u>1000171344</u>
zQSFP+ Cage, 1- by-4 with Spring Fingers, with NET Heatsink and 1 Rear Pin	<u>1000171345</u>
zQSFP+ Cage, 1- by-4 and Spring Fingers, and NET Heatsink, Single Lightpipes with 1 Rear Pin	<u>1000171542</u>

zQSFP+ Cage, 1-by-4 and Spring Fingers, and SAN Heatsink, Double Lightpipes with 1 Rear Pin	<u>1000171544</u>
zQSFP+ Cage, 1-by-4 and Spring Fingers, and NET Heatsink, Double Lightpipes with 1 Rear Pin	<u>1000171545</u>
zQSFP+ Cage, 1-by-4 and Spring Fingers, and SAN Heatsink, Quad Lightpipes with 1 Rear Pin	<u>1000171547</u>
zQSFP+ Cage, 1-by-4 and Spring Fingers, and NET Heatsink, Quad Lightpipes with 1 Rear Pin	<u>1000171548</u>
zQSFP+ Cage, 1-by-6 with Spring Fingers, with NET Heatsink and 1 Rear Pin	<u>1000861345</u>
zQSFP+ Cage, 1-by-6 and Spring Fingers, and PCI Heatsink, Single Lightpipes with 1 Rear Pin	<u>1000861540</u>
zQSFP+ Cage, 1-by-6 and Spring Fingers, and SAN Heatsink, Single Lightpipes with 1 Rear Pin	<u>1000861541</u>
zQSFP+ Cage, 1-by-6 and Spring Fingers, and SAN Heatsink, Quad Lightpipes with 1 Rear Pin	<u>1000861547</u>
1.10mm Pitch microSD Memory Card Connector, Normal Mount, Surface Mount, Push-Pull Type, 2.85mm Height, with Detect Switch	<u>1040320821</u>
1.10mm Pitch microSD Memory Card Connector, Normal Mount, Push-Pull Type, 3.35mm Height, with Detect Switch	<u>1040700811</u>
IllumiMate 1.00mm Pitch Wire-to-Board Header, Surface	<u>1041411010</u>

Mount, Single
Row, Vertical, Side
Positive Locks and
Secondary Middle
Friction Locks, 10
Circuits
IllumiMate 1.00mm [1041421000](#)
Pitch Wire-to-Board
Crimp Housing,
Single Row, Side
Positive Locks and
Secondary Middle
Friction Locks, 10
Circuits, Natural
LED Array Holder for [1042290210](#)
Samsung LC026B,
LC033B and
LC040B, 19.00mm
LES Diameter, Wire
Trap, Push-Button
Type
0.50mm Pitch Easy- [1042470617](#)
On Back Flip FPC
Connector, Right-
Angle, Surface
Mount, Bottom
Contact Style,
2.80mm Mated
Height, High Cable
Retention and High
Temperature Type, 6
Circuits
0.50mm Pitch Easy- [1042470717](#)
On Back Flip FPC
Connector, Right-
Angle, Surface
Mount, Bottom
Contact Style,
2.80mm Mated
Height, High Cable
Retention and High
Temperature Type, 7
Circuits
1.10mm, 0.75mm, [1050270001](#)
0.70mm Pitch
microSD Card
Header with Detect
Switch, Height
1.70mm, Lead-Free,
0.762µm Gold (Au)
Plating
2.54mm SIM Card [1050480001](#)
Connector, Guide
and Holder Style,
6 Circuits, Surface
Mount, Housing
Height 1.45mm,
Lead-Free
2.54mm SIM Card [1050481001](#)
Connector, 6
Circuits, Surface
Mount, with Guide
Rail, Housing Height
1.45mm, Lead-Free

1.10mm Pitch microSD Card Header with Detect Pin, Height 1.45mm, Lead-Free, Gold (Au) Plated 0.381µm	<u>1051620001</u>
1.10mm Pitch microSD Card Header with Detect Pin, Height 1.45mm, Lead-Free, Gold (Au) Plated 0.762µm	<u>1051620101</u>
Contact Pucks with Pick-and-Place Cap, 1.00mm Height, Tape and Reel	<u>1054020022</u>
Universal Serial Bus (USB) Shielded I/ O Plug, Type C, Right-Angle, Surface Mount, 0.76µm Gold (Au) Plating, Tape and Reel	<u>1054440011</u>
Bezel, Simplex, Black Body, Logo, Shutter, SC Duplex Blue Adapter Loaded, Zirconia (Zn) Alignment Sleeve, Snap Mount Style	<u>1060043075</u>
Bezel Adapter, Simplex, Black Body, Logo, Shutter, ST/ SC Metal Adapter Loaded, Phosphor Bronze (CuSn) Alignment Sleeve, Snap Mount Style	<u>1060043080</u>
Bezel Adapter, Simplex, Black Body, Logo, Shutter, FC/ SC Metal Adapter Loaded, Zirconia (Zn) Alignment Sleeve, Snap Mount Style	<u>1060043083</u>
Bezel Adapter, Simplex, Black Body, Logo, Shutter, LC Duplex Black Adapter Loaded, Phosphor Bronze (CuSn) Alignment Sleeve, Snap Mount Style	<u>1060043093</u>
Bezel Adapter, Duplex, Black Body, Logo, Shutter, SC Duplex Black Adapter Loaded, Zirconia (Zn) Alignment Sleeve, Snap Mount Style	<u>1060043181</u>

Bezel Adapter, 1060043262
Simplex, Black Body,
Push Tab, Logo,
Shutter, FC Duplex
Black Adapter
Loaded, Zirconia
(Zn) Alignment
Sleeve, Snap Mount
Style

Bezel Adapter, 1060043266
Simplex, Black
Body, Push Tab,
Logo, Shutter, SC/
FC Metal Adapter
Loaded, Zirconia
(Zn) Alignment
Sleeve, Snap Mount
Style

Bezel Adapter, 1060043278
Simplex, Black
Body, Push Tab,
Logo, Shutter, LC
Duplex Blue Adapter
Loaded, Zirconia
(Zn) Alignment
Sleeve, Snap Mount
Style

Bezel Adapter, 1060043284
Simplex, Black Body,
Push Tab, Logo,
Shutter, SC Black
Adapter Loaded,
Phosphor Bronze
(CuSn) Alignment
Sleeve, Snap Mount
Style

Bezel Adapter, 1060043290
Simplex, Black Body,
Push Tab, Shutter,
ST/SC Metal Adapter
Loaded, Phosphor
Bronze (CuSn)
Alignment Sleeve,
Snap Mount Style

Bezel Adapter, 1060043291
Simplex, Black Body,
Push Tab, Shutter,
ST/SC Metal Adapter
Loaded, Zirconia
(Zn) Alignment
Sleeve, Snap Mount
Style

Bezel Adapter, 1060043298
Simplex, Black Body,
Push Tab, Shutter,
MTP* Black Adapter
Loaded, Snap Mount
Style

Bezel Adapter, 1060043383
Simplex, Metalized
Body, Logo, Shutter,
FC/SC Metal Adapter
Loaded, Zirconia
(Zn) Alignment

Sleeve, Snap Mount Style	
Bezel Adapter, Simplex, Metalized Body, Push Tab, Shutter, LC Duplex Metal Adapter Loaded, Phosphor Bronze (CuSn) Alignment Sleeve, Snap Mount Style	<u>1060043577</u>
Bezel Adapter, Simplex, Metalized Body, Push Tab, Shutter, FC/SC Metal Adapter Loaded, Zirconia (Zn) Alignment Sleeve, Snap Mount Style	<u>1060043593</u>
ST Connector, Multimode, 127µm Ceramic PC+ Ferrule, 1.60mm and 2.00mm Simplex Cable, Polymer Coupling Nut, Straight Boot	<u>1060100100</u>
ST Connector, Multimode, 127µm Ceramic PC+ Ferrule, 1.60mm and 2.00mm Simplex Cable, Polymer Coupling Nut, Straight Boot	<u>1060100110</u>
ST Connector, Multimode, 127µm Ceramic PC+ Ferrule, 1.60mm and 2.00mm Simplex Cable, Polymer Coupling Nut, Straight Boot	<u>1060100140</u>
ST Connector, Multimode, 127µm Ceramic PC+ Ferrule, 1.60mm and 2.00mm Simplex Cable, Polymer Coupling Nut, Straight Boot	<u>1060100160</u>
ST Connector, Multimode, 127µm Ceramic PC+ Ferrule, 2.40mm and 3.00mm Simplex Cable, Polymer Coupling Nut, Short Crimp Boot	<u>1060100200</u>
ST Connector, Multimode, 128µm Ceramic PC+ Ferrule, 1.60mm and 2.00mm Simplex	<u>1060103110</u>

Cable, Polymer
Coupling Nut,
Straight Boot
ST Connector, 1060103200
Multimode
Enhanced, 128µm
Ceramic PC Ferrule,
2.40mm and 3.00mm
Simplex Cable,
Polymer Coupling
Nut, Black Short
Crimp Boot
ST Connector, 1060105100
Singlemode, 126µm
Ceramic PC+
Ferrule, 1.60mm and
2.00mm Simplex
Cable, Polymer
Coupling Nut,
Straight Boot
ST Connector, 1060105130
Singlemode, 126µm
Ceramic PC+
Ferrule, 1.60mm and
2.00mm Simplex
Cable, Polymer
Coupling Nut,
Straight Boot
ST Connector, 1060105200
Singlemode, 126µm
Ceramic PC Ferrule,
2.40mm and 3.00mm
Simplex Cable,
Polymer Coupling
Nut, Black Short
Crimp Boot
ST Connector, 1060120140
Multimode, 127µm
Ceramic PC+
Ferrule, 1.60mm and
2.00mm Simplex
Cable, Red Short
Crimp Boot
ST Connector, 1060120200
Multimode, 127µm
Ceramic PC+
Ferrule, 2.40mm and
3.00mm Simplex
Cable, Metal
Coupling Nut, Black
Short Crimp Boot
ST Connector, 1060122100
Multimode, 125.5µm
Ceramic PC+
Ferrule, 1.60mm and
2.00mm Simplex
Cable, Black Short
Crimp Boot
ST Connector, 1060123100
Multimode, 128µm
Ceramic PC+
Ferrule, 1.60mm and
2.00mm Simplex
Cable, Black Short
Crimp Boot

ST Connector, 1060123200
Multimode, 128µm
Ceramic PC Ferrule,
2.40mm and 3.00mm
Simplex Cable, Metal
Coupling Nut, Black
Short Crimp Boot

ST Connector, 1060125130
Multimode, 126µm
Ceramic PC+
Ferrule, 1.60mm and
2.00mm Simplex
Cable, Yellow Short
Crimp Boot

ST Connector, 1060125200
Singlemode, 126µm
Ceramic PC Ferrule,
2.40mm and 3.00mm
Simplex Cable, Metal
Coupling Nut, Black
Short Crimp Boot

Tight-Jacketed 1060212200
Cable LC Connector,
Singlemode, Blue
Housing, Straight
Boot, Duplex Cable,
Diameter 2.00mm

Tight-Jacketed 1060212300
Cable LC Connector,
Multimode, Beige
Housing, Straight
Boot, Duplex Cable,
Diameter 2.00mm

Tight-Jacketed 1060212400
Cable LC Connector,
Singlemode, APC,
Green Housing,
Straight Boot,
Simplex Cable,
Diameter 2.00mm

Tight-Jacketed 1060212600
Cable LC Connector,
Multimode, without
APC, Beige Housing,
Straight Boot,
Simplex Cable,
Diameter 2.00mm

Tight-Jacketed 1060213300
Cable LC Connector,
Multimode, Beige
Housing, 900 Boot,
Duplex Cable,
Diameter 2.00mm

Tight-Jacketed 1060214300
Cable LC Connector,
Multimode, Beige
Housing, 900 Boot,
Simplex Cable,
Diameter 2.00mm

SC Connector, 1060320125
Multimode, 127µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Beige

Housing, Beige 45°
Boot, Tunable
SC Connector, [1060320900](#)
Multimode, 127µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Blue
Housing, Blue Boot,
Tunable
SC Connector, [1060320950](#)
Multimode, 127µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Beige
Housing, White Boot,
Tunable
SC Connector, [1060320970](#)
Multimode, 127µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Black
Housing, Black Boot,
Tunable
SC Connector, [1060322125](#)
Singlemode,
125.5µm Ceramic
Ferrule, 2.00mm
and 1.60mm Zipcord
Cable, Blue Housing,
Yellow 45° Boot,
Tunable
SC Connector, [1060322165](#)
Singlemode,
125.5µm Ceramic
Ferrule, 2.00mm
and 1.60mm Zipcord
Cable, Blue Housing,
White 45° Boot,
Tunable
SC Connector, [1060322900](#)
Singlemode,
125.5µm Ceramic
Ferrule, 2.00mm
and 1.60mm Zipcord
Cable, Blue Housing,
Yellow Boot, Tunable
SC Connector, [1060322950](#)
Singlemode,
125.5µm Ceramic
Ferrule, 2.00mm
and 1.60mm Zipcord
Cable, Blue Housing,
White Boot, Tunable
SC Connector, [1060322970](#)
Singlemode,
125.5µm Ceramic
Ferrule, 2.00mm
and 1.60mm Zipcord
Cable, Black
Housing, Black Boot,
Tunable
SC Connector, [1060323125](#)
Multimode, 128µm
Ceramic Ferrule,
2.00mm and 1.60mm

Zipcord Cable, Beige
Housing, Beige 45°
Boot, Tunable
SC Connector, [1060323950](#)
Multimode, 128µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Beige
Housing, White Boot,
Tunable
SC Connector, [1060323970](#)
Multimode, 128µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Black
Housing, Black Boot,
Tunable
SC Connector, [1060324125](#)
Singlemode, 125µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Blue
Housing, Yellow 45°
Boot, Tunable
SC Connector, [1060324165](#)
Singlemode, 125µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Blue
Housing, White 45°
Boot, Tunable
SC Connector, [1060324900](#)
Singlemode, 125µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Blue
Housing, Yellow
Boot, Tunable
SC Connector, [1060324950](#)
Singlemode, 125µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Blue
Housing, White Boot,
Tunable
SC Connector, [1060324970](#)
Singlemode, 125µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Black
Housing, Black Boot,
Tunable
SC Connector, [1060325125](#)
Singlemode, 126µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Blue
Housing, Yellow 45°
Boot, Tunable
SC Connector, [1060325165](#)
Singlemode, 126µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Blue

Housing, White 45°
Boot, Tunable
SC Connector, [1060325950](#)
Singlemode, 126µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Blue
Housing, White Boot,
Tunable
SC Connector, [1060325970](#)
Singlemode, 126µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Black
Housing, Black Boot,
Tunable
SC Connector, [1060325990](#)
Singlemode, 126µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Blue
Housing, Yellow
Boot, Tunable, Bulk
Package
SC Connector, [1060326900](#)
Singlemode,
125.5µm Ceramic
Ferrule, 2.00mm
and 1.60mm Zipcord
Cable, Blue Housing,
Yellow Boot, Tunable
SC Connector, [1060326950](#)
Singlemode,
125.5µm Ceramic
Ferrule, 2.00mm
and 1.60mm Zipcord
Cable, Blue Housing,
Yellow Boot, Tunable
SC Connector, [1060327125](#)
Singlemode, 127µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Blue
Housing, Yellow 45°
Boot, Tunable
SC Connector, [1060327165](#)
Singlemode, 127µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Blue
Housing, White 45°
Boot, Tunable
SC Connector, [1060327900](#)
Singlemode, 127µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Blue
Housing, Yellow
Boot, Tunable
SC Connector, [1060327950](#)
Singlemode, 127µm
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Blue

Housing, White Boot,
Tunable
SC Connector, 1060327970
Singlemode, 127 μ m
Ceramic Ferrule,
2.00mm and 1.60mm
Zipcord Cable, Black
Housing, Black Boot,
Tunable
SC/APC Connector, 1060332900
Tunable, 125.5 μ m,
Ceramic Ferrule,
2.0mm and 1.60mm
Simplex Cable,
Green Boot
SC/APC Connector, 1060334900
Tunable, 125 μ m,
Ceramic Ferrule,
2.0mm and 1.60mm
Simplex Cable,
Green Boot
SC/APC Connector, 1060335900
Tunable, 126 μ m,
Ceramic Ferrule,
2.0mm and 1.60mm
Simplex Cable,
Green Boot
FC Connector, 1060530000
Multimode, 127 μ m
Ferrule, 3.00mm
Cable Diameter,
Metal Coupling Nut,
Black Boot
FC Connector, 1060530100
127 μ m, Ceramic
Ferrule, 1.60mm and
2.00mm Multimode
Cable, Black Boot
FC Connector, 1060530500
Multimode, 127 μ m
Ferrule, .90mm
Buffered Fiber, Metal
Coupling Nut, Black
Boot
FC Connector, 1060532000
Singlemode,
125.5 μ m Ferrule,
3.00mm Cable
Diameter, Metal
Coupling Nut, Yellow
Boot
FC Connector, 1060532070
Singlemode,
125.5 μ m Ferrule,
3.00mm Cable
Diameter, Metal
Coupling Nut, Black
Boot
FC Connector, 1060532100
Singlemode,
125.5 μ m Ferrule,
1.60mm / 2.00mm
Cable Diameter,
Yellow Boot

FC Connector, Singlemode, 125.5µm Ferrule, 1.60mm / 2.00mm Cable Diameter, Black Boot	<u>1060532170</u>
FC Connector, Multimode, 128µm Ferrule, 3.00mm Cable Diameter, Metal Coupling Nut, Black Boot	<u>1060533000</u>
FC Connector, Multimode, 128µm Ferrule, 1.60mm / 2.00mm Cable Diameter, Black Boot	<u>1060533170</u>
FC Connector, Multimode, 128µm Ferrule, .90mm Buffered Fiber, Metal Coupling Nut, Black Boot	<u>1060533500</u>
FC Connector, 125µm, Ceramic Ferrule, 1.60mm and 2.00mm Singlemode Cable, Yellow Boot	<u>1060534100</u>
FC Connector, 125µm, Ceramic Ferrule, 1.60mm and 2.00mm Singlemode Cable, Black Boot	<u>1060534170</u>
FC Connector, Singlemode, 125µm Ceramic PC Ferrule, 900mm Buffered Fiber, Metal Coupling Nut, Yellow Boot	<u>1060534500</u>
FC Connector, Singlemode, 126µm Ferrule, 3.00mm Cable Diameter, Metal Coupling Nut, Yellow Boot	<u>1060535000</u>
FC Connector, Singlemode, 126µm Ferrule, 3.00mm Cable Diameter, Metal Coupling Nut, Black Boot	<u>1060535070</u>
FC Connector, Singlemode, 126µm Ferrule, 1.60mm / 2.00mm Cable Diameter, Yellow Boot	<u>1060535100</u>
FC Connector, 126µm, Ceramic Ferrule, 1.60mm and 2.00mm Singlemode Cable, Yellow Boot, 100 Piece Bulk Package	<u>1060535110</u>

FC Connector, 1060535500
Singlemode, 126µm
Ceramic PC Ferrule,
900mm Buffered
Fiber, Metal Coupling
Nut, Yellow Boot

FC Connector, 1060537100
127µm, Ceramic
Ferrule, 1.60mm and
2.00mm Singlemode
Cable, Yellow Boot

FC Connector, 1060537170
127µm, Ceramic
Ferrule, 1.60mm and
2.00mm Singlemode
Cable, Black Boot

FC Connector, APC, 1060555000
Singlemode, 126µm
Angled Ferrule,
3.00mm Cable
Diameter, Metal
Coupling Nut, Green
Boot, Tight Fit Key

FC Connector, 1060555500
APC, Singlemode,
126µm Angled
Ferrule, .90mm
Buffered Fiber, Metal
Coupling Nut, Green
Boot, Tight Fit Key

FC Connector, 1060556550
APC, Singlemode,
125.5µm Ceramic
Ferrule, 900mm
Buffered Fiber, Metal
Coupling Nut, Green
Boot, Tight Fit Key

FC Connector, APC, 1060565000
Singlemode, 126µm
Angled Ferrule,
3.00mm Cable
Diameter, Metal
Coupling Nut, Green
Boot, Standard Key

FC Connector, 1060565500
APC, Singlemode,
126µm Angled
Ferrule, .90mm
Buffered Fiber, Metal
Coupling Nut, Green
Boot, Standard Key

Optical Industrial 1060592100
Plug Assembly Metal
Body with Logo,
Multimode

Optical Industrial 1060592500
Plug Assembly Metal
Body with Logo,
Single Mode

Optical Industrial 1060596100
Cable Assembly,
MPO Multi-fiber,
Outdoor Cable,
Multimode, Male

Optical Industrial Cable Assembly, MPO Multi-fiber, Outdoor Cable, Multimode, Male	<u>1060596105</u>
MTP INDUSTRIAL CONNECTOR,12 FIB,MM, MALE	<u>1060596110</u>
Optical Industrial Cable Assembly, MPO Multi-fiber, Outdoor Cable, Singlemode, Male	<u>1060596115</u>
Optical Industrial Cable Assembly, MPO Multi-fiber, Outdoor Cable, Singlemode, Male	<u>1060596120</u>
Optical Industrial Cable Assembly, MPO Multi-fiber, Outdoor Cable, Singlemode, Male	<u>1060596125</u>
Optical Industrial Cable Assembly, MPO Multi-fiber, Outdoor Cable, Singlemode Enhanced, Male	<u>1060596130</u>
Optical Industrial Cable Assembly, MPO Multi-fiber, Outdoor Cable, Singlemode, Female	<u>1060596155</u>
Optical Industrial Cable Assembly, MPO Multi-fiber, Outdoor Cable, Singlemode Enhanced, Female	<u>1060596165</u>
Optical Industrial Plug Assembly, Metal Body, Outdoor Cable, LC, Multimode Male with Logo	<u>1060597100</u>
Optical Industrial Plug Assembly, Metal Body, Outdoor Cable, LC, Multimode, Male	<u>1060597300</u>
Optical Industrial Plug Assembly, Metal Body, Outdoor Cable, LC, Singlemode Male with Logo	<u>1060597500</u>
Optical Industrial Plug Assembly, Metal Body, Outdoor Cable, LC, Singlemode, Male	<u>1060597700</u>
Optical Industrial Plug Assembly, Metal Body,	<u>1060597900</u>

Outdoor Cable, LC, Singlemode, Male Optical Industrial Plug Connector, Metal Body, LC, Multimode	<u>1060598000</u>
Optical Industrial Plug Connector, Metal Body, LC, Single Mode	<u>1060598008</u>
Optical Industrial Plug Connector, Metal Body with Logo, LC, Multimode	<u>1060598020</u>
Optical Industrial Plug Connector, Plastic Body, LC, Multimode	<u>1060598100</u>
Optical Industrial Plug Connector, Plastic Body with Logo, LC, Multimode	<u>1060598120</u>
Optical Industrial Plug Connector, Plastic Body with Logo, LC, Single Mode	<u>1060598128</u>
Tight-Jacketed Cable SC Connector, Multimode, Beige Housing, Straight Boot, Duplex Cable, Diameter 2.00mm	<u>1060632330</u>
SnapMate Optical Interconnect System, Complete Kit (Housing, Plugs, Spring and Alignment Sleeve)	<u>1060730020</u>
SnapMate Optical Interconnect System, Housing and Alignment Sleeve Kit	<u>1060730021</u>
SnapMate Optical Interconnect System, Plug and Spring Kit	<u>1060730022</u>
MTP*-CPI (Coplanar Interconnect) Removal Clip	<u>1060880800</u>
EMI Multi-format (LC-LC/MU/LX.5) Adapter, Angled, Duplex, Metal Body, Ceramic Alignment Sleeve, Rear Mount Single Screw Style, Internal Shutter	<u>1061009000</u>
HBM High Density Backplane Motherboard Adapter Housing, APC, Singlemode and Multimode, Black Body, Bare Ribbon	<u>1061051000</u>

Fiber, Screw Mount Style, 4 Positions HBMT High	<u>1061051100</u>
Density Backplane Daughtercard Connector Housing, Singlemode and Multimode, Black Body, Bare Ribbon Fiber, Screw Mount Style, 4 Positions HBMT High	<u>1061052000</u>
Density Backplane Motherboard Adapter Housing, APC, Singlemode and Multimode, Black Body, Bare Ribbon Fiber, Screw Mount Fixed Style, 4 Positions HBMT High	<u>1061052100</u>
Density Backplane Daughtercard Connector Housing, Singlemode and Multimode, Black Body, Bare Ribbon Fiber, Rivet Mount Floating Style, 4 Positions SMI Optical	<u>1061083100</u>
Interconnect, Transceiver, Ethernet, Through Hole, Fiber Optic Transceiver (FOT) Signal SMI Optical	<u>1061084100</u>
Interconnect, Transceiver, Industrial Data Link, Through Hole, Fiber Optic Transceiver (FOT) Signal ST Adapter, Metal	<u>1061101000</u>
Body, Ceramic Alignment Sleeve, D- Hole Mount Style ST Adapter,	<u>1061121000</u>
Metal Body, Metal Alignment Sleeve, D- Hole Mount Style ST Adapter, Metal	<u>1061131000</u>
Body, Polymer Alignment Sleeve, D- Hole Mount Style EMI SC Adapter,	<u>1061161000</u>
Angled, Duplex, Metal Body, Ceramic Alignment Sleeve, Screw Mount Style, Shutter One Side EMI SC Adapter,	<u>1061161001</u>
Angled, Duplex,	

Metal Body, Ceramic
Alignment Sleeve,
Screw Mount Style
EMI SC Adapter, 1061162110
Simplex, Metal Body,
Screw Mount Style,
Shutter
EMI SCAPC 1061164520
Adapter, Angled,
Metal Body, Ceramic
Alignment Sleeve,
Snap/Screw Mount
Style, Shutter Snap-
on
LC Adapter, Duplex, 1061260790
Metal Body, Metal
Alignment Sleeve,
Screw Mount Style,
SC Footprint
LC Adapter Kit, 1061261700
Duplex, Snap Mount,
Includes LC Duplex
Receptacle and
Mounting Plate
LC Adapter, Duplex, 1061271694
Singlemode/
Multimode, Zirconia
Alignment Sleeve,
No Mounting Plate,
Metal Body and
Shutter
LC Adapter, Duplex, 1061271695
Singlemode/
Multimode, Zirconia
Alignment Sleeve,
Snap Mount Style,
Metal Body and
Shutters, Nylon Dust
Caps
LC Adapter, Duplex, 1061271790
Singlemode/
Multimode, Zirconia
Alignment Sleeve,
#2-56 Threaded
Insert Style, Rear
Mount, Metal Body
and Shutter
LC Adapter, Duplex, 1061271890
Singlemode/
Multimode, Zirconia
Alignment Sleeve,
#2-56 Threaded
Insert Style, Front
Mount, Metal Body
and Shutter
LC Adapter, Duplex, 1061271990
Singlemode/
Multimode, Phosphor
Bronze Alignment
Sleeve, Front Mount,
Metal Body and
Shutter
FC Adapter, Metal 1061520000
Body, Ceramic
Alignment Sleeve,

Square Hole Mount Style, Standard Key FC Adapter, Metal Body, Ceramic Alignment Sleeve, Square Flange Mount Style, Standard Key (Bulk 100 pieces)	<u>1061520100</u>
FC Adapter, Metal Body, Ceramic Alignment Sleeve, Square Flange Mount Style, Standard Key	<u>1061520200</u>
FC Adapter, Metal Body, Ceramic Alignment Sleeve, D-Hole Mount Style, Standard Key	<u>1061521000</u>
FC Adapter, APC, Metal Body, Ceramic Alignment Sleeve, D- Hole Mount Style	<u>1061521200</u>
FC Adapter, APC, Metal Body, Ceramic Alignment Sleeve, Square Flange Mount Style, Tight Fit Key	<u>1061522000</u>
FC Adapter, APC, Metal Body, Ceramic Alignment Sleeve, D-Hole Mount Style, Tight Fit Key	<u>1061523000</u>
FC Adapter, Metal Body, Metal Alignment Sleeve, Square Flange Mount Style, Standard Key	<u>1061560100</u>
FC Adapter, Metal Body, Metal Alignment Sleeve, D-Hole Mount Style, Standard Key	<u>1061561000</u>
FC Adapter, Metal Body and Sleeve, D- Hole Mount Style, Tight Fit Key	<u>1061563000</u>
SC Adapter, Black Body, Metal Alignment Sleeve, Snap and Standard Flange Mount Style	<u>1061602000</u>
SC Adapter, Beige Body, Metal Alignment Sleeve, Snap and Standard Flange Mount Style	<u>1061605000</u>
SC Adapter, Blue Body, Ceramic Alignment Sleeve, Snap and Standard Flange Mount	<u>1061610500</u>

Style, Standard SC Footprint, Shutter SC/APC Adapter, Green Body, Ceramic Alignment Sleeve, Snap and Standard Flange Mount Style	<u>1061613000</u>
SC/APC Adapter, Green Body, Ceramic Alignment Sleeve, Snap and Standard Flange Mount	<u>1061613500</u>
Style, Standard SC Footprint, Shutter ST-FC Adapter, Metal Body, Metal Alignment Sleeve, Standard Key	<u>1061720000</u>
MTP* Adapter Assembly, 1.75mm Panel Thickness, Screw Mount, Black	<u>1061810000</u>
MTP* Adapter Assembly, Reduced Flange, 1.75mm Panel Thickness, Snap Mount, Black	<u>1061810007</u>
MTP Quad Adapter Assembly, 1.75mm Panel Thickness, 30 °, Screw Mount, Black	<u>1061810020</u>
Standard ST Type Adapter, Ceramic, Sleeve, Red Dust Cap and Black Body	<u>1061960430</u>
MPO Female-to- MPO Female Trunk Cable Assembly, 50/125µm, 3.00mm, Multimode, 12 Fiber, Plenum, OM3, 10.0m Length, Aqua	<u>1062250025</u>
MPO Female-to- MPO Female Trunk Cable Assembly, 50/125µm, 4.80mm, Multimode, 12 Fiber, Plenum, OM3, 50.0m Length, Aqua	<u>1062250027</u>
MPO Female-to- MPO Female Trunk Cable Assembly, 9/125µm, 3.00mm, Singlemode, 12 Fiber, Plenum, OS2, 10.0m Length, Yellow	<u>1062250033</u>
MPO Female-to- MPO Female Trunk Cable Assembly, 9/125µm, 4.80mm, Singlemode, 12	<u>1062250035</u>

Fiber, Plenum, OS2, 50.0m Length, Yellow	
MPO Female-to- MPO Female Trunk Cable Assembly, 50/125µm, 3.80mm, Multimode, 12 Fiber, Plenum, OM3, 10.0m Length, Aqua	<u>1062250037</u>
MPO Female-to- MPO Female Trunk Cable Assembly, 9/125µm, 3.80mm, Singlemode, 12 Fiber, Plenum, OS2, 10.0m Length, Yellow	<u>1062250045</u>
MPO Female-to- MPO Female Trunk Cable Assembly, 9/125µm, 5.40mm, Singlemode, 12 Fiber, Plenum, OS2, 50.0m Length, Yellow	<u>1062250047</u>
VersaBeam POD Cable Assembly, Male, Multimode, 50/125µm, 12 Fiber Bare Ribbon, 0.50m	<u>1062672011</u>
VersaBeam POD Cable Assembly, Male, Multimode, 50/125µm, 12 Fiber Bare Ribbon, 0.20m	<u>1062672013</u>
VersaBeam POD Cable Assembly, Male, Multimode, 50/125µm, 24 Fiber Bare Ribbon, 0.50m	<u>1062672031</u>
VersaBeam POD Cable Assembly, Male, Multimode, 50/125µm, 48 Fiber Bare Ribbon, 0.50m	<u>1062672051</u>
VersaBeam MT Interconnects, 50/125um, 1.0m Pigtail	<u>1062680002</u>
1-by-3 Circular MT Connector and Adapter Assembly, 3.0m Cable Length	<u>1062750000</u>
Circular MT Connector and Receptacle Cable Assembly 3.0m	<u>1062770000</u>
Quad Small Form- factor Pluggable Plus (QSFP+) Optical Jumper Cable Assembly, 4 TX, 4 RX; 8 Fiber MTP Multimode 50/125µm	<u>1062830002</u>

3.00mm Round
Cable Plenum,
Standard Bandwidth
(OM2), 2.0m (6.56')
Length, Orange
Cable
Quad Small Form- [1062830003](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum,
Standard Bandwidth
(OM2), 3.0m (9.84')
Length, Orange
Cable
Quad Small Form- [1062830009](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum,
Standard Bandwidth
(OM2), 9.0m
(29.53') Length,
Orange Cable
Quad Small Form- [1062830010](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum,
Standard Bandwidth
(OM2), 10.0m
(32.81') Length,
Orange Cable
Quad Small Form- [1062830011](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum,
Standard Bandwidth
(OM2), 11.0m
(36.09') Length,
Orange Cable
Quad Small Form- [1062830012](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm

3.00mm Round
Cable Plenum,
Standard Bandwidth
(OM2), 12.0m
(39.37') Length,
Orange Cable
Quad Small Form- [1062830020](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum,
Standard Bandwidth
(OM2), 20.0m
(65.62') Length,
Orange Cable
Quad Small Form- [1062831002](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM3),
2.0m (6.56') Length,
Aqua Cable
Quad Small Form- [1062831006](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM3),
6.0m (19.68')
Length, Aqua Cable
Quad Small Form- [1062831008](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM3),
8.0m (26.25')
Length, Aqua Cable
Quad Small Form- [1062831009](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM3),

9.0m (29.53')
Length, Aqua Cable
Quad Small Form- [1062831011](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM3),
11.0m (36.09')
Length, Aqua Cable
Quad Small Form- [1062831012](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM3),
12.0m (39.37')
Length, Aqua Cable
Quad Small Form- [1062831013](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM3),
13.0m (42.65')
Length, Aqua Cable
Quad Small Form- [1062831014](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM3),
14.0m (45.93')
Length, Aqua Cable
Quad Small Form- [1062831030](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
4.50mm Round
Cable Plenum, High
Bandwidth (OM3),
30.0m (98.40')
Length, Aqua Cable
Quad Small Form- [1062831050](#)
factor Pluggable
Plus (QSFP+)

Optical Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
4.50mm Round
Cable Plenum, High
Bandwidth (OM3),
50.0m (164.04')
Length, Aqua Cable
Quad Small Form- 1062831055
factor Pluggable
Plus (QSFP+)
Optical Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
4.50mm Round
Cable Plenum,
High Bandwidth
(OM3), 55.0m
(180.45')Length,
Aqua Cable
Quad Small Form- 1062831070
factor Pluggable
Plus (QSFP+)
Optical Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
4.50mm Round
Cable Plenum, High
Bandwidth (OM3),
70.0m (229.66')
Length, Aqua Cable
Quad Small Form- 1062831100
factor Pluggable
Plus (QSFP+)
Optical Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
4.50mm Round
Cable Plenum,
High Bandwidth
(OM3),100.0m
(328.08') Length,
Aqua Cable
Quad Small Form- 1062834001
factor Pluggable
(QSFP) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Singlemode 9/125µm
3.00mm Round
Cable Plenum, OS2,
1.0m (3.28') Length,
Aqua Cable
Quad Small Form- 1062834003
factor Pluggable
(QSFP) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Singlemode 9/125µm

3.00mm Round
Cable Plenum, OS2,
3.0m (9.84') Length,
Aqua Cable
Quad Small Form- 1062834005
factor Pluggable
(QSFP) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Singlemode 9/125µm
3.00mm Round
Cable Plenum, OS2,
5.0m (16.40') Length,
Aqua Cable
Quad Small Form- 1062834010
factor Pluggable
(QSFP) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Singlemode 9/125µm
3.00mm Round
Cable Plenum,
OS2, 10.0m (32.81')
Length, Aqua Cable
Quad Small Form- 1062834012
factor Pluggable
(QSFP) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Singlemode 9/125µm
3.00mm Round
Cable Plenum,
OS2, 20.0m (65.62')
Length, Aqua Cable
Quad Small Form- 1062835001
factor Pluggable Plus
(QSFP+) Optical
Breakout Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
- 8 LC Multimode
50/125µm 3.00mm
Round Cable
Plenum, Standard
Bandwidth (OM 2),
1.0m (3.28') Length
Quad Small Form- 1062835002
factor Pluggable Plus
(QSFP+) Optical
Breakout Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
- 8 LC Multimode
50/125µm 3.00mm
Round Cable
Plenum, Standard
Bandwidth(OM2),
3.0m (9.84') Length
Quad Small Form- 1062835004
factor Pluggable Plus
(QSFP+) Optical
Breakout Cable

Assembly, 4 TX, 4
RX; 8 Fiber MTP
- 8 LC Multimode
50/125µm 3.00mm
Round Cable
Plenum, Standard
Bandwidth(OM2),
10.0m (32.81')
Length
Quad Small Form- [1062835009](#)
factor Pluggable Plus
(QSFP+) Optical
Breakout Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
- 8 LC Multimode
50/125µm 3.00mm
Round Cable
Plenum, Standard
Bandwidth (OM 2),
2.0m (6.56') Length
Quad Small Form- [1062835105](#)
factor Pluggable
Plus (QSFP+)
Optical Breakout
Cable Assembly,
4 TX, 4 RX; 8
Fiber MTP - 8LC
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM3),
15.0m (49.21')
Length, Aqua Cable
Quad Small Form- [1062835107](#)
factor Pluggable
(QSFP) Optical
Breakout Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
- 8 LC Multimode
50/125µm 3.00mm
Round Cable
Plenum, High
Bandwidth (OM3),
20.0m (65.62')
Length, Aqua Cable
Quad Small Form- [1062835202](#)
factor Pluggable Plus
(QSFP+) Optical
Breakout Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
- 8LC Multimode
50/125µm 3.00mm
Round Cable
Plenum, Standard
Bandwidth (OM2),
3.0m (9.84') Length,
Aqua Cable
Quad Small Form- [1062835301](#)
factor Pluggable
Plus (QSFP+)
Optical Breakout
Cable Assembly,

4 TX, 4 RX; 8
Fiber MTP - 8LC
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM3),
1.0m (3.28') Length,
Aqua Cable
Quad Small Form- [1062835302](#)
factor Pluggable
Plus (QSFP+)
Optical Breakout
Cable Assembly,
4 TX, 4 RX; 8
Fiber MTP - 8LC
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM3),
3.0m (9.84') Length,
Aqua Cable
Quad Small Form- [1062835303](#)
factor Pluggable
Plus (QSFP+)
Optical Breakout
Cable Assembly,
4 TX, 4 RX; 8
Fiber MTP - 8LC
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM3),
5.0m (16.40')
Length, Aqua Cable
Quad Small Form- [1062835304](#)
factor Pluggable
Plus (QSFP+)
Optical Breakout
Cable Assembly,
4 TX, 4 RX; 8
Fiber MTP - 8LC
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM3),
10.0m (32.81')
(32.81') Length,
Aqua Cable
Quad Small Form- [1062837001](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM4),
1.0m (3.28') Length,
Aqua Cable
Quad Small Form- [1062837002](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4

RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM4),
2.0m (6.56') Length,
Aqua Cable
Quad Small Form- [1062837004](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM4),
4.0m (13.12')
Length, Aqua Cable
Quad Small Form- [1062837005](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM4),
5.0m (16.40')
Length, Aqua Cable
Quad Small Form- [1062837006](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM4),
6.0m (19.68')
Length, Aqua Cable
Quad Small Form- [1062837007](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM4),
7.0m (22.97')
Length, Aqua Cable
Quad Small Form- [1062837011](#)
factor Pluggable Plus
(QSFP+) Optical
Jumper Cable
Assembly, 4 TX, 4
RX; 8 Fiber MTP
Multimode 50/125µm
3.00mm Round
Cable Plenum, High
Bandwidth (OM4),

11.0m (36.09')
Length, Aqua Cable

This document was generated on 08/09/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION