

FO patch cable - FOC-SC:A-LC:A-GZ03/2 - 1400681

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Assembled FO cable, zip cord cable, multi-mode fiberglass 50/125 μm , OM4, plug: LC/SC duplex, degree of protection: IP20, for installation in cable ducts or control cabinets, length: 2 m

Your advantages

- ✓ Multi-mode patch cable for indoor installation
- ✓ Ideal for use in distributor systems and for connecting termination devices
- ✓ All components satisfy UL 94, V0
- ✓ 2.8 mm single elements made from halogen-free and flame-retardant material
- ✓ Interferometer tests at every stage of the certification process
- ✓ Excellent mechanical and optical properties
- ✓ Satisfies optical and mechanical industry standards
- ✓ Connector with UPC polishing for optimum attenuation values
- ✓ Low-bend fiber
- ✓ Individual test report with ≤ 0.3 dB insertion loss, measured according to IEC 61300-3-4
- ✓ Individual test report with ≥ 35 dB return loss, measured according to IEC 61300-3-6
- ✓ Comprehensively tested according to IEC 61753-122-2 and IEC 61753-1 Cat. C
- ✓ Temperature fluctuation test according to IEC 61300-2-1
- ✓ Vibration test according to IEC 61300-2-1
- ✓ Tensile strength of the cable connection according to IEC 61300-2-5

Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 pc |
| GTIN |  4 046356 734905 |
| GTIN | 4046356734905 |

Technical data

Mechanical characteristics

| | |
|---------------------|---|
| Number of positions | 2 |
| Number of fibers | 2 |

FO patch cable - FOC-SC:A-LC:A-GZ03/2 - 1400681

Technical data

Mechanical characteristics

| | |
|----------------------|----------|
| Type of cable | Zip cord |
| Length of cable | 2.00 m |
| Color | violet |
| Degree of protection | IP20 |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -10 °C ... 60 °C |
| Ambient temperature (assembly) | -5 °C ... 50 °C |
| Ambient temperature (storage/transport) | -10 °C ... 60 °C |

Material data

| | |
|--|-------------------|
| Flammability rating according to UL 94 | V0 |
| External sheath, color | Violet |
| Ferrule material | Zirconia ceramics |

Electrical characteristics

| | |
|--------------------|-----|
| Transmission speed | OM4 |
|--------------------|-----|

Standards and Regulations

| | |
|--|------------------------------|
| Halogen-free | complying with IEC 60754-1/2 |
| Flammability rating according to UL 94 | V0 |

Line characteristics

| | |
|---|---|
| Type of cable | Zip cord |
| Cable type | Fiberglass |
| Cable abbreviation | I-V(ZN)H |
| Wire colors | - |
| External sheath, color | Violet |
| Cable, attenuation | 2.5 dB/km (at 850 nm), 0.7 dB/km (at 1300 nm) |
| Cable weight | 15.80 kg/km |
| Smallest bending radius, fixed installation | 15 mm |
| Smallest bending radius, movable installation | 30 mm |
| Tensile strength short-term/long-term | 600 N |
| cable layer type | Indoors |
| Halogen-free | complying with IEC 60754-1/2 |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50 |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Approvals

Approvals

FO patch cable - FOC-SC:A-LC:A-GZ03/2 - 1400681

Approvals


Approvals

UL Listed / EAC

Ex Approvals

Approval details

| | | |
|-----------|---|--|
| UL Listed |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E308814-20070105 |
|-----------|---|--|

| | | |
|-----|---|---------|
| EAC |  | B.00767 |
|-----|---|---------|

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>