

USB-C Multiport Adapter - 4K HDMI, USB-A, GbE, 100W PD Charging, HDCP, Gray

MODEL NUMBER: U444-06N-H4GUSC



4K USB-C adapter connects a 4K HDMI monitor, USB peripheral and wired Gigabit Ethernet network to a USB-C or Thunderbolt 3 device.

Features

USB 3.1 Type-C Adapter Connects an HDMI Monitor to Your USB-C or Thunderbolt 3 Device

This USB 3.1 C adapter helps you transmit digital audio and 4K video from your tablet, laptop, Chromebook, MacBook, smartphone or PC to an HDMI-enabled television, monitor or projector. It's an ideal tool for giving video presentations in conference rooms and classrooms, editing multiple documents on a larger screen, or streaming video for digital signage in crystal-clear 4K.

Supports USB-C DisplayPort Alternate Mode for Transmitting Audio/Video Signals

By connecting the built-in USB-C cable to a source device that supports USB DisplayPort Alt Mode, you can output 4K video and digital audio to a compatible monitor, television or projector without installing special software drivers.

Transmits Crystal-Clear 4K HDMI Video and Digital Audio

To send digital audio and Ultra High Definition video to a 4K-ready HDMI television, projector or monitor, connect the HDMI port to the display using an HDMI cable (such as Tripp Lite's P568-Series high-speed HDMI cables, sold separately). The USB to HDMI 4K adapter supports video resolutions up to 4K @ 30 Hz (3840 x 2160). It's backward compatible with 1080p displays, allowing you to use it with older equipment.

Connects USB Peripherals and Transfers Data at Fast USB 3.1 Gen 1 Speeds

The USB-A port accepts USB peripherals, such as a flash drive, mouse, keyboard or printer, and provides up to 5V/1.5A (7.5 watts) for charging and powering mobile devices. It transfers data at speeds up to 5 Gbps, which is 10 times faster than USB 2.0. The USB Type-C adapter is backward compatible with previous USB generations, so you can continue using older peripherals while getting high-speed performance from new devices. **Note:** Host must support USB OTG (On-the-Go).

PD Charging Port Charges Connected Device via AC Wall Charger

The USB-C Power Delivery 3.0 port provides power output up to 5 amps (100 watts), which is more than sufficient for charging and powering the connected source device, such as a MacBook or Chromebook.

Note: USB-C PD port does not support Quick Charge (QC).

Accesses a Wired Gigabit Ethernet Network

The RJ45 port offers access to a Gigabit Ethernet network when Wi-Fi is unavailable or when a wired connection offers faster speeds. Connect using a UTP cable (such as Tripp Lite's N201-Series Cat6 snagless patch cables, sold separately), and enjoy true 10/100/1000 Mbps (1 Gbps) Ethernet speeds for fast data transfers.

Built-In USB-C Cable Connects in Either Direction

Connect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

Ready to Use Right Out of the Package

The plug-and-play USB 3.1 Type-C adapter is specifically designed for the MacBook, Google

Highlights

- Transmits video signals from sources supporting USB-C DisplayPort Alt Mode
- Delivers UHD picture quality at resolutions up to 4K @ 30 Hz (3840 x 2160)
- Power Delivery port provides 5A (100W) power output for charging connected device
- Connects you to a wired Gigabit Ethernet network when Wi-Fi is weak or unavailable
- USB-A port supports USB 3.1 Gen 1 speeds up to 5 Gbps for fast data transfers

Applications

- Play 4K video from your MacBook or Chromebook on a large-screen HDTV
- Give a video presentation at a meeting, training session or conference
- Write and edit multiple documents on a bigger monitor
- Stream 4K video for digital signage at a trade show
- Charge and power a USB-C or Thunderbolt 3 device
- Connect a USB peripheral, such as an external hard drive, printer or hub
- Upload data from your notebook or download data from the Ethernet at true 10/100/1000 Mbps speeds

System Requirements



Chromebook Pixel and other laptops, tablets and devices equipped with a USB-C or Thunderbolt 3 port. It requires no software, drivers or external power. About the size of a credit card, the U444-06N-H4GUSC fits easily into a pocket, purse or laptop bag for convenient connections on the go.

- Source device with USB-C or Thunderbolt 3 output that supports USB DisplayPort Alternate Mode
- Display device with HDMI input

Package Includes

- U444-06N-H4GUSC USB-C 3.1 to HDMI 4K Adapter with PD Charging, Gray
- Owner's manual

Specifications

OVERVIEW	
UPC Code	037332238764
Technology	Cat5/5e; Cat6; HDMI; USB; USB 3.0 (SuperSpeed); USB 3.1 (Gen 1)
Host Connector	USB C (MALE)
VIDEO	
Max Supported Video Resolution	4K @ 30 Hz (3840 x 2160)
INPUT	
Built-In Cable Length (ft.)	0.392
Built-In Cable Length (m)	0.199
Built-In Cable Length (in.)	4.7
Built-In Cable Length (cm)	11.938
Bus Powered	Yes
Product Length (in.)	6
Product Length (cm.)	15.24
Product Length (ft.)	0.5
Product Length (m.)	0.1524
BATTERY	
Battery Charging (5V/1.5A Port)	Yes
POWER	



USB Power Delivery (PD) Charging Support	Yes
USB Power Delivery (PD) Charging Specification	3.0
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	White = Connected, Orange = Working
CHARGING	
Charging Ports / Amps	1.5A; 5A
PHYSICAL	
Color	Gray
Cable Jacket Rating	VW-1
Material of Construction	Aluminum
Unit Dimensions (hwd / in.)	.51 x 1.77 x 3.35
Unit Packaging Type	Box
Unit Weight (kg)	0.09
Unit Weight (lbs.)	0.2028
ENVIRONMENTAL	
Operating Temperature Range	32 to 113°F (0 to 45°C)
Storage Temperature Range	14 to 158°F (-10 to 70°C)
Operating Humidity Range	10% to 85% RH, non-condensing
Storage Humidity Range	5% to 90% RH, non-condensing
Power Provided to Connected Device(s)	USB-C PD Charging = 20V/5A (100W), USB-A = 5V/1.5A (7.5W)
COMMUNICATIONS	
Network Speed	1Gbps
CONNECTIONS	
Ports	4
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	RJ45 (FEMALE)
Side B - Connector 2	HDMI (FEMALE)
Side B - Connector 3	USB Type-C (FEMALE)
Side B - Connector 4	USB A (FEMALE)
Connector Plating	Nickel



FEATURES & SPECIFICATIONS	
HDCP Specification	1.4
USB Hub Ports	Yes
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
Driver Required	No
STANDARDS & COMPLIANCE	
Certifications	CE, FCC, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>