

4

3

2

1

© 2021 TE Connectivity. All Rights Reserved.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	NC	NEW RELEASE PER E.O.P15990	14MAY1999	-	RDR
	A	REVISED PER PCN E-21-003625	07APR2021	MK	IG

EX. OF MONTH JAN

EX. OF YEAR 1996

TEXT ORIENTATION  
OPTIONAL

ALTERNATE CAP  
CUTOUT POSITIONDESIGNATES REDUCED DIAMETER  
WIRE SERIES

CONTACT SIZE	MIN. INSUL O.D.	MAX. INSUL O.D.	WIRE RANGE [mm <sup>2</sup> ]
16	.053 [1.35]	.120 [3.05]	14-20 AWG [2.0-0.5]

4 MATERIAL: SHELL: HOUSING: PA66 GF15; COLOR: BLACK  
GROMMET: VMQ (BURNT RED)  
FRONT SEAL: VMQ (RED-ORANGE)

4. THIS PLUG MATES WITH DT04-12PA-\*\*\*\* (\*\*\*\* = ALL MODIFICATIONS)  
CONSULT FACTORY FOR MODIFICATIONS.

2 FOR CONTACTS AND WIRE PERFORMANCE AND APPLICATION  
CHARACTERISTICS SEE SPECIFICATION 0425-015-0000

1. USE WITH WEDGELOCK W12S-P012 SOLD SEPARATELY

NOTES:

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN D. SPENCER 28APR1999														
DIMENSIONS: IN [mm]		CHK S. BEARD 28APR1999														
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD R. REED 14MAY1999	NAME 12 WAY PLUG REDUCED WIRE SEAL DT SERIES													
<table border="0"> <tr> <td>0 PLC</td> <td>±-</td> </tr> <tr> <td>1 PLC</td> <td>±-</td> </tr> <tr> <td>2 PLC</td> <td>±-</td> </tr> <tr> <td>3 PLC</td> <td>±.025[0.63]</td> </tr> <tr> <td>4 PLC</td> <td>±-</td> </tr> <tr> <td>ANGLES</td> <td>±-</td> </tr> </table>		0 PLC	±-	1 PLC	±-	2 PLC	±-	3 PLC	±.025[0.63]	4 PLC	±-	ANGLES	±-	PRODUCT SPEC 108-151009	SIZE A3	
0 PLC	±-															
1 PLC	±-															
2 PLC	±-															
3 PLC	±.025[0.63]															
4 PLC	±-															
ANGLES	±-															
MATERIAL		APPLICATION SPEC 114-151009	CAGE CODE 00779	DRAWING NO DT06-12SA-CE11												
FINISH		WEIGHT 16 GR	RESTRICTED TO -													
		CUSTOMER DRAWING		SCALE 1:1												
		SHEET 1 OF 1		REV A												

1470-19 (3/13)