

F463RP125K1L2Z

Not for New Design

F463, Film, Metallized Polypropylene, General Purpose, 1.2 uF, 10%, 1250 VDC, 85°C, Lead Spacing = 37.5mm

FRONT VIEW



Click [here](#) for the 3D model.

Dimensions

L 41mm -0.7mm

H 38mm -0.7mm

Dimensions

T 21mm -0.7mm
S 37.5mm +/-0.5mm
LL 4mm +2mm
F 1mm +/-0.05mm
G 0.5mm NOM

Packaging Specifications

Packaging Pizza, Box
Packaging Quantity 105

General Information

Series F463
Dielectric Metallized Polypropylene
Style Radial
Features MKP, Pulse
RoHS Yes
Lead Cut/Short
AEC-Q200 No
Component Weight 34.4 g
Miscellaneous The Rated Voltage Decreases 2%/C Between +85C And +105C (1.25%/C For AC). ClimCat: 55/105/56.
Notes Series Replaced by R75.

Specifications

Capacitance 1.2 uF
Capacitance Tolerance 10%
Voltage AC 500 VAC
Voltage DC 1250 VDC, 750 VDC (105C)
Temperature Range -55/+105°C
Rated Temperature 85°C
Dissipation Factor 0.1% 1kHz
Insulation Resistance 25 GOhms
Max dV/dt 400 V/us
Inductance 6 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 5/18/2023 - 41383aa6-d214-4cd2-987c-23cc0d12f3a1

© 2006 - 2023 KEMET

Generated 5/18/2023 - 41383aa6-d214-4cd2-987c-23cc0d12f3a1

© 2006 - 2023 KEMET