

USB-C Female to USB-A Male Adapter, USB 3.0

MODEL NUMBER: U329-000



USB-A male to USB-C female adapter connects your smartphone, tablet or Ultrabook to a laptop or desktop PC.

Features

Use Your Existing USB-A Device with a USB Type-C Cable Recommended for charging or synchronizing data on your USB-A computer, laptop or tablet (Note, video is not supported) Data transfer speeds up to 5 Gbps—10 times faster than USB 2.0 Backward compatible with previous USB generations

Reversible USB-C Female Connector Fumble-free reversible port can be connected in either direction to ensure fast, easy connection every time

Premium Construction Molded connectors and gold-plated contacts for maximum conductivity and minimum data loss Slim, sleek design tailored for emerging design trends toward smaller devices

Highlights

- Data transfer speeds up to 5 Gbps—10 times faster than USB 2.0
- Supports power output up to 900mA
- Reversible USB-C port provides fumble-free connection
- Gold-plated contacts for maximum conductivity and minimum data loss
- Backward compatible with previous USB generations

System Requirements

- USB-A host
- Device with USB-C female connector
- USB Type-C M/M Cable

Package Includes

- U329-000 USB 3.0 SuperSpeed Adapter, USB-A Male to USB Type-C Female (M/F)

Specifications

OVERVIEW	
UPC Code	037332213976
Technology	USB; USB 3.x
INPUT	
Bus Powered	Yes
POWER	
USB Power Delivery (PD) Charging Support	No
PHYSICAL	
Color	Black

Material of Construction	PVC, UL94V-0
Shipping Dimensions (hwd / in.)	5.90 x 3.90 x 0.50
Shipping Dimensions (hwd / cm)	14.99 x 9.91 x 1.27
Shipping Weight (lbs.)	0.02
Unit Dimensions (hwd / in.)	0.310 x 0.630 x 1.100
Unit Dimensions (hwd / cm)	0.79 x 1.6 x 2.79
Unit Packaging Type	Polybag
Unit Weight (lbs.)	0.01
Unit Weight (kg)	0.00
ENVIRONMENTAL	
Operating Temperature Range	32° to 113°F (0° to 45°C)
Storage Temperature Range	14° to 158°F (-10° to 70°C)
Operating Humidity Range	10% to 85% RH, Non-Condensing
Storage Humidity Range	5% to 90% RH, Non-Condensing
Power Provided to Connected Device(s)	5V, 0.9A
CONNECTIONS	
Number of Ports	1
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	USB C (FEMALE)
Connector Plating	Nickel
Contact Plating	Gold
FEATURES & SPECIFICATIONS	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
Driver Required	No
STANDARDS & COMPLIANCE	
Product Certifications	EN 55024; EN 55032
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty



1000 Eaton Boulevard
Cleveland, OH 44122
United States



© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.