

## Product Datasheet

### AFBR-57D9AMZ-NS1-C

Avago Broadcom® Compatible 8.5/4.25/2.125Gb/s

#### SFP+ SR Transceiver

Hot Pluggable, Duplex LC, +3.3V, 850nm, VCSEL MMF 300m DDM,

Extended Temperature -10 ~ 85°C

#### FEATURES

- Supports Tri-Rate 8.5/4.25/2.125Gb/s Fibre Channel
- Hot-Pluggable
- Duplex LC connector
- 850nm VCSEL transmitter, PIN photodetector
- MMF links up to 300m @ OM3 and 400m @ OM4
- 2-wire interface for management specifications compliant with SFF 8472 digital diagnostic monitoring interface
- Power Supply: 3.3V
- Power consumption < 1W
- Extended Temperature Range: -10 ~ 85°C
- RoHS compliant

#### APPLICATIONS

- Tri-Rate 8.5/4.25/2.125Gb/s Fibre Channel
- Wireless – CPRI
- Wireless - OBSAI

#### DESCRIPTION

ATGBICS® Compatible AFBR-57D9AMZ-NS1 Transceiver is a very compact 8.5/4.25/2.125Gb/s optical transceiver module for serial optical communication applications at 8.5/4.25/2.125Gb/s. The AFBR-57D9AMZ-NS1-C converts 8.5/4.25/2.125Gb/s serial electrical data stream to 8.5/4.25/2.125Gb/s optical output signal and a 8.5/4.25/2.125Gb/s optical input signal to 8.5/4.25/2.125Gb/s serial electrical data streams. The high speed 8.5/4.25/2.125Gb/s electrical interface is fully compliant with SFI specification.

The high performance 850nm VCSEL transmitter and high sensitivity PIN receiver provide superior performance for Ethernet applications at up to 300m links.

The SFP+ Module is compliant with SFF-8431, SFF-8432 and IEEE 802.3ae 8.5GBASE-SR. Digital diagnostics functions are available via a 2-wire serial interface, as specified in SFF-8472.

The fully SFP compliant form factor provides hot pluggability, easy optical port upgrades and low EMI emission.

## Product Datasheet

### Absolute Maximum Ratings

| Parameter                  | Symbol          | Min. | Typical | Max. | Unit |
|----------------------------|-----------------|------|---------|------|------|
| Storage Temperature        | T <sub>S</sub>  | -40  |         | +85  | °C   |
| Case Operating Temperature | T <sub>A</sub>  | -10  |         | +85  | °C   |
| Maximum Supply Voltage     | V <sub>CC</sub> | -0.5 |         | 4    | V    |
| Relative Humidity          | RH              | 0    |         | 85   | %    |

### Electrical Characteristics (T<sub>OP</sub> = 0 to 70 °C, V<sub>CC</sub> = 3.135 to 3.465 Volts)

| Parameter  | Symbol                 | Min.            | Typical | Max.                 | Unit | Notes |
|--|------------------------|-----------------|---------|----------------------|------|-------|
| Supply Voltage   | V <sub>CC</sub>        | 3.135           |         | 3.465                | V    |       |
| Supply Current   | I <sub>CC</sub>        |                 |         | 250                  | mA   |       |
| Power Consumption  | P                      |                 |         | 1                    | W    |       |
| <b>Transmitter Section:</b>  |                        |                 |         |                      |      |       |
| Input differential impedance                                       | R <sub>in</sub>        |                 | 100     |                      | Ω    | 1     |
| Tx Input Single Ended DC Voltage Tolerance (Ref V <sub>eeT</sub> ) | V                      | -0.3            |         | 4                    | V    |       |
| Differential input voltage swing                                   | V <sub>in,pp</sub>     | 180             |         | 700                  | mV   | 2     |
| Transmit Disable Voltage   | V <sub>D</sub>         | 2               |         | V <sub>CC</sub>      | V    | 3     |
| Transmit Enable Voltage  | V <sub>EN</sub>        | V <sub>ee</sub> |         | V <sub>ee</sub> +0.8 | V    |       |
| <b>Receiver Section:</b>   |                        |                 |         |                      |      |       |
| Single Ended Output Voltage Tolerance                              | V                      | -0.3            |         | 4                    | V    |       |
| Rx Output Diff Voltage   | V <sub>O</sub>         | 300             |         | 850                  | mV   |       |
| Rx Output Rise and Fall Time                                       | Tr/Tf                  | 30              |         |                      | ps   | 4     |
| LOS Fault  | V <sub>LOS fault</sub> | 2               |         | V <sub>CCHOST</sub>  | V    | 5     |
| LOS Normal   | V <sub>LOS norm</sub>  | V <sub>ee</sub> |         | V <sub>ee</sub> +0.8 | V    | 5     |

#### Notes:

1. Connected directly to TX data input pins. AC coupling from pins into laser driver IC.
2. Per SFF-8431 Rev 3.0
3. Into 100 ohms differential termination.
4. 20%~80%
5. LOS is an open collector output. Should be pulled up with 4.7k – 10kΩ on the host board. Normal operation is logic 0; loss of signal is logic 1. Maximum pull-up voltage is 5.5V.

## Product Datasheet

### Optical Parameters (T<sub>OP</sub> = 0 to 70°C, VCC = 3.135 to 3.465 Volts)

| Parameter                      | Symbol            | Min. | Typical | Max.  | Unit  | Notes |
|--------------------------------|-------------------|------|---------|-------|-------|-------|
| <b>Transmitter Section:</b>    |                   |      |         |       |       |       |
| Center Wavelength              | $\lambda_t$       | 840  | 850     | 860   | nm    |       |
| RMS spectral width             | $\lambda_{RMS}$   |      |         | 4     | nm    |       |
| Average Optical Power          | P <sub>avg</sub>  | -7.3 |         | -1    | dBm   | 1     |
| Optical Power OMA              | P <sub>oma</sub>  |      | -1.5    |       | dBm   |       |
| Laser Off Power                | P <sub>off</sub>  |      |         | -30   | dBm   |       |
| Extinction Ratio               | ER                | 3.5  |         |       | dB    |       |
| Transmitter Dispersion Penalty | TDP               |      |         | 3.9   | dB    | 2     |
| Relative Intensity Noise       | R <sub>in</sub>   |      |         | -128  | dB/Hz | 3     |
| Optical Return Loss Tolerance  |                   | 20   |         |       | dB    |       |
| <b>Receiver Section:</b>       |                   |      |         |       |       |       |
| Center Wavelength              | $\lambda_r$       | 840  |         | 860   | nm    |       |
| Receiver Sensitivity (OMA)     | S <sub>en</sub>   |      |         | -11.1 | dBm   | 4     |
| Stressed Sensitivity (OMA)     | S <sub>enST</sub> |      |         | -7.5  | dBm   | 4     |
| Los Assert                     | LOS <sub>A</sub>  | -30  |         | -     | dBm   |       |
| Los Dessert                    | LOS <sub>D</sub>  |      |         | -12   | dBm   |       |
| Los Hysteresis                 | LOS <sub>H</sub>  | 0.5  |         |       | dB    |       |
| Overload                       | Sat               | 0    |         |       | dBm   | 5     |
| Receiver Reflectance           | R <sub>rx</sub>   |      |         | -12   | dB    |       |

#### Notes:

1. Average power figures are informative only, per IEEE802.3ae.
2. TWDP figure requires the host board to be SFF-8431 compliant. TWDP is calculated using the Matlab code provided in clause 68.6.6.2 of IEEE802.3ae.
3. 12dB reflection.
4. Conditions of stressed receiver tests per IEEE802.3ae. CSRS testing requires the host board to be SFF-8431 compliant.
5. Receiver overload specified in OMA and under the worst comprehensive stressed condition.

## Product Datasheet

### Timing Characteristics

| Parameter                                    | Symbol                | Min. | Typical | Max. | Unit |
|--|-----------------------|------|---------|------|------|
| TX_Disable Assert Time                       | t_off                 |      |         | 10   | us   |
| TX_Disable Negate Time                       | t_on                  |      |         | 1    | ms   |
| Time to Initialize Include Reset of TX_FAULT | t_int                 |      |         | 300  | ms   |
| TX_FAULT from Fault to Assertion             | t_fault               |      |         | 100  | us   |
| TX_Disable Time to Start Reset               | t_reset               | 10   |         |      | us   |
| Receiver Loss of Signal Assert Time          | T <sub>A,RX_LOS</sub> |      |         | 100  | us   |
| Receiver Loss of Signal Deassert Time        | T <sub>d,RX_LOS</sub> |      |         | 100  | us   |
| Rate-Select Change Time                      | t_ratesel             |      |         | 10   | us   |
| Serial ID Clock Time                         | t_serial-clock        |      |         | 100  | kHz  |

### Pin Assignment

Diagram of Host Board Connector Block Pin Numbers and Name



## Product Datasheet

### Pin Function Definitions

| PIN No | Name       | Function  | Notes |
|--------|------------|---|-------|
| 1      | VeeT       | Module transmitter ground   | 1     |
| 2      | Tx Fault   | Module transmitter fault  | 2     |
| 3      | Tx Disable | Transmitter Disable; Turns off transmitter laser output   | 3     |
| 4      | SDL        | 2 wire serial interface data input/output (SDA)   |       |
| 5      | SCL        | 2 wire serial interface clock input (SCL)   |       |
| 6      | MOD-ABS    | Module Absent, connect to VeeR or VeeT in the module  | 2     |
| 7      | RS0        | Rate select0, optionally control SFP+ receiver. When high, input data rate >4.5Gb/s; when low, input data rate <=4.5Gb/s    |       |
| 8      | LOS        | Receiver Loss of Signal Indication  | 4     |
| 9      | RS1        | Rate select0, optionally control SFP+ transmitter. When high, input data rate >4.5Gb/s; when low, input data rate <=4.5Gb/s |       |
| 10     | VeeR       | Module receiver ground  | 1     |
| 11     | VeeR       | Module receiver ground  | 1     |
| 12     | RD-        | Receiver inverted data out put  |       |
| 13     | RD+        | Receiver non-inverted data out put  |       |
| 14     | VeeR       | Module receiver ground  | 1     |
| 15     | VccR       | Module receiver 3.3V supply   |       |
| 16     | VccT       | Module transmitter 3.3V supply  |       |
| 17     | VeeT       | Module transmitter ground   | 1     |
| 18     | TD+        | Transmitter inverted data out put   |       |
| 19     | TD-        | Transmitter non-inverted data out put   |       |
| 20     | VeeT       | Module transmitter ground   | 1     |

#### Notes:

1. The module ground pins are isolated from the module case.
2. This pin is an open collector/drain output pin and is pulled up with 4.7K-10Kohms to Host\_Vcc on the host board.
3. This pin is pulled up with 4.7K-10Kohms to VccT in the module.
4. This pin is an open collector/drain output pin and is pulled up with 4.7K-10Kohms to Host\_Vcc on the host board.

## Product Datasheet

### SFP Module EEPROM Information and Management

The SFP modules implement the 2-wire serial communication protocol as defined in the SFP -8472. The serial ID information of the SFP modules and Digital Diagnostic Monitor parameters can be accessed through the I<sup>2</sup>C interface at address A0h and A2h. The memory is mapped in Table 1. Detailed ID information (A0h) is listed in Table 2. And the DDM specification at address A2h. For more details of the memory map and byte definitions, please refer to the SFF-8472, "Digital Diagnostic Monitoring Interface for Optical Transceivers". The DDM parameters have been internally calibrated.

Table 1 - Digital Diagnostic Memory Map (Specific Data Field Descriptions)



## Product Datasheet

Table 2 - EEPROM Serial ID Memory Contents (A0h)

| Data Address                     | Length (Byte) | Name of Length | Description and Contents  |
|----------------------------------|---------------|----------------|---|
| <b>Base ID Fields</b>            |               |                |   |
| 0                                | 1             | Identifier     | Type of Serial transceiver (03h=SFP)  |
| 1                                | 1             | Reserved       | Extended identifier of type serial transceiver (04h)  |
| 2                                | 1             | Connector      | Code of optical connector type (07=LC)  |
| 3-10                             | 8             | Transceiver    | 8.5G Base-SR  |
| 11                               | 1             | Encoding       | 64B/66B   |
| 12                               | 1             | BR, Nominal    | Nominal baud rate, unit of 100Mbps  |
| 13-14                            | 2             | Reserved       | (0000h)   |
| 15                               | 1             | Length(9um)    | Link length supported for 9/125um fibre, units of 100m  |
| 16                               | 1             | Length(50um)   | Link length supported for 50/125um fibre, units of 10m  |
| 17                               | 1             | Length(62.5um) | Link length supported for 62.5/125um fibre, units of 10m  |
| 18                               | 1             | Length(Copper) | Link length supported for copper, units of meters   |
| 19                               | 1             | Reserved       |   |
| 20-35                            | 16            | Vendor Name    | SFP vendor name: ATGBICS  |
| 36                               | 1             | Reserved       |   |
| 37-39                            | 3             | Vendor OUI     | SFP transceiver vendor OUI ID   |
| 40-55                            | 16            | Vendor PN      | Part Number: "AFBR-57D9AMZ-NS1-C" (ASCII)   |
| 56-59                            | 4             | Vendor rev     | Revision level for part number  |
| 60-62                            | 3             | Reserved       |   |
| 63                               | 1             | CCID           | Least significant byte of sum of data in address 0-62   |
| <b>Extended ID Fields</b>        |               |                |   |
| 64-65                            | 2             | Option         | Indicates which optical SFP signals are implemented (001Ah = LOS, TX_FAULT, TX_DISABLE all supported) |
| 66                               | 1             | BR, max        | Upper bit rate margin, units of %   |
| 67                               | 1             | BR, min        | Lower bit rate margin, units of %   |
| 68-83                            | 16            | Vendor SN      | Serial number (ASCII)   |
| 84-91                            | 8             | Date code      | OEM's Manufacturing date code   |
| 92-94                            | 3             | Reserved       |   |
| 95                               | 1             | CCEX           | Check code for the extended ID Fields (addresses 64 to 94)  |
| <b>Vendor Specific ID Fields</b> |               |                |   |

## Product Datasheet

|                |     |          |                              |
|----------------|-----|----------|------------------------------|
| <b>96-127</b>  | 32  | Readable | OEM specific date, read only |
| <b>128-255</b> | 128 | Reserved | Reserved for SFF-8079        |

### Digital Diagnostic Monitor Characteristics

| Data Address   | Parameter                        | Accuracy | Unit |
|----------------|----------------------------------|----------|------|
| <b>96-97</b>   | Transceiver Internal Temperature | ±3.0     | °C   |
| <b>98-99</b>   | VCC3 Internal Supply Voltage     | ±3.0     | %    |
| <b>100-101</b> | Laser Bias Current               | ±10      | %    |
| <b>102-103</b> | Tx Output Power                  | ±3.0     | dBm  |
| <b>104-105</b> | Rx Input Power                   | ±3.0     | dBm  |

### Regulatory Compliance

The AFBR-57D9AMZ-NS1-C complies with international Electromagnetic Compatibility (EMC) and international safety requirements and standards (see details in Table following).

|   |  |  |
|---|--|--|
| Electrostatic Discharge (ESD) to the Electrical Pins      | MIL-STD-883E Method 3015.7   | Class 1(>1000 V)                       |
| Electrostatic Discharge (ESD) to the Duplex LC Receptacle | IEC 61000-4-2 GR-1089-CORE   | Compatible with standards              |
| Electromagnetic Interference (EMI)                        | FCC Part 15 Class B<br>EN55022 Class B (CISPR 22B)<br>VCCI Class B | Compatible with standards              |
| Laser Eye Safety  | FDA 21CFR 1040.10 and 1040.11<br>EN60950, EN (IEC) 60825-1,2       | Compatible with Class 1 laser product. |



## Product Datasheet

### Recommended Circuit



**Recommended Host Board Power Supply Circuit**



**Recommended High-speed Interface Circuit**

## Product Datasheet

### Mechanical Dimensions

