



SPECIFICATIONS								
WIRING	INPUT		OUTPUT			SHAFT ROTATION FOR VOLTAGE INCREASE	TERMINAL CONNECTIONS FOR INCREASING VOLTAGE AS VIEWED FROM TOP	
	VOLTS	HERTZ	VOLTS	CONSTANT CURRENT LOAD			INPUT	OUTPUT
THREE PHASE WYE	240	60	0-280	MAX. AMPS	MAX. KVA	CW	2-2-2	B-B-B
				100	48.5			
UNLESS OTHERWISE SPECIFIED, TOLERANCE IS # DECIMALS .XX, .XXX, .XXX, .005			Holes .12, .03			ANGLES 1°		
DRAFT 1-1/2°			UNITS IN [mm]			TITLE: SPEC. CONTROL DRAWING VARIABLE CURRENT TRANSFORMER TYPE: 5011E-6Y		
MATERIAL:			ALL DIMENSIONS APPLY AFTER PLATING			DRAWN BY: TIM RAU DATE: 8/7/97		
FIRST USED ON			DO NOT SCALE DWG.			CUSTOMER APPROVAL		
CHECKER			DATE			WEIGHT APPROX.		
ENGINEER			DATE			SCALE .2=1		
SHEET 1 OF 1			DWG. NO. 031-6782			D		

