



**ANATECH ELECTRONICS INC**  
RF & Microwave Filters & Products

**& ) ) 'A < n' # & % \$ ' A < n' 7 cbbYWcf]nYX  
7 YfUa ]W8 i d`YI Yf**

**DUfhBi a VYf. '5 A & ) ) ! & % \$ 8 % / + , ! 7**



**9`YWf]WU`GdYVZ]WU]cbg**

FI `6 UbX. 2355 MHz  
HI `6 UbX. `2130 MHz  
6 UbXk ]XH . 10 MHz  
`bgYfh]cb` @gg. 2.0 dB Max  
F]dd`Y]b`6 K. `0.5 dB Max  
FYi fb` @gg. 15 dB Min  
FI `5 H]Ybi U]cb. >40 dB @ 2125-2135 MHz  
HI `5 H]Ybi U]cb. >40 dB @ 2350-2360 MHz  
`b#Ci h`a dYXUbWY. 50 Ω  
`bdi hDck Yf. 3 Watts Max

**A YW Ub]WU`**

7 cbbYWcf`HndY. SMA (F)  
8]a Ybg]cbg. `65 x 40 x 20 mm

**9bj ]fcba YbHJ**

CdYfU]b[ `HYa dYfUi fY. -25 to +85° C  
G]cfU] Y`HYa dYfUi fY. -40 to +95° C  
G]cW. 20 G. 11 ms  
J]VfU]cb. 20 G. 5 to 200 MHz

**H] ]g`dfcXi W] ]g`Fc < G`W`a d`]UbH`**

**Ci h]bY`8 fUk ]b[ .**

