


NO.	MASSE / DIMENSION
A	2 1/4-16UN-2A
B1	31.8
B2	26.8
C	22.2
D	4
E	76
F	63.1
G	57.5


NO.	BESCHREIBUNG / DESCRIPTION
2	ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET
3	DICHTKÖRPER / GROMMET
4	ENDRING / ENDRING
6	KONTAKTBUCHSE / CONTACT SOCKET
8	DOSENGEHÄUSE / SHELL
12	ENDGEHÄUSE / ENDBELL



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate coating over cadmium plating
Insulator Material:	Neoprene
Contact Material:	Copper alloy
Contact Plating:	Hard silver

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  
 drawing for CUSTOMER

 <b>ITT</b> <i>Engineered for life</i> <small>ITT CANNON GmbH  D - 71384 Weinstadt/Germany</small>	description <b>CA3101E36A34S</b> Cable connecting plug Endbell with clamp and bushing Solder Cup / Socket / Layout: 36A34
	page 1/1 revision 929 11. Jun 19

© All rights reserved. Reproduction or issue to third in any form  
 whoever is only permitted with written authorization of ITT Cannon