

VIEW ON MATING SIDE

∞ B
 ◀ A

A = 32 STANDARD CONTACTS L=3

B = 32 STANDARD CONTACTS L=3

S = 64 TOTAL NUMBER OF CONTACTS

Marking	Standard
Performance level	G2/0 = Contact area level2 / Termination tin
Flux proof	no
Fixing clip	yes
Dimensions	SDA-85001-0001 sht.1
Technical Data	PS-85003-0001

B	G2/0
A	G2/0
Contact symbol	Perform. level
Contact position number	

C	see ECN No. 2204	96/07/18 Cd	REVISIONS	FOR PREVIOUS REVISIONS SEE MRI LIST
	LTR			

UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 2°	DRWG BY	SIGN	CAD/CAM PROJECT NAME s8500101 s91	REVISE ONLY ON CAD SYSTEM	SH. REV.
	3 PLACE ± .	CHK'D BY			
2 PLACE ± .	KN	APP'D BY	TITLE 64 pos. Male connector acc. DIN 41612 style B contacts arrangement	SHEET NO. DATE 1 OF 1 95/05/23	SIZE A
1 PLACE ± .	SCALE	MOLEX® MOLEX EUROPE			
DESIGN DIMENSION <input type="checkbox"/> MM <input type="checkbox"/> IN.	EQUIVALENT DIMENSION <input type="checkbox"/> MM <input type="checkbox"/> IN.	PART NO. DWG NO.	85001-0191 SDA-85001-0191		
IF TWO DIMENSIONS ARE SHOWN, THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY					