



**Inch table**

Dimensions in: inches - millimeters

Length <b>L</b>	<b>d</b> Standard material (PP)	<b>a</b>	<b>b</b>	<b>h</b>	<b>t</b> min.
3.39 ±0.02 86 ±0.5	1/4 x 20	0.55 14	0.91 23	1.73 44	0.47 12
4.61 ±0.02 117 ±0.5	5/16 x 18	0.59 15	0.98 25	1.93 49	0.51 13
5.20 ±0.02 132 ±0.5	5/16 x 18	0.63 16	1.02 26	2.13 54	0.51 13
5.91 ±0.04 150 ±1	5/16 x 18	0.63 16	1.06 27	2.20 56	0.51 13
7.05 ±0.04 179 ±1	5/16 x 18	0.63 16	1.06 27	2.24 57	0.51 13

**Metric table**

Dimensions in: millimeters - inches

Length <b>L</b>	<b>d</b>						<b>a</b>	<b>b</b>	<b>h</b>	<b>t</b> min.				
	Standard material (PP)				HT material (PA)					M4	M5	M6	M8	M10
86 ±0.5 3.39 ±0.02	M 5	M 6	-	-	M 6	-	14	23	44	-	10	12	-	-
94 ±0.5 3.70 ±0.02	M 5	M 6	-	-	-	-	14	24	48	-	10	12	-	-
117 ±0.5 4.61 ±0.02	M 4	M 5	M 6	M 8	M 6	M 8	15	25	49	10	10	12	13	-
120 ±0.5 4.72 ±0.02	M 5	M 6	M 8	-	-	-	15	25	49	-	10	12	13	-
132 ±0.5 5.20 ±0.02	M 5	M 6	M 8	-	-	-	16	26	54	-	10	12	13	-
150 ±1 5.91 ±0.04	M 6	M 8	M 10	-	-	-	16	27	56	-	-	12	13	17
160 ±1 6.30 ±0.04	M 6	M 8	M 10	-	-	-	16	27	55	-	-	12	13	17
179 ±1 7.05 ±0.04	M 8	M 10	-	-	M 8	-	16	27	57	-	-	-	13	17
235 ±1 9.25 ±0.04	M 8	M 10	-	-	-	-	18.5	29	61	-	-	-	13	17
300 ±1 11.81 ±0.04	M 10	-	-	-	-	-	22	32	64	-	-	-	-	17

**Specification**

- Technopolymer plastic (Polypropylene PP) —
  - Shock-resistant
  - Temperature resistant up to 212 °F (100 °C)
  - Black, matte finish

- Technopolymer plastic (Polyamide PA) **HT**
  - Glass fiber reinforced
  - Temperature resistant up to 390 °F (200 °C)
  - Black-gray, matte finish

- Tapped inserts  
Brass

• Strength Values

• Plastic Characteristics

• RoHS compliant

**Information**

EN 725 cabinet “U” handles are well known for their smooth ergonomically shaped elliptical design. High impact strength. Resistant to solvents, oils, grease and other chemical agents.

**On request**

- Various metric and inch size fasteners and kit packaging

How to order (Inch, up to 212 °F (100 °C))	1	Length <b>L</b>
	2	Thread <b>d</b>
<b>EN 725-132-5/16X18</b>		

How to order (Metric, up to 390 °F (200 °C))	1	Length <b>L</b>
	2	Thread <b>d</b>
	3	Material
<b>EN 725-86-M6-HT</b>		