



NOTES:

MECHANICAL REQUIREMENTS:

Durability: 20'000 cycles
 Theoretical Working stroke S= .065 in
 Working stroke between H1 and H2: S= .055 mm
 Spring forces (F):
 Finit= 0.50 N at Hinit= .317 in
 F1= 0.57 N at H1= .309 in
 Fnom= 0.82±0.15 N at Hnom= .281 in
 F2= 1.0 N at H2= .253 in
 Recommended working range: between H1 and H2

Forces are measured in mean value of compression / decompression

ELECTRICAL REQUIREMENTS:

Contact resistance:
 R= 30 mOhms max in static mode at Hnom
 Current per individual contact in free air at ambient temperature:
 ICont= 5 A at Hnom with temperature raise max 30°C

ENVIRONMENTAL REQUIREMENTS:

Operating temperature: -25 °C / +125 °C
 Storage temperature: -40 °C / +125 °C
 Relative humidity: 5% / 95%

MATERIALS / PLATINGS:

Barrel: Brass - 5 µin Au over Ni
 Rod: Brass - 20 µin Au over Ni
 Piston: Brass - 20 µin Au over Ni
 Spring: Stainless steel
 Clip: BeCu - 20 µin Au over Ni

5	Clip	1	See notes
4	Spring	1	See notes
3	Rod	1	See notes
2	Piston	1	See notes
1	Barrel	1	See notes
Pos.	Désignation	Qté	Matière - Protection

90645-AS
20-187



Remplace:

Remplacé par:

25:1

Dessiné

10.11.2020

C.Bidault

Contrôlé

N° dessin

Révision



preci-dip
swiss world connects

0907-3-CLIP

P1