


Specification Sheet

Part Number: 596-00859

Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure.

Aggressive adhesive ensures strong bond, even on powder coated surfaces.

Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability.



Optional Paint Shields provide additional protection for pre-printed and variable data placards.

Metal Solar Placard, Engravable, PHOTOVOLTAIC AC DISCONNECT, 3.75" x 1.0", AA, Black, 5/pkg

Article Number 596-00859

Type PVACDISM5ENG

Color Black (BK)

Quantity Per pack

Product Description Variable data placards are used to mark areas specific to the individual installation, like voltage data. Made of the same durable material as pre-printed metal solar placards, engravable placards are designed to meet industry codes. Engravable placards have a black area that can be engraved using standard engraving equipment.

Short Description	Metal Solar Placard, Engravable, PHOTOVOLTAIC AC DISCONNECT, 3.75" x 1.0", AA, Black, 5/pkg
Global Part Name	PVACDISM5ENG-AA-BK
Technical Description	3.75" X 1" Black text on aluminum background that reads as: "PHOTOVOLTAIC AC DISCONNECT. MAXIMUM AC OPERATING CURRENT. NOMINAL OPERATING AC VOLTAGE." 5 per pack. Nameplate can be used with standard engraving equipment to add variable data.
Local Order Number 2	Cross Reference = Paint Shield: 596-00796
Length L (Imperial)	1.0
Length L (Metric)	25.4
Width W (Imperial)	3.75
Width W (Metric)	95.25
Height H (Imperial)	1.0
Height H (Metric)	25.40
Material	Anodized Aluminum (AA)
Material Shortcut	AA
Adhesive	Ultra High Bond Permanent Acrylic Adhesive

Halogen Free	No
Adhesive Operating Temperature	from +50°F (from +10°C)
Operating Temperature	-40°F to +203°F (-40°C to +95°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	NEC2014
Warranty (US)	Yes
Package Quantity (Imperial)	5
Package Quantity (Metric)	5
Customs Number	7616995195
Labels per Column	1
Labels per Row	1