



**MATERIALS**  
 HOUSING: LCP 30% G.F. V0 BLACK  
 TERMINALS: PhPz CuSn 8 (C521) 0.20mm THICK  
 PLATING  
 CONTACT AREA : 0.764m Au MIN OVER 1.274m Ni  
 SOLDER AREAS: 3.84m Sn OVER 1.274m Ni MIN

- NOTES**
- CONTACT NORMAL FORCE: 0.8N MIN AT FULL DEFLECTION
  - COMPONENT SMT AND PICK & PLACE COMPATIBLE
  - DURABILITY: 10K CYCLES MIN
  - PACKAGING: IN TRAYS (SEE DWG nbr. PK-94324-001)  
 S.P.Q.= 400 PCS
  - OTHER PRODUCT CHARACTERISTICS ACCORDING TO PS-94324-001

STD. DESCR. : 7 CKT COMPRESSION CONNECTOR

ENTER DESCRIPTION EC NO: Z2008-0039 DRWN:LSANTISS 2008/06/03 CHKD:LSANTISS 2008/06/03 APPR:GZUIN 2008/06/04	QUALITY SYMBOLS ▽=0 ∇=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	FIRST ANGLE PROJECTION		
		mm	INCH	MM/IN		5:1	METRIC			
		4 PLACES	± ---	± ---	DRAWN BY	DATE	TITLE			
		3 PLACES	± ---	± ---	GZUIN	2005/03/01	7 CKT COMPRESSION CONNECTOR			
			2 PLACES	± 0.13	± ---	CHECKED BY	DATE			
			1 PLACE	± 0.25	± ---	RSANDANO	2005/03/01			
			ANGULAR ± 2 °		APPROVED BY		DATE			
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		FBISELLO		2005/03/01			
					MATERIAL NO.		DOCUMENT NO.		SHEET NO.	
					94324-0007		SD-94324-001		1 OF 1	
					THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					