			0	σ	A	
			LAYOUT SHOWN AS	EXAMPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III         -Shell Material       : Aluminium         -Shell Plating       : Nickel         -Insulator       : Thermoplastic         -Contacts       : Copper Alloy	DimNominalØS29.4 MaxZ31 MaxVV THREADM18x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum			Coun			
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D513			
-Temperature Range : -65°C to +200°C		A 17-10-20	16 First Release			
-Salt Spray : 48 hours		ISS DATE Designed By:	Latest modification - by Date:	СИЅТОМ	MOD N°	
		TITLE	Alumi	Aluminium Plug 8D series		
BASIC SERIES: 8D 5 - 13 F SHELL TYPE : Plug with RFI Shielding	03 S A L Delivered W/O Cor	SCALE NA	General linear Tolerances:		5 / PROJECT <b>859</b>	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIENTATIC CONTACT TYPE : SOCKET(500 Ma		A SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or			
PLATING : F = Nickel	CONTACT LAYOUT :	A3		J DRG N° 03SAL-C	SHEET	

	т	۵	т	п	D	C	
		Contact Layout					
4							
	Ctc A B C	3#16 13-03 X Y 2.39 1.47 0 -2.79 -2.39 1.47					
ω		-2.33 1.47					
	L						
						SOURIAU shall not be due to a use of the the Specifications issue (professional re	e Products v d by either
N							Coun
						PN: 8	8D513
					A 17-10-2016	First Release	
_					ISS DATE Designed By:	Latest modification - by Date:	
					TITLE		Alumi
_ <b>_</b>					SCALE		eneral linear olerances: ±
					SOURIAU	WWW.SO	JRIAU.
					FORMAT	SC	URIA

G

Н

F

Е

A3

D

С

