



## Features

- Under Stencil Rolls for DEK Printers
- Prevents smearing, bridging, solder balls, and other problems associated with the stencil printing of solder paste
- Manufactured from a blend of polyester and cellulose fibers
- More paper per roll resulting in less down time, less changeover time, and less inventory required
- Exceptionally low lint levels
- Solvent resistant material results in increased absorption per square inch



## DEK Paper Specifications

Test	Orientation	Units	Value	Method
Composition			54% Wood Pulp 46% Polyester White	
Basis Weight		oz/yd <sup>2</sup> g/m <sup>2</sup>	1.5 50.8	ASTM D3776
Thickness		mils mm	12 .30	ASTM D1777
Grab Tensile Strength	Machine Direction	lb N	28 125	ASTM D5034
	Cross Direction	lb N	16 71	

## DEK Stencil Roll Part Numbers

Part Number	Core Type	Core Length	Paper Width	Core ID	Paper Length	Core Notch Width	Core Notch Depth	# of Notches on Core End 1	# of Notches on Core End 2
EB41D2112	Plastic	20.82"	12"	.75"	39'	0.10"	0.125"	4	0
EB41D2116	Plastic	20.82"	15.75"	.75"	39'	0.10"	0.125"	4	0
EB41D2120	Plastic	20.82"	20.25"	.75"	39'	0.10"	0.125"	4	0
EB41D2121	Plastic	21.22"	20.75"	.75"	39'	0.10"	0.125"	4	0
EB41D2424	Plastic	24.37"	24.12"	.75"	39'	0.10"	0.125"	4	0

### Dimensional Tolerances:

Core Length: ± 1/16"  
 Paper Width: ± 1/8"  
 Core ID: + 1/8"  
 Paper Length: ± 5%  
 Notch Width: ± 0.02"  
 Notch Depth: ± 0.03"

Specifications and procedures subject to change without notice.

*EasyBraid expressly warrants that for a period of one (1) year from the date of purchase, EasyBraid products will be free of defects in material (parts) and workmanship (labor). Within the warranty period, a unit/product will be tested, repaired or replaced at EasyBraid's option, free of charge.*

## DEK STENCIL ROLLS

11520 K-TEL DRIVE, MINNETONKA, MN 55343  
 (909) 627-2453  
 WEBSITE: [EASYBRAIDCO.COM](http://EASYBRAIDCO.COM)

**DRAWING  
NUMBER**  
DEK

**DATE:**  
September  
2022

# EasyBraid