

## Specification Sheet

Part Number: 156-01342



Bundle can rotate to any orientation, allowing routing in any direction regardless of mounting point.

Clip is reusable, making relocation or adjustments simple.

All-in-one bundling and mounting solution reduces costs.

1-Pc Cable Ties with Pipe Clip, 19-24.5mm, PA66HIRHS, Black, 500/pkg

<b>Article Number</b>	156-01342
<b>Type</b>	T50SMVCOC19-24.5
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton's 1-Piece Cable Tie with Pipe Clip secures cables to tubular frame rails. The cable tie bundles wires, cables or tubes, and the C-clip snaps onto the tubular frame rail. The clip can be removed from the mounting surface and reinstalled without additional fasteners.
<b>Short Description</b>	1-Pc Cable Ties with Pipe Clip, 19-24.5mm, PA66HIRHS, Black, 500/pkg

**Global Part Name** T50SMVCOC19-24.5-PA66HS/PA66HIRHS-BK

**Minimum Tensile Strength (Imperial)** 50.0

**Minimum Tensile Strength (Metric)** 222

**Length L (Imperial)** 8.3

**Length L (Metric)** 210.0

**Fixation Method** Omega Clips

**Identification Plate Position** none

**Width W (Imperial)** 0.19

**Width W (Metric)** 4.7

**Bundle Diameter Min (Imperial)** 0.08

**Bundle Diameter Min (Metric)** 2.0

**Bundle Diameter Max (Imperial)** 2.0

**Bundle Diameter Max (Metric)** 50.0

**Thickness T (Metric)** 1.35

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS PA66HS
<b>Material Cable Tie</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988