



NOTES:

- 1- APPLICABLE WITH FEMALE CONNECTOR 64328100X OR 64329100X
- 2- MATERIAL : >PA6.6<
- 3- APPLICATION SPECIFICATION : AS-64327-001
- 4- WEIGHT : 9.133 g

SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION												
	DIMENSION UNITS	SCALE	CURRENT REV DESC: MIGRATION TO NX/ECTR							 CMX 104-120CKT - WIRE CAP			
∇ = 0	mm	2:1	EC NO: 628384									DOCUMENT NUMBER	DOC TYPE
∇ = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DRWN: GMANIVANNAN 2019/04/05							SD-64330-002	PSD	001	A1
∇ = 0	ANGULAR TOL ± °		CHK'D: TBADAROUX 2019/12/18										
∇ = 0	4 PLACES ±		APPR: CBOUCHAN 2019/12/20							PRODUCT CUSTOMER DRAWING			
∇ = 0	3 PLACES ±		INITIAL REVISION:							MATERIAL NUMBER			
∇ = 0	2 PLACES ±		DRWN: VJOUAS 2015/11/18							CUSTOMER			
∇ = 0	1 PLACE ±		APPR: OPLESSIS 2016/01/25							GENERAL MARKET			
∇ = 0	0 PLACES ±		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		FIRST ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER		SHEET NUMBER		
∇ = 0						A2-SIZE	64330	643300002	GENERAL MARKET		1 OF 1		