

Product data sheet

Characteristics

NSYMDVR10

Vertical aluminium rail, height 1000mm.

Packaging unit: 10 pieces.



Main

Range	Spacial
Accessory / separate part category	Mounting accessory
Product or Component Type	Rail
Anwendung	Multi-purpose
Nennmaße des Gehäuses	-
Mounting Support	Fixing nut
Range compatibility	Spacial S3D Spacial CRN Spacial S3X Thalassa PLM
Device composition	1 upright
Quantity per Set	Set of 10
Material	aluminium

Complementary

Fixing mode	Screwed M8 - on backstuds of enclosure
Height	Nominal 39.37 in (1000 mm) Real 36.98 in (939.3 mm)
Width	0.98 in (25 mm)
Depth	0.59 in (15 mm)
Thickness	0.10 in (2.5 mm)
Net Weight	0.64 lb(US) (0.29 kg)

Ordering and shipping details

Category	80035-ENCLOSURE SYSTEMS FLOOR MOUNT
Discount Schedule	ES1
GTIN	3606480182884
Nbr. of units in pkg.	1
Package weight(Lbs)	10.23 oz (290.0 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.38 in (3.5 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	37.20 in (94.5 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------