




ETHERNET-ENABLED
SINGLE-BOARD
COMPUTER



DIGI RABBIT SBC BL2600 SERIES

Best suited for industrial control applications and is a low-cost PLC alternative

The BL2600 series represents a class of advanced single-board computers that incorporates the powerful Rabbit 3000 microprocessor, Flash memory and RS-232/RS-485 serial ports. Additional module variants enable data logging of up to 1 GB in data storage. Functionality of the BL2600 series can be expanded using optional RabbitNet™ expansion cards.


The BL2600 series can be connected via two mechanisms: Dual-entry IDC through-hole sockets, which allow header mounting on either side of the board, and polarized locking industry-standard friction-lock connectors that enable rapid assembly with a wire harnesses. These connectors provide

dependable cable harness connectivity to I/O. RabbitNet expansion boards are available (including A/D, D/A, digital I/O and keypad/display interface cards) to interface via the two multiplexed SPI RS-422 ports.


BENEFITS

- Rabbit® 3000 microprocessor at 44 MHz
- 10/100Base-T Ethernet, RJ-45
- 512K Flash/512K SRAM
- 36 digital I/O (configurations include protected digital inputs, sinking/sourcing outputs, high current outputs)
- 12 analog channels: eight 11-bit A/D, four 12-bit D/A buffered outputs
- RabbitNet expansion ready
- Multiple “core module” options allow flexibility in functionality

APPLICATION EXAMPLE



RELATED PRODUCTS



SPECIFICATIONS	BL2600	BL2610
-----------------------	---------------	---------------

FEATURE		
MICROPROCESSOR	Rabbit® 3000 at 44 MHz	Rabbit® 3000 at 29 MHz
ETHERNET PORT	10/100Base-T, 3 LEDs	None
FLASH MEMORY	512K (standard)	512K (standard)
PROGRAM EXECUTION SRAM	512K	None
DATA SRAM	256K	512K
BACKUP BATTERY	Panasonic CR2477 or equivalent 3V lithium coin type, 950 mA-h standard, socket-mounted	
CONFIGURABLE I/O	16 individually software-configurable I/O channels may be configured as digital inputs ± 36 VDC, switching threshold 1.5V typical, or as sinking digital outputs up to 40V, 200 mA each	
DIGITAL INPUTS	8 inputs hardware-configurable pull-up or pull-down, ± 36 VDC, switching threshold 1.4V typical	
HIGH-CURRENT DIGITAL OUTPUTS	4 outputs individually software-configurable as sinking or sourcing, +40VDC, 2A max. per channel	
ANALOG INPUTS	Eight 11-bit res. channels, software-selectable ranges unipolar: 1, 2, 2.5, 5, 10, 20VDC; bipolar ± 1 , ± 2 , ± 5 , ± 10 VDC: 4 channels can be hardware-configured for 4–20 mA; 1 M Ω input impedance, up to 4,100 samples/s	
ANALOG OUTPUTS	Four 12-bit res. channels, buffered, 0–10VDC, ± 10 VDC, and 4–20 mA, update rate 12 kHz	
SERIAL PORTS	5 serial ports: <ul style="list-style-type: none"> 1 RS-485 or 1 RS-232 2 RS-232 or 1 RS-232 (with CTS/RTS) 1 clocked serial port multiplexed to 2 RS-422 SPI master ports 1 serial port dedicated for programming/debug 	
SERIAL RATE	Max. asynchronous rate = CLK/8, Max. synchronous rate = CLK/2	
CONNECTORS	<ul style="list-style-type: none"> RJ-45 connectors: 1 Ethernet and 2 RabbitNet™ Friction-lock connectors: 2 polarized 9-position terminals with 0.1" pitch; three 4-position power terminals with 0.156" pitch; two 20-position terminals with 0.1" pitch (2 \times 20 IDC option); one 13-position terminal with 0.1" pitch (2 \times 13 IDC option); one 10-position terminal with 0.1" pitch (2 \times 7 IDC option) Programming port: 2 \times 5 IDC, 1.27 mm pitch (BL2600), 2 \times 5 IDC, 2 mm pitch (BL2610) 	
REAL-TIME CLOCK	Yes	
TIMERS	One 10-bit timer with 2 match registers	
POWER	Yes	
WATCHDOG/SUPERVISOR	9–36 VDC, 12W max.	
OPERATING TEMPERATURE	–40° C to +70° C (–40° C to +85° C without battery)	
HUMIDITY	5 to 95%, non-condensing	
BOARD SIZE	4.85" \times 4.96" \times 1.00" (123 mm \times 126 mm \times 25 mm)	
PRODUCT WARRANTY	1 year	

PART NUMBERS	DESCRIPTION
---------------------	--------------------

20-101-0889	BL2600. 10/100Base-T Ethernet
20-101-0891	BL2610. No Ethernet
20-101-1095	BL2600 w/ 10/100Base-T, 512k Flash, 512k SRAM, 16MB NAND Flash, xD removable memory slot

DIGI SERVICE AND SUPPORT / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit www.digi.com/support.

© 1996-2019 Digi International Inc. All rights reserved.
All trademarks are the property of their respective owners.

91001596
C3/319

DIGI INTERNATIONAL WORLDWIDE HQ
877-912-3444 / 952-912-3444 / www.digi.com

DIGI INTERNATIONAL GERMANY
+49-89-540-428-0

DIGI INTERNATIONAL JAPAN
+81-3-5428-0261 / www.digi-intl.co.jp

DIGI INTERNATIONAL SINGAPORE
+65-6213-5380

DIGI INTERNATIONAL CHINA
+86-21-50492199 / www.digi.com.cn

