Mallory Sonalert Products, Inc.				Part #: JT028-RYG-CD		
Sales Outline Drawing				Revision:	С	
Specifications:						
Stack Number:	1	2	3			
LED Color:	RED	YELLOW	GREEN			
Connection Wires:	Red and Brown	Yellow and Brown	Green and Brown			
LED Current Draw:	<50 mA	<60 mA	<40 mA			
Rated Voltage:	24 VAC/DC					
Operating Voltage:		20-28 VAC/DC				
Total Max Current:	<150mA					
Operating Temperature:	-25° ~ +60°C					
Lens Color:	Opaque White					
Material:	ABS FR15U					
Mounting Method:	Direct Mount using 1/2" NPT Stainless Steel Pipe and Nut					
Weight Typical (g):	250					
NEMA 12:		Approved				
Options:	Please contact factory.					
Dimensions: Inches (r	nm)	cUL Recogn			ROHS Compliant	
		PATENT NUMBER	10309594			
	YELLOW 0 [152.3]		48″ wire			
2.7 [68.3]— TOP VIEW	2.4 [61.8]		Ø0.88 [Ø22. KNOCK OU' FOR WIRE:	T ~		
LED OPERATION: CONNEC	CT STACK COLOR WIRE	TO POWER AND BR	OWN WIRE TO POW			
LED OF LIGHTION. DOININE	ST STACK GOLOK WIN	L TO TOVVEN AND DIV	CTTIN VVIIVE TO LOVV	LIV.		