



Circuit breaker size S00 for motor protection, CLASS 10 A-release 2.8...4 A N release 52 A Screw terminal Standard switching capacity with transverse auxiliary switch 1 NO+1 NC

|  |                      |
|--|----------------------|
| <b>product brand name</b>  | SIRIUS               |
| <b>product designation</b>   | Circuit breaker      |
| <b>design of the product</b>   | For motor protection |
| <b>product type designation</b>  | 3RV1                 |
| <b>General technical data</b>  |                      |
| <b>size of the circuit-breaker</b>   | S00                  |
| <b>size of contactor can be combined company-specific</b>                                  | S00                  |
| product extension auxiliary switch   | Yes                  |
| <b>power loss [W] for rated value of the current</b>                                       |                      |
| • at AC in hot operating state   | 7.25 W               |
| • at AC in hot operating state per pole  | 2.4 W                |
| insulation voltage with degree of pollution 3 at AC rated value                            | 690 V                |
| <b>surge voltage resistance rated value</b>  | 6 kV                 |
| <b>mechanical service life (switching cycles)</b>  |                      |
| • of the main contacts typical   | 100 000              |
| • of auxiliary contacts typical  | 100 000              |
| electrical endurance (switching cycles) typical  | 100 000              |
| <b>reference code according to IEC 81346-2</b>   | Q                    |
| <b>Substance Prohibition (Date)</b>  | 01/01/2013           |
| <b>Ambient conditions</b>  |                      |
| installation altitude at height above sea level maximum                                    | 2 000 m              |
| <b>ambient temperature</b>   |                      |
| • during operation   | -20 ... +60 °C       |
| • during storage   | -50 ... +80 °C       |
| • during transport   | -50 ... +80 °C       |
| relative humidity during operation   | 10 ... 95 %          |
| <b>Main circuit</b>  |                      |
| <b>number of poles for main current circuit</b>  | 3                    |
| <b>adjustable current response value current of the current-dependent overload release</b> | 2.8 ... 4 A          |
| <b>operating voltage</b>   |                      |
| • rated value  | 20 ... 690 V         |
| • at AC-3 rated value maximum  | 690 V                |
| • at AC-3e rated value maximum   | 690 V                |
| <b>operating frequency rated value</b>   | 50 ... 60 Hz         |
| <b>operational current rated value</b>   | 4 A                  |
| <b>operational current</b>   |                      |
| • at AC-3 at 400 V rated value   | 4 A                  |
| • at AC-3e at 400 V rated value  | 4 A                  |

|   |  |
|---|--|
| <b>operating power</b>  |  |
| <ul style="list-style-type: none"> <li>● at AC-3 <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> <li>● at AC-3e <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> </ul> | 0.8 kW<br>1.5 kW<br>2.2 kW<br>3 kW<br><br>0.8 kW<br>1.5 kW<br>2.2 kW<br>3 kW |
| <b>operating frequency</b>  |  |
| <ul style="list-style-type: none"> <li>● at AC-3 maximum</li> <li>● at AC-3e maximum</li> </ul>   | 15 1/h<br>15 1/h   |
| <b>Auxiliary circuit</b>  |  |
| <b>design of the auxiliary switch</b>   | transverse   |
| <b>number of NC contacts for auxiliary contacts</b>   | 1  |
| <ul style="list-style-type: none"> <li>● note</li> </ul>  | 1  |
| <b>number of NO contacts for auxiliary contacts</b>   | 1  |
| <ul style="list-style-type: none"> <li>● note</li> </ul>  | 1  |
| number of CO contacts for auxiliary contacts  | 0  |
| <b>operational current of auxiliary contacts at AC-15</b>   |  |
| <ul style="list-style-type: none"> <li>● at 24 V</li> <li>● at 110 V</li> <li>● at 120 V</li> <li>● at 125 V</li> <li>● at 230 V</li> </ul>   | 2 A<br>2 A<br>2 A<br>2 A<br>0.5 A  |
| <b>operational current of auxiliary contacts at DC-13</b>   |  |
| <ul style="list-style-type: none"> <li>● at 24 V</li> <li>● at 60 V</li> </ul>  | 1 A<br>0.15 A  |
| <b>Protective and monitoring functions</b>  |  |
| <b>product function</b>   |  |
| <ul style="list-style-type: none"> <li>● ground fault detection</li> <li>● phase failure detection</li> </ul>   | No<br>Yes  |
| <b>trip class</b>   | CLASS 10   |
| <b>design of the overload release</b>   | thermal  |
| <b>breaking capacity maximum short-circuit current (I<sub>cu</sub>)</b>   |  |
| <ul style="list-style-type: none"> <li>● at AC at 240 V rated value</li> <li>● at AC at 400 V rated value</li> <li>● at AC at 500 V rated value</li> <li>● at AC at 690 V rated value</li> </ul>  | 100 kA<br>100 kA<br>3 kA<br>2 kA   |
| <b>breaking capacity operating short-circuit current (I<sub>cs</sub>) at AC</b>   |  |
| <ul style="list-style-type: none"> <li>● at 240 V rated value</li> <li>● at 400 V rated value</li> <li>● at 500 V rated value</li> <li>● at 690 V rated value</li> </ul>  | 100 kA<br>100 kA<br>3 kA<br>2 kA   |
| response value current of instantaneous short-circuit trip unit   | 52 A   |
| <b>UL/CSA ratings</b>   |  |
| <b>full-load current (FLA) for 3-phase AC motor</b>   |  |
| <ul style="list-style-type: none"> <li>● at 480 V rated value</li> <li>● at 600 V rated value</li> </ul>  | 4 A<br>4 A   |
| <b>yielded mechanical performance [hp]</b>  |  |
| <ul style="list-style-type: none"> <li>● for single-phase AC motor <ul style="list-style-type: none"> <li>— at 110/120 V rated value</li> <li>— at 230 V rated value</li> </ul> </li> <li>● for 3-phase AC motor <ul style="list-style-type: none"> <li>— at 200/208 V rated value</li> <li>— at 220/230 V rated value</li> </ul> </li> </ul>   | 0.13 hp<br>0.33 hp<br><br>0.8 hp<br>0.75 hp                                  |

|   |  |
|---|--|
| — at 460/480 V rated value  | 2 hp   |
| — at 575/600 V rated value  | 3 hp   |
| <b>contact rating of auxiliary contacts according to UL</b>   | C300 / R300  |
| <b>Short-circuit protection</b>   |  |
| <b>product function short circuit protection</b>  | Yes  |
| <b>design of the short-circuit trip</b>   | magnetic   |
| <b>design of the fuse link</b><br>• for short-circuit protection of the auxiliary switch required   | fuse gG: 10 A, miniature circuit breaker C 6 A (short-circuit current I <sub>k</sub> < 400 A)  |
| <b>design of the fuse link for IT network for short-circuit protection of the main circuit</b><br>• at 240 V<br>• at 400 V<br>• at 500 V<br>• at 690 V  | none required<br>gL/gG 40 A<br>gL/gG 35 A<br>gL/gG 35 A  |
| <b>Installation/ mounting/ dimensions</b>   |  |
| <b>mounting position</b>  | any  |
| <b>fastening method</b>   | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 60715   |
| <b>height</b>   | 90 mm  |
| <b>width</b>  | 45 mm  |
| <b>depth</b>  | 75 mm  |
| <b>required spacing</b><br>• for grounded parts at 400 V<br>— downwards<br>— upwards<br>— at the side<br>• for live parts at 400 V<br>— downwards<br>— upwards<br>— at the side<br>• for grounded parts at 500 V<br>— downwards<br>— upwards<br>— at the side<br>• for live parts at 500 V<br>— downwards<br>— upwards<br>— at the side<br>• for grounded parts at 690 V<br>— downwards<br>— upwards<br>— backwards<br>— at the side<br>— forwards<br>• for live parts at 690 V<br>— downwards<br>— upwards<br>— backwards<br>— at the side<br>— forwards | 20 mm<br>20 mm<br>9 mm<br>20 mm<br>20 mm<br>9 mm<br>20 mm<br>20 mm<br>9 mm<br>20 mm<br>20 mm<br>9 mm<br>20 mm<br>20 mm<br>0 mm<br>9 mm<br>0 mm<br>20 mm<br>20 mm<br>0 mm<br>9 mm<br>0 mm |
| <b>Connections/ Terminals</b>   |  |
| <b>type of electrical connection</b><br>• for main current circuit<br>• for auxiliary and control circuit   | screw-type terminals<br>screw-type terminals   |
| <b>arrangement of electrical connectors for main current circuit</b>  | Top and bottom   |
| <b>type of connectable conductor cross-sections</b><br>• for main contacts<br>— solid or stranded<br>— finely stranded with core end processing   | 2x (0,5 ... 1,5 mm <sup>2</sup> ), 2x (0,75 ... 2,5 mm <sup>2</sup> ), 2x (1 ... 4 mm <sup>2</sup> )<br>2x (0,5 ... 1,5 mm <sup>2</sup> ), 2x (0,75 ... 2,5 mm <sup>2</sup> )            |

|   |   |
|---|---|
| <b>type of connectable conductor cross-sections</b><br>• for auxiliary contacts<br>— solid or stranded                          | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> ) |
| <b>tightening torque</b><br>• for main contacts with screw-type terminals<br>• for auxiliary contacts with screw-type terminals | 0.8 ... 1.2 N·m<br>0.8 ... 1.2 N·m                                    |
| <b>size of the screwdriver tip</b>  | Pozidriv size 2   |
| <b>design of the thread of the connection screw</b><br>• for main contacts<br>• of the auxiliary and control contacts           | M3<br>M3  |

**Safety related data**

|  |  |
|--|--|
| <b>B10 value</b><br>• with high demand rate according to SN 31920  | 5 000  |
| <b>proportion of dangerous failures</b><br>• with low demand rate according to SN 31920<br>• with high demand rate according to SN 31920 | 50 %<br>50 %                                     |
| <b>failure rate [FIT]</b><br>• with low demand rate according to SN 31920  | 50 FIT   |
| <b>protection class IP on the front according to IEC 60529</b>   | IP20   |
| <b>touch protection on the front according to IEC 60529</b>  | finger-safe, for vertical contact from the front |
| display version for switching status   | Rocker switch                                    |

**Certificates/ approvals**

|                                 |                                       |
|---------------------------------|---------------------------------------|
| <b>General Product Approval</b> | <b>For use in hazardous locations</b> |
|---------------------------------|---------------------------------------|



[Confirmation](#)



|                                       |                                  |                          |                          |
|---------------------------------------|----------------------------------|--------------------------|--------------------------|
| <b>For use in hazardous locations</b> | <b>Declaration of Conformity</b> | <b>Test Certificates</b> | <b>Marine / Shipping</b> |
|---------------------------------------|----------------------------------|--------------------------|--------------------------|



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



**Marine / Shipping**



|              |                |
|--------------|----------------|
| <b>other</b> | <b>Railway</b> |
|--------------|----------------|

[Confirmation](#)

[Miscellaneous](#)



[Special Test Certificate](#)

**Further information**

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3RV1011-1EA15>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV1011-1EA15>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RV1011-1EA15>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RV1011-1EA15&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV1011-1EA15&lang=en)

**Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current**

<https://support.industry.siemens.com/cs/ww/en/ps/3RV1011-1EA15/char>

**Further characteristics (e.g. electrical endurance, switching frequency)**

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RV1011-1EA15&objecttype=14&gridview=view1>

last modified:

6/25/2022 