



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

CHARACTERISTICS

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Olive drab Cadmium
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours
- Mass : 30.42 g ± 10%

| Connector dimension | |
|---------------------|-----------------|
| Dim | Nominal |
| A | 41.3±0.3 |
| B | 26.97+0.1/-0.15 |
| R | 32.5Max |
| S | 38.1±0.4 |
| W | 2.2+0.9/-0.1 |
| VV THREAD | M22x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| | |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR | Not Listed |

PN: 8D715W15AD

| | | | |
|----------------|---------------------------------------|--------------------------------|---|
| A | 08-11-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Aluminium Receptacle 8D series | | |
| SCALE | | General linear Tolerances: ±-- | NPRDS / PROJECT 859 |
| NA | | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| SOURIAU | WWW.SOURIAU.COM | | |
| FORMAT | SOURIAU DRG N° 8D715W15AD-C | | SHEET 1/2 |

| | | | | | | | | |
|----------------|------------------------|---|---|----|------------------------|----|---------------------------------|---|
| BASIC SERIES: | 8D | 7 | - | 15 | W | 15 | A | D |
| SHELL TYPE : | Jam nut Receptacle | | | | | | | |
| CONTACT TYPE : | Standard Crimp Contact | | | | | | | |
| SHELL SIZE : | 15 | | | | | | | |
| PLATING : | W = Olive drab Cadmium | | | | | | | |
| | | | | | ORIENTATION : D | | CONTACT TYPE : PIN(500 Matings) | |
| | | | | | CONTACT LAYOUT : 15-15 | | | |

Contact Layout



| Contacts (Insert arrangement 15-15) | | | | | |
|--|-------------|-------------|---------------------|-------------|-------------|
| Contact position ID | Location | | Contact position ID | Location | |
| | X-axis (mm) | Y-axis (mm) | | X-axis (mm) | Y-axis (mm) |
| A | +100 (2.54) | +225 (5.72) | J | -244 (6.20) | +014 (0.36) |
| B | +202 (5.13) | +140 (3.56) | K | -202 (5.13) | +140 (3.56) |
| C | +244 (6.20) | +014 (0.36) | L | -100 (2.54) | +225 (5.72) |
| D | +218 (5.54) | -113 (2.87) | M | +000 (0.00) | +140 (3.56) |
| E | +126 (3.20) | -209 (5.31) | N | +110 (2.79) | +040 (1.02) |
| F | +000 (0.00) | -245 (6.22) | P | +000 (0.00) | -077 (1.96) |
| G | -126 (3.20) | -209 (5.31) | R | -110 (2.79) | +040 (1.02) |
| H | -218 (5.54) | -113 (2.87) | | | |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 15 | -15 | 14 | 16 | I | P All other | MS20052-15 |

Panel cutout

JAM NUT RECEPTACLE (TYPE 7)



Max. thickness panel for receptacle: Type 7: 3.2 mm

| Dim | Nominal |
|-----|---------------|
| B | 27.56+0/-0.25 |
| ØC | 28.83+0.25/-0 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR | Not Listed |

PN: 8D715W15AD

| | | | |
|----------------|------------------------------------|----------------------------|---|
| A | 08-11-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Aluminium Receptacle 8D series | | |
| SCALE | | General linear Tolerances: | NPRDS / PROJECT |
| NA | | ±-- | 859 |
| SOURIAU | WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | SOURIAU DRG N° 8D715W15AD-C | | SHEET 2/2 |