

THIS SERIES FULLY CONFORMS TO


THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

2

J

COMPLIANT






N	0	TE	ES	

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATE	
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	30A (CURRENT) 5A PER CONTACT 10m0 MAX	
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.	Ð

WITHSTANDING VOLTAGE:

1000V AC rms



		SW REFERENCE NO.: 630 COMBO ASSEMBLY			
			DRAWN: C.B	DATE: JAN. 01/20	19
			CHECKED:	DATE:	
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
YOUR CONNECTION TO	TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 630-3WK3240-3N1		ISSUE
	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-3WK	3240-3N1	1

