


## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED



## OPERATING TEMPERATURE: -55°C ~ 125°C


.XX ±0.13

.XXX ±0.05


POWER/CO-AX CONTACT RATING:20A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:





|  |                                      |   | SW REFERENCE NO.: 630 COMBO ASSEMBLY |                  |       |
|--|--------------------------------------|---|--------------------------------------|------------------|-------|
|  |                                      |   | DRAWN: C.B                           | DATE: JAN. 01/20 | 19    |
|  |                                      |   | CHECKED:                             | DATE:            |       |
|  | EDAC INC                             | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND  | SCALE: (IN C.A.D. 1:1)               | SHEET 1 OF       | 2     |
|  | YOUR CONNECTION TO QUALITY & SERVICE | SHALL NOT BE REPRODUCED, OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | DRAWING NUMBER: 630-9W4-250-2T4      |                  | ISSUE |
|  |                                      |   | PART NUMBER: 630-9W4-                | 250-2T4          | 1     |





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

