



MGV06038R2M-12

PHYSICAL DIMENSIONS:

A	7.30	±	0.50
B	6.70	±	0.40
C	3.00	±	0.40
D	3.00	±	0.30
E	1.80	±	0.30



LAND PATTERNS FOR REFLOW SOLDERING



ELECTRICAL SPECIFICATION @ 25°C


	Min	Norm	Max
INDUCTANCE (uH) L @ 100 KHz/0.25V ± 20%	6.56	8.20	9.84
DCR (Ω)			0.068

Saturation Current ³ Isat (A)	7.50
Temperature Rise Current Irms ⁴ (A)	4.00



NOTES: UNLESS OTHERWISE SPECIFIED

- COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
- OPERATION TEMPERATURE RANGE:
-55°C~+125°C (INCLUDING SELF-HEATING) .
- SATURATION CURRENT Isat IS DEFINED AS MAXIMUM AMOUNT OF CURRENT BY WHICH INDUCTANCE WILL DROP BY APPROXIMATELY VALUE OF 30% OF INITIAL INDUCTANCE (Ta=25±5°C).
- DEFINITION OF TEMPERATURE RISE CURRENT (IRMS):
DC CURRENT THAT CAUSES THE TEMPERATURE RISE (ΔT APPROXIMATELY 40°C) FROM 25°C AMBIENT.

DIMENSIONS ARE IN mm.				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.	
					
PROJECT/PART NUMBER:				REV	PART TYPE:
MGV06038R2M-12				A	POWER INDUCTOR
DATE:				SCALE:	DRAWN BY:
08/17/18				NTS	Jonson
REV	DESCRIPTION	DATE	INT	CAD #	TOOL #
A	ORIGINAL DRAFT	08/17/18	Jonson		
				MGV06038R2M-12-A	
				SHEET:	
				1 of 1	