

## Single relay - REL-IR/LDP- 48DC/2X21 - 2834038

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Pluggable industrial relays with power contacts, 2 PDT, test button, status LED, free-wheeling diode, mechanical switch position indicator, polarity A1+, A2-, input voltage 48 V DC

The figure shows version: REL-IR/  
LDP- 24DC/2X21



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	38.5 g
Custom tariff number	85364190
Country of origin	Japan

### Technical data

#### Dimensions

Width	21.5 mm
Height	28 mm
Depth	36 mm

#### Ambient conditions

Ambient temperature (operation)	-55 °C ... 70 °C
Ambient temperature (storage/transport)	-55 °C ... 70 °C

#### Coil side

Nominal input voltage $U_N$	48 V DC
Typical input current at $U_N$	19 mA
Typical response time	13 ms
Typical release time	5 ms
Coil resistance	2560 $\Omega$ $\pm$ 15 % (at 20 °C)

# Single relay - REL-IR/LDP- 48DC/2X21 - 2834038

## Technical data

### Coil side

Power dissipation for nominal condition	0.91 W
---	--------

### Contact side

Contact type	2 PDT
Contact material	Ag
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	5 V
Min. switching current	1 mA
Maximum inrush current	20 A (15 ms)
Limiting continuous current	10 A
Interrupting rating (ohmic load) max.	2500 VA (for 250 V AC)

### Connection data input side

Connection name	Coil side
Connection method	Plug / solder connection

### Connection data output side

Connection name	Contact side
Connection method	Plug / solder connection

### General

Test voltage relay winding/relay contact	2 kV AC (50 Hz, 1 min.)
Test voltage relay contact/relay contact	2 kV AC (50 Hz, 1 min.)
Operating mode	100% operating factor
Mechanical service life	5 x 10 <sup>7</sup> cycles
Standards/regulations	DIN EN 61810-1
	VDE 0435-201
	EN 50178
	IEC 62103
Degree of pollution	2
Overvoltage category	II
Mounting position	any
Assembly instructions	On relay base PR2

### Standards and Regulations

Standards/regulations	DIN EN 61810-1
	VDE 0435-201
	EN 50178
	IEC 62103
Degree of pollution	2

# Single relay - REL-IR/LDP- 48DC/2X21 - 2834038

## Technical data

### Standards and Regulations

Overvoltage category	II
----------------------	----

## Classifications

### eCl@ss

eCl@ss 4.0	27371104
eCl@ss 4.1	27371104
eCl@ss 5.0	27371001
eCl@ss 5.1	27371001
eCl@ss 6.0	27371001
eCl@ss 7.0	27371001
eCl@ss 8.0	27371601
eCl@ss 9.0	27371601

### ETIM

ETIM 2.0	EC000196
ETIM 3.0	EC000196
ETIM 4.0	EC000196
ETIM 5.0	EC001437

### UNSPSC

UNSPSC 6.01	30211916
UNSPSC 7.0901	39121515
UNSPSC 11	39121515
UNSPSC 12.01	39121515
UNSPSC 13.2	39121515

## Approvals

### Approvals

---

#### Approvals

UL Listed / VDE Gutachten mit Fertigungsüberwachung / cUL Listed / EAC / EAC / cULus Listed

---

#### Ex Approvals

---

# Single relay - REL-IR/LDP- 48DC/2X21 - 2834038

## Approvals

Approvals submitted

### Approval details

UL Listed

VDE Gutachten mit Fertigungsüberwachung

cUL Listed


EAC

EAC

cULus Listed


## Drawings

Diagram



Operating voltage range


Diagram



AC interrupting rating


# Single relay - REL-IR/LDP- 48DC/2X21 - 2834038

Diagram




DC interrupting rating

Diagram




Electrical service life

Diagram



Service life reduction factor

Circuit diagram



Shown without LED and damping diode.  
Contacts 21, 22, 24 are led onto relay socket connections 41, 42, 44.