<u>Contact Dimensions:</u>
500-Wire Hole .050x.025(1.27x0.64) - Tail LG=.260(6.60)
.100 (2.54) Contact Spacing x .200 (5.08) Row Spacing 1 -2x Ø.156[3.96] CARD SLOT ACCEPTS .054" [1.37] TO .070"[1.78] THICK PCB 6.700 170.18 6.860 174.24 POINT OF CONTACT 330[8.38] CARD SLOT 160 4.06 EDRG 600 [15.24] **SECTION A-A** -7.435[188.85] 345-ENG-MASTER 345/395 SERIES CARD EDGE CONNECTOR DRAWN: R.STA.MONICA DATE:MAY.16/2017 PART NUMBER: 345-132-500-278 INSULATOR MATERIAL: THERMOPLASTIC PBT BLACK, UL 94V-0 1:1 SHEET 1 OF 2 CONTACT MATERIAL; COPPER TIN ALLOY CONTACT PLATING: GOLD ON THE MATING AREA, TIN PLATING

YOUR CONNECTION TO QUALITY & SERVICE

345-ENG-MASTER

ON THE CONTACT TAILS, NICKEL UNDERPLATE









Contact Code 558

Contact Code 559

Contact Code 560

INSULATOR MATERIAL: THERMOPLASTIC POLYESTER, UL 94V-0

DAP MATERIAL AVAILABLE UPON REQUEST

CONTACT MATERIAL; COPPER ALLOY CONTACT PLATING: GOLD ON THE MATING AREA, TIN PLATING ON THE CONTACT TAILS, NICKEL UNDERPLATE

345/395 SERIES CARD EDGE CONNECTOR CONTACT CODE 555,556,558,559,560 DIMENSIONS

YOUR CONNECTION TO QUALITY & SERVICE

ACAD REFERENCE NO. 345-ENG-MASTER DATE:MAY.16/2017 DRAWN: R.STA.MONICA 1:1 SHEET 2 OF 2 345-ENG-MASTER