

ITEM	PART#	DESCRIPTION	QTY	UOM
A,B	436400500	MicroFit 3.0 Plug SR Pnl Mnt 5Ckt	2	PC
C	430310023	MICROFIT 3.0 M CRP TERM CHN 30AU 18AWG	10	PC
D	--	PAPER PRINTED PAPER WHITE	1	PC

FROM	TO	DESCRIPTION	COLOR
A1	B5	1X18AWG DISC SR-PVC BK UL10002	BLACK
A2	B4	1X18AWG DISC SR-PVC BK UL10002	BLACK
A3	B3	1X18AWG DISC SR-PVC BK UL10002	BLACK
A4	B2	1X18AWG DISC SR-PVC BK UL10002	BLACK
A5	B1	1X18AWG DISC SR-PVC BK UL10002	BLACK




TABLE			
PART NUMBER	L1	L2	TITLE
2147522051	150±8	63 REF	MICROFIT 3.0 SR P-P 5CKT 150 MM Au
2147522052	300±10	138 REF	MICROFIT 3.0 SR P-P 5CKT 300 MM Au
2147522053	600±10	288 REF	MICROFIT 3.0 SR P-P 5CKT 600 MM Au

- NOTES**
1. Cable assembly must pass 100% continuity and polarity test.
  2. Connector view shown is from mating side.
  3. Label text must be 2mm max. in height with Arial font.
  4. Label must be wrapped in Flag type on a single cable.

MOLEX P/N  
 MOLEX  
 BATCH WK/YR  
 DETAIL A

REVISION			
DATE	REV	DESCRIPTION	CHANGER
2020/02/29	A	INITIAL RELEASE	ARAJU

FUNCTIONAL SYMBOLS $\frac{E}{A} = 0$ $\frac{E}{E} = 0$ $\frac{E}{P} = 0$ DIVISIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:		
	DIMENSION UNITS	SCALE	GENERAL TOLERANCES (UNLESS SPECIFIED)		
	mm	NTS	ANGULAR TOL ± °		
	4 PLACES ±		3 PLACES ±		
3 PLACES ±		2 PLACES ±		EC NO: 637489	PRODUCT CUSTOMER DRAWING
2 PLACES ±		1 PLACE ±		DRWN: ARAJU 2020/03/02	
1 PLACE ±		0 PLACES ±		CHK'D: RDESAI01 2020/05/14	DOCUMENT NUMBER <b>2147522051</b>
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	APPR: RDESAI01 2020/05/14	
			A4-SIZE	SERIES 214752	MATERIAL NUMBER SEE TABLE
				CUSTOMER GENERAL MARKET	SHEET NUMBER 1 OF 1

DOCUMENT STATUS	P1	RELEASE DATE	2020/05/14	03:37:10
-----------------	----	--------------	------------	----------