

# 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

## 1. Product Number

H 2 U 6 6 K 1 K 2 J 0 1 0 0



## 2. Features

- \*Stable and reliable in performances
- \*Low profile, compact size
- \*RoHS 2.0 compliance
- \*SMT processes compatible

## 3. Applications

- \*Smart meters
- \*Wireless alarm and security system
- \*Industrial monitoring and control
- \*Machine to machine data communication
- \*433/450/470/510 MHz ISM Band applications
- \*LTE band 31
- \*LPD433

## 4. Description

Unictron's C420D5 chip antenna is designed for ISM 433/450/470/510 MHz bands applications, covering frequencies 433 MHz or 450~470 MHz or 470~510 MHz. Fabricated with proprietary design and processes, C420D5 shows excellent performance and is fully compatible with SMT processes which can decrease the assembly cost and improve device's quality and consistency.

## 5. Layout Guide & Electrical Specifications

Unictron  
Technologies Corp.  
**2019-04-17**  
Document  
Control Center



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : **Wen**      Designed by : **Peter**      Checked by : **Mike**      Approved by : **Herbert**

**TITLE** : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

**DOCUMENT NO.**


**H2U66K1K2J0100**

**REV.**  
**G**


### 5-1. Layout Guide (unit : mm)

#### Solder Land Pattern:

The solder land pattern (gold marking areas) is shown below. Recommendation on matching circuit will be provided according to customer's installation conditions.



**Transmission Line with 50Ω Impedance Characteristic Top View**



**Bottom View**

### 5-2. Electrical Specifications (Evaluation Board Dimensions: 80 x 40 mm<sup>2</sup>)



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Wen

Designed by : Peter

Checked by : Mike

Approved by : Herbert

**TITLE** : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

**DOCUMENT NO.**

**H2U66K1K2J0100**

**REV.**  
**G**

5-2-1. Electrical Table (\*for 433 MHz band applications)

Characteristics		Specifications	Unit
Outline Dimensions		20.0 x 5.0 x 1.6	mm
Ground Plane Dimensions		55.75 x 40	mm
Working Frequency		433.05 ~ 434.79	MHz
VSWR(@ center frequency)*		2 Max.	
Characteristic Impedance		50	Ω
Polarization		Linear Polarization	
Peak Gain	(@433 MHz)	-0.2 (typical) **	dBi
Efficiency		32 (typical) **	%

\*Center frequency means the frequency with the lowest value in return loss of the chip antenna on the evaluation board.

\*\*A typical value is for reference only, not guaranteed.

5-2-2. Electrical Table (\*for 450~470 MHz band applications)

Characteristics		Specifications	Unit
Working Frequency		450 ~ 470	MHz
VSWR(@ center frequency)*		2.5 Max.	
Characteristic Impedance		50	Ω
Polarization		Linear Polarization	
Peak Gain	(@460 MHz)	-0.2 (typical) **	dBi
Efficiency		35 (typical) **	%

\*Center frequency means the frequency with the lowest value in return loss of the chip antenna on the evaluation board.

\*\*A typical value is for reference only, not guaranteed.



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : **Wen**      Designed by : **Peter**      Checked by : **Mike**      Approved by : **Herbert**

**TITLE** : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

**DOCUMENT NO.**

**H2U66K1K2J0100**

**REV.**  
**G**

5-2-3. Electrical Table (\*for 470~510 MHz band applications)

Characteristics		Specifications	Unit
Working Frequency		470 ~ 510	MHz
VSWR(@ center frequency)*		2.5 Max.	
Characteristic Impedance		50	$\Omega$
Polarization		Linear Polarization	
Peak Gain	(@490 MHz)	-0.2 (typical) **	dBi
Efficiency		34 (typical) **	%

\*Center frequency means the frequency with the lowest value in return loss of the chip antenna on the evaluation board.

\*\*A typical value is for reference only, not guaranteed..

\*C420D5 can be implemented for 433MHz / 450MHz / 470 MHz/ 510 MHz with specific matching components.

The specific matching components will be defined base on the environment of cases or devices.



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : **Wen**      Designed by : **Peter**      Checked by : **Mike**      Approved by : **Herbert**

**TITLE** : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

**DOCUMENT NO.**



**H2U66K1K2J0100**

**REV.**  
**G**

5-2-4. Return Loss & VSWR for 433 MHz Band

Return Loss (S<sub>11</sub>)



VSWR (S<sub>11</sub>)



5-2-5. Return Loss & VSWR for 450~470 MHz Band

Return Loss (S<sub>11</sub>)



VSWR (S<sub>11</sub>)



5-2-6. Return Loss & VSWR for 470~510 MHz Band

Return Loss (S<sub>11</sub>)

VSWR (S<sub>11</sub>)



Unictron Technologies Corp.  
2019-04-17  
Document Control Center



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Wen

Designed by : Peter

Checked by : Mike

Approved by : Herbert

TITLE : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification


DOCUMENT NO.

H2U66K1K2J0100

REV. G

## 6. Outline Dimensions of Antenna & Evaluation Board (unit: mm)


### 6-1. Antenna Dimensions



**NOTE:**

1. All materials are RoHS 2.0 compliant.
2. " $\textcircled{A}$ ~ $\textcircled{C}$ " Critical Dimensions.
3. " $\langle \quad \rangle$ " Reference Dimensions.

### PIN Definitions



PIN	1	2 ~3
Soldering Pad	Signal	N/C



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : **Wen**      Designed by : **Peter**      Checked by : **Mike**      Approved by : **Herbert**


**TITLE :** 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

**DOCUMENT NO.**

**H2U66K1K2J0100**

**REV.**  
**G**

6-2. Evaluation Board with Antenna



unit : mm



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Wen

Designed by : Peter

Checked by : Mike

Approved by : Herbert

TITLE : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

DOCUMENT NO.





H2U66K1K2J0100

REV. G

## 7. Radiation Pattern (with 80 x 40 mm<sup>2</sup> Evaluation Board)

### 7-1. 433 MHz Band

#### 7-1-1. 3D Radiation Gain Pattern @ 433 MHz (unit: dBi)



詠業科技股份有限公司  
Unicon Technologies Corporation  
Website: www.unicon.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Wen

Designed by : Peter

Checked by : Mike

Approved by : Herbert

TITLE : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

DOCUMENT NO.

H2U66K1K2J0100

REV.


G



7-1-2. 3D Efficiency Table

Frequency (MHz)	428	429	430	431	432	433	434	435	436	437	438
Efficiency (dB)	-5.2	-5.2	-5.1	-5.1	-5.0	-4.9	-5.1	-5.1	-5.2	-5.3	-5.3
Efficiency (%)	29.9	30.2	30.6	30.9	31.4	32.2	31.2	30.8	29.9	29.2	29.5
Peak Gain (dBi)	-0.7	-0.2	0.0	-0.2	0.1	-0.2	-0.4	-0.8	-0.7	-0.8	-0.9

7-1-3. 3D Efficiency vs. Frequency



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : **Wen**      Designed by : **Peter**      Checked by : **Mike**      Approved by : **Herbert**

TITLE : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification





DOCUMENT NO.

**H2U66K1K2J0100**

REV.  
**G**

7-2. 450 ~ 470 MHz Band

7-2-1. 3D Radiation Gain Pattern @ 460 MHz (unit: dBi)



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Wen

Designed by : Peter

Checked by : Mike

Approved by : Herbert

TITLE : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

DOCUMENT NO.


H2U66K1K2J0100

REV. G

7-2-2. 3D Efficiency Table

Frequency (MHz)	450	452	454	456	458	460	462	464	466	468	470
Efficiency (dB)	-5.1	-5.1	-5.0	-4.7	-4.5	-4.5	-4.6	-4.8	-5.0	-5.0	-5.4
Efficiency (%)	30.7	31.2	31.6	34.0	35.8	35.6	34.9	33.1	31.4	31.4	29.0
Peak Gain (dBi)	-0.5	-0.4	-0.4	-0.3	-0.3	-0.2	-0.2	-0.3	-0.4	-0.3	-0.5

7-2-3. 3D Efficiency vs. Frequency



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Wen

Designed by : Peter

Checked by : Mike

Approved by : Herbert

TITLE : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

DOCUMENT NO.





H2U66K1K2J0100

REV.

G

### 7-3. 470 ~ 510 MHz Band

#### 7-3-1. 3D Radiation Gain Pattern @ 490 MHz (unit: dBi)



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Wen

Designed by : Peter

Checked by : Mike

Approved by : Herbert

TITLE : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

DOCUMENT NO.


H2U66K1K2J0100

REV. G

7-3-2. 3D Efficiency Table

Frequency (MHz)	470	475	480	485	490	495	500	505	510
Efficiency (dB)	-6.3	-5.7	-5.2	-4.9	-4.7	-4.8	-4.8	-5.2	-5.6
Efficiency (%)	23.5	26.8	30.3	32.6	34.3	33.0	33.1	30.3	27.6
Peak Gain (dBi)	-1.7	-1.3	-1.0	-0.6	-0.2	-0.1	0.1	-0.2	-0.6

7-3-3. 3D Efficiency vs. Frequency



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : **Wen**      Designed by : **Peter**      Checked by : **Mike**      Approved by : **Herbert**

**TITLE** : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification


**DOCUMENT NO.**

**H2U66K1K2J0100**

**REV.**  
**G**


## 8. Frequency tuning

### 8-1. Chip antenna tuning scenario :



### 8-2. Matching circuit :

With the following recommended values of matching, the covering frequencies will be about 433 MHz at our standard 80 x 40 mm<sup>2</sup> evaluation board. However, these are typical reference values which may need to be changed when circuit boards or part vendors are different.



System Matching Circuit Component			
Location	Description	Vendor	Tolerance
1	N/A	-	-
2	0Ω, (0402)	-	-
3	N/A	-	-
4	Fine tuning element 0.4pF, (0402)	MURATA	±0.05pF
5	Fine tuning element 56nH, (0402)	MURATA	±3%

Unictron  
Technologies Corp.  
2019-04-17  
Document  
Control Center



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Wen

Designed by : Peter

Checked by : Mike

Approved by : Herbert


TITLE : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

DOCUMENT NO.

H2U66K1K2J0100

REV.  
G

## 9. Soldering Conditions



\*Recommended solder paste alloy: SAC305 (Sn96.5 /Ag3 /Cu0.5) Lead Free solder paste.



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Wen

Designed by : Peter

Checked by : Mike

Approved by : Herbert

TITLE : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

DOCUMENT NO.


H2U66K1K2J0100

REV.  
G

## 10. Packing

- (1) Quantity/Reel: 2500 pcs/Reel
- (2) Plastic tape: Black Conductive Polystyrene.

a. Tape Drawing



b. Tape Dimensions (unit: mm)

Feature	Specifications	Tolerances
W	32.00	±0.30
P	8.00	±0.10
E	1.75	±0.10
F	14.20	±0.10
P2	2.00	±0.10
D	1.50	+0.10 -0.00
D1	1.50	±0.10
Po	4.00	±0.10
10Po	40.00	±0.20

## 11. Operating & Storage Conditions

### 11-1. Operating

- (1) Maximum Input Power: 2 W
- (2) Operating Temperature: -40°C to 85°C
- (3) Relative Humidity: 10% to 70%

### 11-2. Storage (sealed)

- (1) Storage Temperature: -5°C to 40°C
- (2) Relative Humidity: 20% to 70%
- (3) Shelf Life: 1 year

### 11-3. Storage (unsealed)

Meet the criteria of J-STD-033 MSL2a

### 11-4. Storage (After mounted on customer's PCB with SMT process)

- (1) Storage Temperature: -40°C to 85°C
- (2) Relative Humidity: 10% to 70%



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Wen

Designed by : Peter

Checked by : Mike

Approved by : Herbert

TITLE : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip  
Antenna (C420D5) Engineering Specification

DOCUMENT  
NO.

H2U66K1K2J0100

REV.  
G



## 12. Notice

(1) Installation Guide:

Please refer to Unictron's application note "General guidelines for the installation of Unictron's chip antennas" for further information.

(2) All specifications are subject to change without notice.



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : **Wen**

Designed by : **Peter**

Checked by : **Mike**

Approved by : **Herbert**

**TITLE** : 20.0 x 5.0 x 1.6 (mm) ISM 433/450/470/510 MHz Chip Antenna (C420D5) Engineering Specification

**DOCUMENT NO.**

**H2U66K1K2J0100**

**REV.**  
**G**