

Data sheet | Item number: 756-5401/050-020




Sensor/Actuator cable; M12A socket; straight; M12A plug; straight; 5-pole;
Length: 2 m



www.wago.com/756-5401/050-020



 Picture differs from the item.



Item description

Short description:

- PUR, halogen-free
- Suitable for drag chains
- High resistance to microbes, hydrolysis, oil, chemicals and UV radiation
- High chemical resistance
- Cable used: UL listed

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Data

Technical data

General

Operating voltage	250 VAC/DC
Operating current	4 A
Rated surge voltage	1.5 kV
Contact resistance	10 mΩ
Conductor resistance	≤ 60 Ω/km
Pollution degree	3 per VDE 0110
Protection type	IP67
Ambient (operating) temperature (static)	-50 ... +90 °C
Ambient (operating) temperature (dynamic)	-25 ... +90 °C

Suitable for drag chains

Bending radius	10 x cable diameter (min.)
Bending cycles	2 Mio.
Acceleration (min.)	5
Travel speed (max.)	3.33
Travel path (horizontal) max.	5
Travel path (vertical) max.	2
Torsional capacity	180

Cable

Cable length	2 m
Type code	LiF9YH-11YH or LiF9YC11YFHF
Conductor configuration	Bare copper wire, fine-stranded (42 x 0.1 mm)
Conductor insulation	PP9Y (halogen-free)
Sheath material	Polyurethane (PUR), halogen-free per DIN VDE 0472 Part 815, flame resistant per IEC 332-2, self-extinguishing
Sheathed cable color	black
Sheathed cable diameter	4.8 ... 5.2 mm

Connector

Connection type	M12 Socket - M12 plug
Cable connection direction to mating direction	0°
Cable connection direction to mating direction (2)	0°

Subject to changes. Please also observe the further product documentation!



Connector interface coding (cable/adapter) 1 1	A-coded
Connector interface coding (cable/adapter) 2 1	A-coded
Housing material	Polyurethane (PUR)
Contact material	CuSn
Tightening torque	1 Nm

Commercial data

eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	10 (1) pcs
Packaging type	Box
Country of origin	HU
GTIN	4044918975629
Customs tariff number	85444290900

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	82812c3a-f96a-4278-b718-63eb45acebe4
SCIP notification number (Belgium)	69499b23-ac34-4e3b-b453-18416917ac6f
SCIP notification number (Bulgaria)	da8859b5-3147-4f54-8a1f-0dd5918d72ab
SCIP notification number (Czech Republic)	1c833606-3bee-49e8-9b1c-a23aa88dc406
SCIP notification number (Denmark)	973080f8-fc27-423f-a367-7f8fc24ee09f
SCIP notification number (Finland)	f43c5598-2775-4e81-b43b-01b31a6c204b
SCIP notification number (France)	766d6309-4139-405f-9a2b-3b065c153a0a
SCIP notification number (Germany)	65c5d823-89dc-495c-9546-3fb638b75eb7
SCIP notification number (Hungary)	ce2c9b32-e830-4e15-a916-77a4e3df71ba
SCIP notification number (Italy)	4131a34a-80e6-4431-b83d-35f90ed908a5
SCIP notification number (Netherlands)	33f9fba7-63c7-4706-867d-955aa7528570
SCIP notification number (Poland)	683e2ccd-dc45-4e70-9cb2-bda6401ba763
SCIP notification number (Romania)	fd80b9d2-e563-44e9-b059-0cd046d8c850
SCIP notification number (Sweden)	35abedb8-a47c-430e-8559-4638c33c015e


Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL Underwriters Laboratories Inc.	UL 2238	E519602

Downloads

Documentation

Bid Text

756-5401/050-020 X81 - Datei	2019 Feb 19	xml 3.3 kB	Download
756-5401/050-020 doc - Datei	2017 Sep 20	doc 27.1 kB	Download

System Description

IP67 Cables and Pluggable Connectors	pdf 161.6 kB	Download
--------------------------------------	-----------------	----------

CAD/CAE-Data

CAE data

WSCAD Universe 756-5401/050-020	URL	Download
WSCAD Universe 756-5401/050-020	URL	Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 756-5401/050-020 Sensor/Actuator cable; M12A socket; straight; M12A plug; straight; 5-pole; Length: 2 m	URL	Download
---	-----	----------

Subject to changes. Please also observe the further product documentation!



Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.