




1






UNLESS OTHERWISE SPECIFIED		D
.X.	±0.25	
.XX	±0.13	
.XXX	±0.05	



NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYES STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLI	,
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	30A (CURRENT)	
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.	
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.	
WITHSTANDING VOLTAGE:	1000V AC rms	

COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY			
		DRAWN: C.B	DATE: JAN. 01/20	19	
		CHECKED:	DATE:		
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 630-5W1-650-3N2		ISSUE	
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-5W1	-650-3N2	1	





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

