ت 	m m		0	Φ	⊳	
A A						4
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Keying Shown as example Connector dimension Dim Nominal		LAYOUT SHOWN A	AS EXAMPLE		3
-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered without Souriau contacts	ØS25 MaxZ31 MaxVV THREADM15x1-6g		Cou	s which does not comply wi er of the Parties or by a thir ndation, technical notice.) untry Jurisdiction 8 FR Not L	th d party & Control List	2
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours -Mass : 16.32 g ± 10%		A 18-10-201 ISS DATE Designed By:	6 First Release Latest modification - by Date:	CUST	MOD N°	
SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	CONTACT TYPE : SOCKET(50	TATION : D 0 Matings)	General linea Tolerances: ±	J.COM	RDS / PROJECT 859 his document is the property of SOURIAU it must not be reproduced or mmunicated without permission	1
PLATING : Z = Black Zinc Nickel	F E	DUT:11-01 A3 D		AU DRG N° Z01SDL-C B	A SHEET	

	т	G	нт — — — — — — — — — — — — — — — — — — —	т	U	0
		Contact Layout				
4		01				
	(1#12 11-01	1			
ω	Ctc A	X Y 0 0				
	-					SOURIAU shall not be liable for any due to a use of the Products wh
N						the Specifications issued by either of (professional recommendat Countr FR PN: 8D511Z
					A 18-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
<u> </u>					SCALE NA	Alumin General linear Tolerances: ±
					FORMAT A3	J WWW.SOURIAU.C SOURIAU 8D511Z0
l	Н	G	F	E	D	С

B		А				
				4		
				3		
any non-conformit which does not co r of the Parties or I dation, technical n ntry Jurisc R LZO1SDL	mply with by a third part			2		
	CUSTOME	R DRAWING	MOD N°			
inium Plug 8D series						
r	NPRDS / PROJECT 859					
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
U DRG N° 201SDL-C			SHEET 2/2			
В		А		I		