

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
A		INITIAL RELEASE	06APR2015	GY	CW
B		ECR-15-013759	12OCT2015	DW	CW
B1		ECR-16-015492	16NOV2016	QY	CW
C		ECR-21-106515	09JUL2021	SQ	CW

PANEL CUT FOR INSERTS FOR USING  
WITHOUT HOODS/ HOUSINGS

不使用防护外壳时芯件的安装开孔图

4X M3 SCREW, RECOMMENDED  
TIGHTENING TORQUE 0.5Nm  
4X M3螺丝, 推荐锁紧力矩0.5Nm

M4 SCREW, RECOMMENDED  
TIGHTENING TORQUE 1.2Nm  
M4螺丝, 推荐锁紧力矩1.2Nm


NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 500V  
RATED CURRENT: 16A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 6KV  
POLLUTION DEGREE: 3  
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
WIRE RANGE:  $0.14mm^2 \sim 4mm^2$  (AWG26-AWG12)  
CONTACT TYPE: CRIMP CONTACT
- CONTACTS NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING: T20300X20XX000)

注释:

- 技术参数:  
绝缘材料: PC  
额定电压: 500V  
额定电流: 16A  
绝缘电阻:  $\geq 400M\Omega$   
脉冲电压: 6KV  
污染等级: 3  
阻燃等级: UL94V-0  
插拔次数: 500次  
接线范围:  $0.14mm^2 \sim 4mm^2$  (AWG26-AWG12)  
接线类型: 冷压接
- 端子需要单独订购。  
(订货号参考图面: T20300X20XX000)

TYPE-1, T2040064201-000, TE LOGO  
类型-1, T2040064201-000, TE LOGO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Gino.Yao 06APR2015		 TE Connectivity	
DIMENSIONS: mm		CHK Chris.Wang 06APR2015			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD Xiang.Xu 06APR2015		NAME HE-006-FC	
0 PLC $\pm$		PRODUCT SPEC 108-137044		SIZE	
1 PLC $\pm$		APPLICATION SPEC 114-137044		CAGE CODE	
2 PLC $\pm$		WEIGHT -		DRAWING NO	
3 PLC $\pm$		Customer Drawing		A300779	
4 PLC $\pm$		SCALE 1:1		SHEET 1 OF 2	
ANGLES $\pm$		RESTRICTED TO -		REV C	
FINISH -					
MATERIAL -					

1470-19 (3/13)

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

REVISIONS

© COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

P	LTR	DESCRIPTION	DATE	DWN	APVD
-		SEE SHEET 1	-	-	-

NOTE:  
SEE SHEET 1

注释:  
见页 1

TYPE-2, T2040064201-001, STAINLESS STEEL SCREW, NO LOGO  
类型-2, T2040064201-001, 不锈钢螺丝, 无LOGO

ALL SPEC DIMENSION REFER TO TYPE 1  
所有产品规格尺寸参照 TYPE 1

T2040064201-001	HE-006-FC	HE-006 FEMALE INSERT, CRIMPING, STAINLESS STEEL SCREW, NO LOGO HE-006母插, 冷压针, 不锈钢螺丝, 无LOGO	TYPE-2 类型-2
T2040064201-000	HE-006-FC	HE-006 FEMALE INSERT, CRIMPING HE-006母插, 冷压针	TYPE-1 类型-1
PART NUMBER 料号	PART DESCRIPTION 描述		TYPE 类型

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Gino.Yao 06APR2015					
DIMENSIONS: mm		CHK Chris.Wang 06APR2015					
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD Xiang.Xu 06APR2015					
		PRODUCT SPEC 108-137044	NAME HE-006-FC				
MATERIAL -		FINISH -	APPLICATION SPEC 114-137044	SIZE A3	CAGE CODE 00779	DRAWING NO T2040064201000	RESTRICTED TO -
-		Customer Drawing	WEIGHT -	SCALE 1:1	SHEET 2 OF 2	REV C	

1470-19 (3/13)